

An Antimicrobial Copper–Plastic Composite Coating: Characterization and In Situ Study in a Hospital Environment

Alexandre M. Emelyanenko ^{1,*}, Fadi S. Omran ¹, Maria A. Teplonogova ², Marina Y. Chernukha ^{1,3}, Lusine R. Avetisyan ^{1,3}, Eugenia G. Tselikina ³, Gleb A. Putsman ^{1,4}, Sergey K. Zyryanov ^{1,5}, Olga I. Butranova ^{1,5}, Kirill A. Emelyanenko ¹, Ludmila B. Boinovich ^{1,*}

¹ A. N. Frumkin Institute of Physical Chemistry and Electrochemistry, Russian Academy of Sciences, Leninsky Prospekt 31, 119071 Moscow, Russia

² N. S. Kurnakov Institute of General and Inorganic Chemistry, Leninsky Prospekt 31, 119071 Moscow, Russia;

³ Department of Medical Microbiology, Gamaleya National Research Center for Epidemiology and Microbiology, Ministry of Health of the Russian Federation, 18 Gamaleya St., 123098 Moscow, Russia

⁴ City Clinical Hospital No. 24, Moscow City Health Department, 10 Pistsovaya St., 127015 Moscow, Russia

⁵ Department of General and Clinical Pharmacology, Institute of Medicine, Peoples' Friendship University of Russia named after Patrice Lumumba, 6 Miklukho-Maklaya St. 117198 Moscow, Russia

* Correspondence: ame@phych.ac.ru (A.M.E.); boinovich@mail.ru (L.B.B.); Tel.: +7-495-955-4625 (A.M.E.)




Figure S1. Typical EDS spectra of the ABS plastic switch after application of a copper coating.



Figure S2. Electric light switch: left paired buttons were coated with a copper layer whereas the right single button was uncoated common ABS plastic.