

Effects of Heat Treatment on the Microstructure and Mechanical Properties of a Dual-Phase High-Entropy Alloy Fabricated via Laser Beam Power Bed Fusion

Xiaojun Tan ^{a,b,c,d}, Zihong Wang ^e, Haitao Chen ^b, Xuyun Peng ^b, Wei Zhang ^c, Haibing Xiao ^{c,*}, Zhongmin Liu ^{a,d}, Yu Hu ^{f,g}, Liang Guo ^{a,d,*}, Qingmao Zhang ^{a,d}

^a Guangdong Provincial Key Laboratory of Nanophotonic Functional Materials and Devices, School of Information and Optoelectronic Science and Engineering, South China Normal University, Guangzhou, 510006, China

^b Sino-German Intelligent Manufacturing school, Shenzhen Institute of Technology, 518116, China

^c Intelligent Manufacturing and Equipment School, Shenzhen Institute of Information Technology, Shenzhen, 518172, China

^d Guangdong Provincial Key Laboratory of Industrial Ultrashort Pulse Laser Technology, Shenzhen, 518055, China

^e College of Materials Science and Engineering, Chongqing University, Chongqing 400045, China

^f School of Locomotive and Vehicle, Guangzhou Railway Polytechnic, Guangzhou 510430, China

^g Guangdong-Hongkong-Macao Joint Laboratory of Energy Saving and Intelligent Maintenance for Modern Transportations, Guangzhou 510430, China

* Email: xiaohb@szit.edu.cn, Guoliangchn@163.com

Supplementary Figure




Figure S1 Tensile stress-strain curves at room temperature of as-printed and annealed HEA samples with different VEDs