

Supplementary Information

Efficient OLEDs fabricated by solution process based on carbazole and thienopyrrolediones derivatives

L. A. Lozano-Hernández¹, J. L. Maldonado^{1,*}, C. Garcias-Morales^{1,3}, A. E. Roa^{1,†}, O. Barbosa-García¹, M. Rodríguez¹ and E. Pérez-Gutiérrez²

¹ Research Group of Optical Properties of Materials (GPOM), Centro de Investigaciones en Óptica, A.P. 1-948, 37000 León, Guanajuato, México; luislozano@cio.mx (L.A.L.-H.); jlmr@cio.mx (J.L.M.);

cgarcias@uadec.edu.mx (C.G.-M); arian.espinosa@cqua.edu.mx (A.E.R.); barbosag@cio.mx (O.B.-G.);


mrodrri@cio.mx (M.R.)

² CONACYT-Laboratorio de Polímeros, Centro de Química, Instituto de Ciencias, Benemérita Universidad Autónoma de Puebla (BUAP), Complejo de Ciencias, ICUAP, Edif. 103H, 22 Sur y San Claudio, C.P. 72570 Puebla, Puebla, México; eperez@conacyt.mx (E.P.-G.)


³ Departamento de Química Orgánica, Facultad de Ciencias Químicas, Universidad Autónoma de Coahuila, Saltillo, 25280, Coahuila, México.

* Correspondence: jlmr@cio.mx (J.L.M.); Tel.: +52-477-441-4200 (ext. 265) (J.L.M.)


† Present address: CONACYT-Centro de Investigación en Química Aplicada, Unidad Monterrey, Alianza Sur No. 204 Parque de Innovación e Investigación Tecnológica (PIIT), Apodaca, 66600 Nuevo León, México.




Supplementary Figure S1. IR of molecule CZ-2.



Supplementary Figure S2. IR of molecule CZ-1.




Supplementary Figure S3. IR of molecule MOC-1.




Supplementary Figure S4. IR of molecule MOC-16.


Quantum yield (QY) of CZ-1 molecule (in solid state film) and the fluorescence lifetime (concentration of 1.11×10^{-5} mol/L) were also measured using a spectrofluorometer (Edinburgh instruments, FS5 spectrofluorometer).




Supplementary Figure S5. Intensities with direct exc. and indirect exc. measured for CZ-1 molecule in solid state film. PLQY = 51.9%.



Supplementary Figure S6. Fluorescence lifetime for CZ-1 molecule in solution.



Supplementary Figure S7. J-L-V curves for the best 3 OLEDs for three different thicknesses with EMLs based on CZ-1 and CZ-2.



Supplementary Figure S8. Average J-L-V curves with standar deviation/errors bars for a set of three different fabricated OLED devices (for each EML), with EMLs based on **CZ-1** and **CZ-2** (EML thickness: 70-80 nm)