

Supporting Information

[BMP]⁺[BF₄]⁻-Modified CsPbI_{1.2}Br_{1.8} Solar Cells with Improved Efficiency and Suppressed Photoinduced Phase Segregation

Haixia Xie^{1, 2, *}, Lei Li³, Jiawei Zhang³, Yihao Zhang¹, Yong Pan¹, Jie Xu¹, Xingtian Yin^{3, *}, Wenxiu Que³

¹School of Science, Xi'an University of Architecture and Technology, Xi'an 710055, People's Republic of China

²State Key Laboratory for Strength and Vibration of Mechanical Structures, School of Aerospace Engineering, Xi'an Jiaotong University, Xi'an 710049, People's Republic of China

³Electronic Materials Research Laboratory, Key Laboratory of the Ministry of Education, International Center for Dielectric Research, Shaanxi Engineering Research Center of Advanced Energy Materials and Devices, School of Electronic Science and Engineering, Xi'an Jiaotong University, Xi'an 710049, People's Republic of China

*Correspondence: xiehaixia@xauat.edu.cn (H. X), xt_yin@xjtu.edu.cn (X. Y)




Figure S1. Normalized XRD patterns of pristine $\text{CsPbI}_{1.2}\text{Br}_{1.8}$ and $\text{CsPbI}_{1.2}\text{Br}_{1.8}$ films doped with different mass concentrations ($0.5, 1, 2$ and 3 mg mL^{-1}) of $[\text{BMP}]^+[\text{BF}_4]^-$.