

Correction

Correction: Thermal Stability and Magnetic Properties of Polyvinylidene Fluoride/Magnetite Nanocomposites. *Materials* 2015, 8, 4553–4564

Zen-Wei Ouyang, Erh-Chiang Chen and Tzong-Ming Wu *

Received: 29 May 2015 ; Accepted: 10 July 2015 ; Published: 22 October 2015

Academic Editor: Lorena Pardo

Department of Materials Science and Engineering, National Chung Hsing University, 250, Kuo Kuang Road, Taichung 402, Taiwan; redfish20614@hotmail.com (Z.-W.O.); erhchiang.chen@gmail.com (E.-C.C.)

* Correspondence: tmwu@dragon.nchu.edu.tw; Tel.: +886-4-2284-0500 (ext. 806); Fax: +886-4-2285-7017

In the published manuscript, “Thermal Stability and Magnetic Properties of Polyvinylidene Fluoride/Magnetite Nanocomposites. *Materials* 2015, 8(7), 4553–4564” [1], we detected that in three places the explanations were slightly incorrect. We apologize for any inconvenience this may have caused.

Page 4556, Section “3.1. Characterization and Physical Properties of PVDF/Magnetite Composites”

Please replace: The X-ray diffraction pattern of magnetite presented in Figure 2 contains six strong diffraction peaks at $2\theta = 30.2^\circ, 35.5^\circ, 43.2^\circ, 53.5^\circ, 57.1^\circ$ and 62.9° , corresponding to (220), (311), (400), (422), (511), and (440) crystalline planes of magnetite phase, respectively [27].

With: The X-ray diffraction pattern of magnetite presented in Figure 2, though affected by a high signal/noise ratio, contains five strong diffraction peaks at $2\theta = 30.2, 35.5, 43.2, 53.5$ and 57.1 , corresponding to (220), (311), (400), (422) and (511) crystalline planes in the magnetite phase [27].

Page 4558, Section “3.1. Characterization and Physical Properties of PVDF/Magnetite Composites”

Please replace: The piezoelectricity of PVDF and PVDF/magnetite nanocomposites with various strengths of applied electric field were summarized in Table 1. All data suggested that the value of d_{33} increased with increasing the strength of electric field.

With: The piezoelectricity of PVDF and PVDF/magnetite nanocomposites with various strengths under applied electric field are summarized in Table 1. The standard deviations of the measurements for each sample, as shown in Table 1, are much lower than the resolution of the technique (± 1 pC/N). All data suggests that the value of d_{33} increased on increasing the strength of the electric field.

Page 4558, Section “3.1. Characterization and Physical Properties of PVDF/Magnetite Composites”

Please replace: The obtained d_{33} values are almost the same order as those reported in the literatures, but the used electric field is much smaller [30–32].

With: Though some recent works report higher d_{33} values for PVDF under β -phase optimization or other special conditions, the obtained d_{33} values are almost of the same order as those currently reported in the literature for PVDF, but the electric field used was much smaller [30–32].

Reference

1. Ouyang, Z.-W.; Chen, E.-C.; Wu, T.-M. Thermal stability and magnetic properties of polyvinylidene fluoride/magnetite nanocomposites. *Materials* **2015**, *8*, 4553–4564. [[CrossRef](#)]



© 2015 by the authors; licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons by Attribution (CC-BY) license (<http://creativecommons.org/licenses/by/4.0/>).