

Correction

Correction: Šejnoha, M. et al. Mori-Tanaka Based Estimates of Effective Thermal Conductivity of Various Engineering Materials. *Micromachines* 2011, 2, 129–149

Jan Stránský¹, Jan Vorel¹, Jan Zeman¹ and Michal Šejnoha^{1,2,*}

¹ Department of Mechanics, Faculty of Civil Engineering, Czech Technical University in Prague, Prague, Czech Republic

² Centre for Integrated Design of Advanced Structures, Faculty of Civil Engineering, Czech Technical University in Prague, Prague, Czech Republic

* Author to whom correspondence should be addressed; E-Mail: sejnom@fsv.cvut.cz; Tel.: +420-2-2435-4494; Fax: +420-2-2435-4494.

Received: 20 July 2011 / Published: 25 July 2011

We have discovered a mistake in our original derivation related to the definition of the apparent conductivity due to orientation averaging. Equation (23) needs to be corrected to

$$\tilde{s} = \frac{ss}{s} \quad (23)$$

and the similar adjustment needs to be made in the two-dimensional case:

$$\tilde{s} = \frac{ss_{2D}}{s_{2D}} \quad (38)$$

Finally, Equation (39) and the corresponding text becomes: "... , define a certain indicator of the real microstructure k_{corr} , e.g. as a ratio of the modified and original partial temperature gradient concentration factors

$$k_{\text{corr}} = \frac{\tilde{T}1_{\text{cir}}}{T1_{\text{cir}}} \quad (39)$$

now determined for circular inclusions."

We apologize to readers for any inconvenience.

© 2011 by the authors; licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution license (<http://creativecommons.org/licenses/by/3.0/>).