

Supporting Information

Thermally Activated Delayed Fluorescence in Commercially Available Materials for Solution-Process Exciplex OLEDs

Zong-Liang Tseng^{1, 2,*}, Wei-Lun Huang¹, You-Xun Xu¹, Chih-Hsun Chiang¹

¹Department of Electronic Engineering and ²Organic Electronics Research Center,
Ming Chi University of Technology, New Taipei City 24301, Taiwan (R.O.C)

Corresponding authors' e-mail:

zltseng@mail.mcut.edu.tw (Z. L. Tseng)

Table S1. Average exciton lifetime of Investigated Exciplexes

Exciplex	τ_{av} (s)
TAPC:POT2T	6.70×10^{-7}
PVK:POT2T	6.10×10^{-7}
NPB:POT2T	1.53×10^{-7}
Poly-TPD:POT2T	9.41×10^{-8}




Figure S1. Phosphorescence spectrum of (a) TAPC:POT2T (b) PVK:POT2T (c) NPB:POT2T (d) Poly-TPD:POT2T at 77K.




Figure S2. Electroluminescence spectra of fabricated devices at various driving voltages.; (a) TAPC:POT2T, (b) PVK :POT2T, (c) NPB:POT2T, (d) Poly-TPB:POT2T.