

Tailoring the stabilization and pyrolysis processes of carbon molecular sieve membrane derived from polyacrylonitrile for ethylene/ethane separation

DaeHun Kim^{a,b}, YongSung Kwon^{a,c}, Jung-Hyun Lee^b, Seong-Joong Kim^{d*} and You-In Park^{a*}

^a Green Carbon research Center, Korea Research Institute of Chemical Technology (KRICT), Gajeong-ro 141, Yuseong-gu, Daejeon 34114, Republic of Korea

^b Department of Chemical and Biological Engineering, Korea University, 5-1 Anam-dong, Seongbuk-gu, Seoul 136-713, Republic of Korea

^c Department of Chemical and Biomolecular Engineering, Korea Advanced Institute of Science and Technology (KAIST), Daejeon, 34141, Republic of Korea

^d Center for Convergence Bioceramic Materials, Convergence R&D Division, Korea Institute of Ceramic Engineering and Technology (KICET), 202 Osongsangmyeong 1-ro, Osong-eup, Heungdeok-gu, Cheongju-si, Chungcheongbuk-do, 28160, Republic of Korea

* Correspondence: authors: sjkim@kicet.re.kr (S.-J. Kim); yipark@kict.re.kr (Y.-I. Park)




Figure S1. Deconvolution of C1s XPS spectra of CMSs pyrolyzed at different temperature.




Figure S2. Deconvolution of N1s XPS spectra of CMSs pyrolyzed at different temperature.