Binder-Free Nickel Oxide Lamellar Layer Anchored CoO_x Nanoparticles on Nickel Foam for Supercapacitor Electrodes

Bohua Chen ¹, Yu Zhong ¹, Gengzhe Shen ¹, Fengming Wang ¹, Zhihao Liu ¹, Mei Chen ¹, Weijia Yang ¹, Chi Zhang ¹ and Xin He ^{1,2,*}

- ¹ School of Applied Physics and Materials, Wuyi University, Jiangmen 529020, China; cbhmusuia@163.com (B.C.); zhongyuzzby@163.com (Y.Z.); shengzwyu@126.com (G.S.); wuyiwangfengming@126.com (F.W.); wlxylzh607@163.com (Z.L.); chenmei116@126.com (M.C.); yangweijia5377@126.com (W.Y.); ch.zhang@outlook.com (C.Z.)
- ² Institute for Mechanical Process Engineering and Mechanics, Karlsruhe Institute of Technology (KIT), 76131 Karlsruhe, Germany
- * Correspondence: hexin@mail.wyu.edu.cn

Received: 5 January 2020; Accepted: 20 January 2020; Published: 22 January 2020



Figure S1: CV curves of the commercial nickel foam and ONFs with various electrolysis currents within the potential window of 0~0.7 V.



Figure S2: CV curves of the ONF/CoO_x electrode using different temperature rates during the heat-treating process.



Figure S3: Plots of current against the specific capacitance and Coulombic efficiency of the ONF/CoO_x electrode.