

Supplementary Material:

New three-dimensional porous electrode concept: vertically-aligned carbon nanotubes directly growth on embroidered copper structures

Noemí Aguiló-Aguayo ^{1,*}, Roger Amade ^{2,3}, Shahzad Hussain ², Enric Bertran ^{2,3} and Thomas Bechtold ¹

¹ Research Institute of Textile Chemistry and Textile Physics, University of Innsbruck, Hoehsterstrasse 73, Dornbirn 6850, Austria; thomas.bechtold@uibk.ac.at

² FEMAN Group, Departament de Física Aplicada, Universitat de Barcelona, c/Martí i Franquès 1, 08028 Barcelona, Catalonia, Spain; r.amade@ub.edu (R.A.); sha.awan@hotmail.com (S.H.); ebertran@ub.edu (E.B.)

³ Institute of Nanoscience and Nanotechnology (IN2UB), Universitat de Barcelona, c/Martí i Franquès 1, 08028 Barcelona, Catalonia, Spain

* Correspondence: noemi.aguilo-aguayo@uibk.ac.at or noeaguilo@gmail.com or textilchemie@uibk.ac.at; Tel.: +43-5572-28533-583




Figure S1. Schematic drawing of an embroidered structure with a layout of one layer. Cu wires are used as embroidery and looper yarns. (a) Front view showing the arrangement of one layer with vertical wires; (b) Cross section showing the lockstitching technique, and the arrangement of the embroidery and looper yarns.




Figure S2. (a) SEM image showing the Cu wire used for embroidery with a diameter of 80 μm ; (b) SEM image of the Cu wires with VA-CNTs. The final diameter is about 100 μm , indicating an average VA-CNT length of about 10 μm .




Figure S3. SEM images of the Cu wire with VA-CNTs from different areas: (a) front; (b) side and (c) backside with respect to the plasma. CNTs showed a preferential growth in the vertical direction. Shorter VA-CNTs were observed in the backside.




Figure S4. Photomicrograph of the embroidered structure after the growth of VA-CNTs. Some areas where Cu wires crossed (marked with a white rectangle) seem to be semi-completely covered by VA-CNTs.




Figure S5. (a) Growth of VA-CNTs on $3 \times 3 \text{ cm}^2$ embroidered Cu current collectors; (b) Preparation of a half-pouch cell of $1.5 \times 3 \text{ cm}^2$.