

Erratum

Erratum: Lindner, M. and Schmid, M. Thickness Measurement Methods for Physical Vapor Deposited Aluminum Coatings in Packaging Applications: A Review. *Coatings* 2017, 7, 9

Martina Lindner ^{1,*}  and Markus Schmid ^{1,2,†} 

¹ Fraunhofer-Institute for Process Engineering and Packaging IVV, Giggenhauser Strasse 35, Freising 85354, Germany

² Chair for Food Packaging Technology, Technische Universität München, Weihenstephaner Steig 22, Freising 85354, Germany

* Correspondence: martina.lindner@ivv.fraunhofer.de; Tel.: +49-8161-491-536

† Present Address: Faculty of Life Sciences, Albstadt-Sigmaringen University, Anton-Günther-Str. 51, 72488 Sigmaringen, Germany; schmid@hs-albsig.de

Received: 11 January 2019; Accepted: 11 January 2019; Published: 12 January 2019



The authors wish to make the following change to their published paper [1]. The following sentence on page 18

“The absorption coefficient (α) in turn is linked to the frequency (ω), particle concentration (c) and extinction coefficient (K), as illustrated in Equation (27) [79].”

is replaced by

“The absorption coefficient (α) in turn is linked to the frequency (ω), speed of light (c), and extinction coefficient (K), as illustrated in Equation (27) [79].”

The manuscript will be updated and the original will remain available. A link to this Erratum will be added.

Reference

1. Lindner, M.; Schmid, M. Thickness Measurement Methods for Physical Vapor Deposited Aluminum Coatings in Packaging Applications: A Review. *Coatings* **2017**, *7*, 9. [[CrossRef](#)]



© 2019 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).