

The Effect of Calcination Temperature on Various Sources of ZrO_2 Supported Ni Catalyst for Dry Reforming of Methane

Ahmed Aidid Ibrahim ^{1,*}, Anis Hamza Fakeeha ^{1,**}, Mahmud Sofiu Lanre ¹, Abdulrhman S. Al-Awadi ¹, Salwa Bader Alreshaidan ², Yousef Abdulrahman Albaqmaa ¹, Syed Farooq Adil ², Ateyah A. Al-Zahrani ¹, Ahmed Elhag Abasaheed ¹ and Ahmed S. Al-Fatesh ¹

¹ Chemical Engineering Department, College of Engineering, King Saud University, P.O. Box 800, Riyadh 11421, Saudi Arabia; alawadi@ksu.edu.sa (A.S.A.-A.); abasaheed@ksu.edu.sa (A.E.A.); mahmudsofiu@gmail.com (M.S.L.); aalfatesh@ksu.edu.sa (A.S.A.-F.); yousef201629@gmail.com (Y.A.A.-B.); aazz@ksu.edu.sa (A.A.Z.)

² Department of Chemistry, College of Science, King Saud University, P.O. Box 800, Riyadh 11451, Saudi Arabia; sfadil@ksu.edu.sa (S.F.A.); chem241@ksu.edu.sa (S.B.A.-R.)

* Correspondence: aidid@ksu.edu.sa (A.A.I.); anishf@ksu.edu.sa (A.H.F.); Tel.: +966-467-6859 (A.A.I. & A.H.F.)

Supplementary Information




Figure S1. Experimental set-up.




Figure S2. Pore size distribution for catalysts calcined at 600°C.




Figure S3. Pore size distribution for catalysts calcined at 700°C.




Figure S4. Pore size distribution for catalysts calcined at 800°C.




Figure S5. Stability study of the best catalyst (Ni-15Y-RC).