

Article

Improving Electricity Consumption Estimation for Electric Vehicles Based on Sparse GPS Observations

Jiangbo Wang ¹, Kai Liu ^{1,*} and Toshiyuki Yamamoto ²

¹ School of Transportation and Logistics, Dalian University of Technology, Dalian 116024, China; wangjiangbo@mail.dlut.edu.cn

² Institute of Materials and Systems for Sustainability, Nagoya University, Nagoya 464-8603, Japan; yamamoto@civil.nagoya-u.ac.jp

* Correspondence: liukai@dlut.edu.cn

Academic Editor: Michael Pecht

Received: 8 November 2016; Accepted: 12 January 2017; Published: 20 January 2017

Abstract: Improving the estimation accuracy for the energy consumption of electric vehicles (EVs) would greatly contribute to alleviating the range anxiety of drivers and serve as a critical basis for the planning, operation, and management of charging infrastructures. To address the challenges in energy consumption estimation encountered due to sparse Global Positioning System (GPS) observations, an estimation model is proposed that considers both the kinetic characteristics from sparse GPS observations and the unique attributes of EVs: (1) work opposing the rolling resistance; (2) aerodynamic friction losses; (3) energy consumption/generation depending on the grade of the route; (4) auxiliary load consumption; and (5) additional energy losses arising from the unstable power output of the electric motor. Two quantities, the average energy consumption per kilometer and the energy consumption for an entire trip, were focused on and compared for model fitness, parameter, and effectiveness, and the latter showed a higher fitness. Based on sparse GPS observations of 68 EVs in Aichi Prefecture, Japan, the traditional linear regression approach and a multilevel mixed-effects linear regression approach were used for model calibration. The proposed model showed a high accuracy and demonstrated a great potential for application in using sparse GPS observations to predict the energy consumption of EVs.

Keywords: electricity consumption; electric vehicle (EV); sparse Global Positioning System (GPS) observations; linear regression model; multilevel model

1. Introduction

For reducing the world's dependency on fossil fuels and their harmful emissions, electric vehicles (EVs) have attracted significant attention in recent years. However, the driving range of EVs is not competitive compared with that of internal combustion engine vehicles because of significant technological barriers, and this can make drivers feel anxious about their remaining energy. It has been widely accepted that accurate range prediction is the key to minimizing range anxiety and helping drivers make the best use of their limited electricity [1,2]. More importantly, the energy consumption of vehicles is a critical aspect to consider both in transportation planning and in evaluating the energy impacts of operational-level projects [3]. In particular, EV energy consumption data serve as a critical basis for the spatial planning, operation, and management of charging infrastructures.

According to previous studies, a variety of factors affect energy consumption, including travel-related factors [4,5], environment-related factors [6–9], vehicle-related factors [10–14], roadway-related factors [15], traffic-related factors [16–18], driver-related factors [3,19–22], the health and degradation condition of the battery [23–26], the efficiency of braking energy recovery [27–31], and the charge and discharge character of the battery [32]. Some previous studies collected the

information through driving-cycle experiments in the lab [4,24] and Global Positioning System (GPS) observations in the real world [32–34], but some results showed the significant difference between experiments and real-world conditions [35,36], leading to a relative low accuracy and poor practicality of models. Particularly, it is very difficult for the experimental design of predetermined conditions to take some real-world conditions into consideration, including the behaviors of drivers on air-conditioner and heater usage, the influence of driving environment, real-world aerodynamic friction loss, lane changing behaviors, car following behaviors, driving behaviors, etc. Thus, for a high accuracy of energy consumption estimation, the collection of extremely detailed and comprehensive information on the operation of EVs in the real world is required.

In practice, detailed and comprehensive field observations of daily travel are extremely difficult to obtain because of the high costs of implementation and privacy issues. However, sparser and more fragmentary data on EVs are relatively easy to obtain from simple devices implemented in such vehicles, such as GPS devices. Nevertheless, energy consumption estimation based on sparse observations of EVs faces many challenges. First, with sparse GPS data, many slight changes in the level of stored energy and the finer details of driving behavior characteristics and traffic conditions, which might be derived from real-time location information, will remain unobserved [37]. Moreover, without continuous observations of vehicle movement, the kinetic characteristics that most strongly influence the energy consumption of EVs are difficult to model, and the quantization of these factors may readily introduce large errors. In particular, sparse GPS observations increase the difficulty of and errors in map matching [38,39].

To overcome these challenges, improving the accuracy of energy consumption estimation, based on sparse observations, would make an important contribution to practical applications. Thus, the purpose of the present work is to improve the accuracy of electricity consumption estimation, based on sparse spatial-temporal behavior observations of EVs. An energy consumption model is proposed that considers the kinetic characteristics and unique attributes of EVs: (1) work opposing the rolling resistance; (2) aerodynamic friction losses; (3) energy consumption/generation depending on the grade of the route; (4) auxiliary load consumption; and (5) additional energy losses arising from the unstable power output of the electric motor. The traditional linear regression approach and a multilevel mixed-effects linear regression approach are used for model calibration based on GPS observations of 68 EVs.

For the energy consumption estimations, either the energy consumption for an entire trip [35] or the energy consumption per unit distance [5] is used as the research object in previous studies. An estimation for an entire trip gives drivers an overview of the electricity costs for future travel, while an estimation for per unit distance provides a detailed view of the electricity consumed when driving. In the present work, energy consumption models for both are built, and the results are compared and analyzed from the aspects of model fitness, parameters, and effectiveness.

The paper is organized as follows. The second section provides a detailed description of the data collection procedures used to obtain the EV energy consumption observations. The energy consumption estimation models and the results of the study are then successively discussed in the following sections (Sections 3 and 4, respectively). Finally, a summary of our findings is presented.

2. Data Collection

GPS trajectory data were collected for approximately 500 EVs in Japan from February 2011 to January 2013. Among these data, those for 39,685 trips of 68 EVs in Aichi Prefecture, collected from February 2012 to January 2013, were used in this study. The vehicle coordinates, the timestamps, the vehicle odometer records, the vehicle ID, the state of charge (SOC) of the battery, and the usage states of the air conditioner and heater were collected once per minute. It should be noted that the odometer records distance in integer kilometers, which makes it impossible to model energy consumption on a road link basis.

With the help of map matching, the trips completed by each vehicle were identified. The travel distance, travel time, SOC before and after travel, and so on were acquired. Furthermore, based on elevation data for the road network in Aichi Prefecture, the gradients of the travel routes were also determined. To investigate the influence of the ambient environment, the ambient temperature for each trip was recorded, except for 208 trips with the temperature missing. In total, 39,477 trips of 68 EVs were employed in the present study.

The polling frequency of the EVs' GPS reports was relatively low (once per minute), and therefore the data could not provide detailed information on actual driving behavior or the moments at which the SOC changed (which occurred in steps of 0.5% during operation). It would be extremely difficult to compare the energy consumption of vehicles under varying driving conditions or to estimate the actual SOC values at the start and end nodes of each link; thus, we focused on the energy consumption per trip. In total, 39,477 trips completed by 68 EVs were investigated in this study.

3. Energy Consumption Estimation Models

The energy consumption model for an internal combustion engine vehicle is formulated in terms of the work of the tractive force necessary to overcome acceleration resistance, air resistance, gradient resistance, and rolling resistance and is also used for EVs [15,40] and given by:

$$\Delta E_i = E_{ac_i} + E_{ro_i} + E_{ae_i} + E_{gr_i} \quad (1)$$

where ΔE_i is the energy consumption for trip i , E_{ac_i} is the work necessary to overcome the acceleration resistance, E_{ro_i} is the work opposing the rolling resistance, E_{ae_i} is the aerodynamic friction loss, and E_{gr_i} is the energy consumed or generated depending on the grade of the route (this value will be positive when the vehicle is travelling uphill and negative during downhill travel).

Nevertheless, for an EV, these four components corresponding to the work opposing various resistances will always underestimate the true energy consumption in the real world. The electricity consumed by auxiliary loads represents a non-negligible contribution. In particular, the effect of the ambient temperature is seldom considered. Because of the particularities of the dynamic system, the energy loss arising from the unstable power output of the electric motor, as influenced by the ambient temperature, must also be included in the energy consumption model. Thus the energy consumption model in the present work is formulated as follows:

$$\Delta E_i = E_{ro_i} + E_{ae_i} + E_{gr_i} + E_{au_i} + E_{te_i} \quad (2)$$

where E_{au_i} is the auxiliary load consumption and E_{te_i} is the additional energy loss due to the unstable power output of the electric motor under the influence of the ambient temperature, which most previous studies have ignored. Notably, the once-per-minute polling frequency of the GPS devices used in this study resulted in considerable difficulty in measuring acceleration. The work necessary to overcome the acceleration resistance is actually correlated with other parts of power output and therefore will shift to other terms when the model is calibrated by a regression model [35].

3.1. Average Energy Consumption Estimation per Unit Distance

An estimation of energy consumption per unit distance provides a detailed view of the electricity consumed while driving. However, because of the low polling frequency of the GPS observations in this study (once per minute) and because the prevalence of dropping interruptions in the residual SOC records was 0.5%, corresponding to intervals of approximately 1–3 min during continuous driving, the energy consumption per kilometre could not be directly observed. Thus, the average electricity consumption per kilometre was estimated, as described in this section.

When the average energy consumption per kilometre is considered, ΔE_i on the left-hand side of Equation (1) is replaced with Δe_i . The work opposing the rolling resistance [15,40] is formulated as:

$$Ero_i = \varphi * M * g * l_i * \cos \theta \approx \varphi * M * g \quad (3)$$

$$\varphi = \eta_1 + \eta_2 * V_i \quad (4)$$

where φ is the rolling resistance coefficient, which is a function of the vehicle speed, V_i [41]; M is the mass of the vehicle, which is taken to be a constant because all vehicles investigated were of the same type; g is the gravitational constant; and θ is the road grade angle. The product $\varphi * M * g$ is the rolling resistance, and l_i is the unit distance, i.e. one kilometre in this study. Most of the road grade angles in the urban area of Aichi Prefecture are less than 5%; therefore, Ero_i is approximately equal to $\varphi * M * g$. For φ , a simple linear function of the average travel speed is applied. η_1 and η_2 are the two parameters of this function, which are estimated in the regression model.

The aerodynamic friction loss [15,40] is given by:

$$Eae_i = 0.5 * q * K * V_i^2 * l_i \propto V_i^2 \quad (5)$$

where q is the air density, which is estimated in the regression model; K is the frontal area of the vehicle; and V_i is the average travel speed for trip i . In fact, Eae_i is proportional to V_i^2 when $l_i = 1$ km.

Regarding the energy consumed for hill climbing, previous studies [15,40] formulate it as:

$$Egr_i = \sum M * g * l_s * \sin \theta \quad (6)$$

where l_s is the traveling distance in a second and θ is the road grade angle. The product of $l_s * \sin \theta$ is the height difference in this second. In fact, even with a same height difference but a different road grade angle, the electricity consumptions are not identical [5,18]. In order to quantify the influence of different gradients, the gradient should be classified into several gradient intervals [18]. The observations indicate that most trips had their origins and destinations in urban areas and were relatively short in length. If the range of each interval is too small, the coefficients estimated for two adjacent intervals may be same. While if the range of each interval is too wide, we can't catch continuous change of the coefficients on different grades. Thus after several experiments, 11 intervals were classified, which are $<-9\%$, $-7\% \sim -9\%$, $-5\% \sim -7\%$, $-3\% \sim -5\%$, $-1\% \sim -3\%$, $-1\% \sim 1\%$, $1\% \sim 3\%$, $3\% \sim 5\%$, $5\% \sim 7\%$, $7\% \sim 9\%$, and $>9\%$ (where '-' indicates a downwards gradient). Furthermore, ten of them (except $-1\% \sim 1\%$, which is a flat slope) were used to formulate Egr_i to avoid multicollinearity in the model:

$$Egr_i = \tau^T * p = \tau_1 * p_{<-9\%} + \tau_2 * p_{-7\% \sim -9\%} + \tau_3 * p_{-5\% \sim -7\%} + \tau_4 * p_{-3\% \sim -5\%} + \tau_5 * p_{-1\% \sim -3\%} + \tau_6 * p_{1\% \sim 3\%} + \tau_7 * p_{3\% \sim 5\%} + \tau_8 * p_{5\% \sim 7\%} + \tau_9 * p_{7\% \sim 9\%} + \tau_{10} * p_{>9\%} \quad (7)$$

$$p_j = G_j / l_i * 100\% \quad (8)$$

where p_j is the percentage of the link length per kilometre with grade angle j ($j \in (<-9\%, -7\% \sim -9\%, -5\% \sim -7\%, -3\% \sim -5\%, -1\% \sim -3\%, 1\% \sim 3\%, 3\% \sim 5\%, 5\% \sim 7\%, 7\% \sim 9\%, \text{ and } >9\%)$), τ_1 to τ_{10} are the influence coefficients for the different gradient, G_j is the link length with grade angle j for trip i , and l_i is the total travelled distance.

The auxiliary load consumption consists of two main components in this study, (1) the air conditioning load consumption and (2) the heating load consumption. This is expressed as follows:

$$Eau_i = \zeta_1 * A_i + \zeta_2 * H_i \quad (9)$$

$$A_i = \frac{t_i}{l_i} * \frac{a_i}{n_i} \quad (10)$$

$$H_i = \frac{t_i}{l_i} * \frac{h_i}{n_i} \quad (11)$$

where A_i and H_i are the average service times per kilometer of the air conditioner and heater, respectively, which are calculated as shown in Equations (10) and (11), respectively; t_i is the total travel time; a_i and h_i are the numbers of GPS points at which the air conditioner and heater, respectively, are switched on; n_i is the total number of GPS points recorded for trip i ; and ζ_1 and ζ_2 are the effects of the air conditioner and heater, respectively, on the EV's energy consumption.

As illustrated in Reference [42], the relationship between energy efficiency and ambient temperature exhibits an asymmetrical 'U' shape, which is best fit by a third-order polynomial. Thus, the additional energy loss due to the unstable power output of the electric motor under the influence of the ambient temperature is formulated as:

$$Ete_i = \alpha_1 * T_i + \alpha_2 * T_i^2 + \alpha_3 * T_i^3 \quad (12)$$

where α_1 – α_3 are the influence coefficients, which are estimated during model calibration, and T is the ambient temperature.

3.2. Energy Consumption Estimation for an Entire Trip

The ability to accurately estimate the energy consumption for an entire trip would help drivers to better manage and use the limited electricity stored in their vehicle batteries. Thus, the electricity consumption for an entire trip (ΔE_i) is the focus of this section. The work opposing the rolling resistance for an entire trip is formulated as:

$$Ero_i = \varphi * M * g * l_i * \cos \theta \quad (13)$$

For a small road grade angle, Equation (13) can be simplified to:

$$Ero_i = (\eta_1 + \eta_2 * V_i) * M * g * l_i \propto \eta_1 * l_i + \eta_2 * V_i * l_i \quad (14)$$

where Ero_i is proportional to $\eta_1 * l_i + \eta_2 * V_i * l_i$.

The aerodynamic friction loss is given by:

$$Eae_i = 0.5 * q * K * V_i^2 * l_i \propto V_i^2 * l_i \quad (15)$$

whereas Egr_i is formulated as:

$$Egr_i = \tau^T * G = \tau_1 * G_{<-9\%} + \tau_2 * G_{-7\% \sim -9\%} + \tau_3 * G_{-5\% \sim -7\%} + \tau_4 * G_{-3\% \sim -5\%} + \tau_5 * G_{-1\% \sim -3\%} + \tau_6 * G_{1\% \sim 3\%} + \tau_7 * G_{3\% \sim 5\%} + \tau_8 * G_{5\% \sim 7\%} + \tau_9 * G_{7\% \sim 9\%} + \tau_{10} * G_{>9\%} \quad (16)$$

The auxiliary load consumption is given by:

$$Eau_i = \zeta_1 * AC_i + \zeta_2 * HT_i \quad (17)$$

$$AC_i = t_i * \frac{a_i}{n_i} \quad (18)$$

$$HT_i = t_i * \frac{h_i}{n_i} \quad (19)$$

where AC_i and HT_i are the service times of the air conditioner and heater, respectively, during trip i .

The additional energy loss due to the unstable power output of the electric motor under the influence of the ambient temperature is again formulated as shown in Equation (12).

3.3. Model Calibration

A linear regression model was employed to calibrate the energy consumption model. The model for the average energy consumption per unit distance was formulated as:

$$\Delta e_i = \beta_0 + \eta_1 + \eta_2 * V_i + \beta_1 * V_i^2 + \tau^T * p + \zeta_1 * A_i + \zeta_2 * H_i + \alpha_1 * T_i + \alpha_2 * T_i^2 + \alpha_3 * T_i^3 + \varepsilon_i \quad (20)$$

where Δe_i is the average electricity consumption per kilometre during trip i (dependent variable); V_i , p , A_i , H_i , and T_i are the independent variables described in Section 3.4; and η_2 , β_1 , τ^T , ζ_1 , ζ_2 , α_1 , α_2 , and α_3 are the coefficients of the variables. $\beta_0 + \eta_1$ is the intercept term of the regression model; particularly, τ and p , in particular, are the vectors of the influence coefficients for the different grade angle categories and the link length percentages at the different grade angles, respectively; and ε_i is the residual term.

Furthermore, the model for the energy consumption for an entire trip was formulated as:

$$\Delta E_i = \beta_0 + \eta_1 * l_i + \eta_2 * V_i * l_i + \beta_1 * V_i^2 * l_i + \tau^T * G + \zeta_1 * AC_i + \zeta_2 * HT_i + \alpha_1 * T_i + \alpha_2 * T_i^2 + \alpha_3 * T_i^3 + \varepsilon_i \quad (21)$$

where ΔE_i is the energy consumption for the entire trip i ; β_0 is the intercept term; τ and G are the vectors of the influence coefficients for the different grade angle categories and the link lengths at the different grade angles, respectively; and ε_i is the residual term.

To address the heterogeneity of drivers [18], another regression model based on multilevel mixed-effects regression was also employed to capture the potential correlations and non-constant variability of the energy consumption characteristics. The general form of a two-level mixed-effects regression model [43] is given by:

$$E_{ij} = \beta_0 + \sum_{\lambda=1}^{\pi} \beta_{\lambda} * x_{\lambda ij} + \sum_{m=1}^{\omega} u_{m0j} * z_{mij} + u_{0j} + \varepsilon_{ij} \quad (22)$$

where E_{ij} is the dependent variable, β_0 is the fixed intercept term of the model, $x_{\lambda ij}$ is a variable with a fixed coefficient β_{λ} , π is the number of variables $x_{\lambda ij}$ that appear in the model, z_{mij} is a variable with a random coefficient u_{m0j} , ω is the number of variables z_{mij} that appear in the model, u_{0j} is the random intercept, and ε_{ij} is the residual term. Particularly, in this study, for average electricity consumption per kilometre and the energy consumption in an entire trip, the dependent variable E_{ij} in Equation (22) will be replaced by Δe_i and ΔE_i respectively. Accordingly, the fixed independent variables are also replaced by those in Equations (20) and (21), respectively, while the random effects for each will be discussed in Section 4.

3.4. Variable Descriptions

All of the variables for the energy consumption estimation were calculated as discussed above and are listed in Table 1. The average energy consumption was 0.752 kWh, and the energy consumption per kilometre was 0.15 kWh/km. The mean trip distance was only 5.342 km, and the average speed was less than 22 km/h. Regarding the gradient distribution, 75% of the road distance travelled was at a grade of -1% – 1% , whereas approximately 98% of the distance travelled fell within the range of -5% – 5% . Thus, the observations indicate that most trips had their origins and destinations in urban areas and were relatively short in length. Moreover, the mean ambient temperature was approximately $18\text{ }^{\circ}\text{C}$, with a large variance among the different trips.

Table 1. Descriptive statistics of the variables.

Variable	Description	Mean	Standard Deviation
Δe_i	Energy consumption per kilometre (kWh/km).	0.150	0.060
ΔE_i	Energy consumption for trip i (kWh).	0.752	0.580
A_i	Average service time of the air conditioner per kilometre (min/km).	1.147	1.756
H_i	Average service time of the heater per kilometre (min/km).	0.476	1.295
AC_i	Service time of the air conditioner during trip i (min).	5.223	8.124
HT_i	Service time of the heater during trip i (min).	2.244	6.105
l_i	Travel distance (km).	5.342	4.402
V_i	Average travel speed (km/h).	21.771	7.061

Table 1. Cont.

Variable	Description	Mean	Standard Deviation
T_i	Ambient temperature ($^{\circ}\text{C}$).	18.352	9.159
$G_{<-9\%}$	Link length at a road grade angle steeper than -9% (km).	0.007	0.040
$G_{-7\%\sim-9\%}$	Link length at a road grade angle between $-7\%\sim-9\%$ (km).	0.010	0.054
$G_{-5\%\sim-7\%}$	Link length at a road grade angle between $-5\%\sim-7\%$ (km).	0.039	0.109
$G_{-3\%\sim-5\%}$	Link length at a road grade angle between $-3\%\sim-5\%$ (km).	0.139	0.249
$G_{-1\%\sim-3\%}$	Link length at a road grade angle between $-1\%\sim-3\%$ (km).	0.499	0.675
$G_{-1\%\sim1\%}$	Link length at a road grade angle between $-1\%\sim1\%$ (km).	3.941	3.339
$G_{1\%\sim3\%}$	Link length at a road grade angle between $1\%\sim3\%$ (km).	0.513	0.691
$G_{3\%\sim5\%}$	Link length at a road grade angle between $3\%\sim5\%$ (km).	0.137	0.241
$G_{5\%\sim7\%}$	Link length at a road grade angle between $5\%\sim7\%$ (km).	0.039	0.106
$G_{7\%\sim9\%}$	Link length at a road grade angle between $7\%\sim9\%$ (km).	0.010	0.055
$G_{>9\%}$	Link length at a road grade angle steeper than 9% (km).	0.007	0.041
$p_{<-9\%}$	Percentage of the link length at a road grade angle steeper than -9% .	0.001	0.005
$p_{-7\%\sim-9\%}$	Percentage of the link length at a road grade angle between $-7\%\sim-9\%$.	0.002	0.008
$p_{-5\%\sim-7\%}$	Percentage of the link length at a road grade angle between $-5\%\sim-7\%$.	0.008	0.020
$p_{-3\%\sim-5\%}$	Percentage of the link length at a road grade angle between $-3\%\sim-5\%$.	0.025	0.039
$p_{-1\%\sim-3\%}$	Percentage of the link length at a road grade angle between $-1\%\sim-3\%$.	0.089	0.084
$p_{-1\%\sim1\%}$	Percentage of the link length at a road grade angle between $-1\%\sim1\%$.	0.747	0.215
$p_{1\%\sim3\%}$	Percentage of the link length at a road grade angle between $1\%\sim3\%$.	0.092	0.087
$p_{3\%\sim5\%}$	Percentage of the link length at a road grade angle between $3\%\sim5\%$.	0.026	0.041
$p_{5\%\sim7\%}$	Percentage of the link length at a road grade angle between $5\%\sim7\%$.	0.007	0.019
$p_{7\%\sim9\%}$	Percentage of the link length at a road grade angle between $7\%\sim9\%$.	0.002	0.009
$p_{>9\%}$	Percentage of the link length at a road grade angle steeper than 9% .	0.001	0.006

4. Results

Four regression models were constructed for calibrating the energy consumption models discussed above. Specifically, Models 1 and 2 are related to the estimation of the energy consumption per kilometre, whereas Models 3 and 4 are related to the energy consumption estimation for an entire trip.

Moreover, Models 1 and 3 are traditional linear regression models, formulated as shown in Equations (20) and (21), respectively, whereas the other two are multilevel mixed-effects linear regression models that consider the heterogeneity among drivers, formulated as shown in Equation (22).

In Models 1 and 2, both V_i and a constant are used to explain the work opposing the rolling resistance, as described by Equation (3); V_i^2 is used to account for the aerodynamic friction loss; the link length percentages corresponding to each gradient category per kilometre are used to interpret the energy consumed for hill climbing; the service times of the air conditioner and heater per kilometre (A_i and H_i respectively) are used to explain the auxiliary load consumption; and a third-order polynomial with respect to T_i is used to consider the influence of the ambient temperature. Additionally, the differing driving habits of different drivers lead to variations in energy consumption characteristics. Thus, a number of variables related to driving behaviour, such as the average travel speed, air-conditioner usage time, and heater usage time, may show heterogeneity. The same average travel speed may contribute differently to the energy consumption depending on the driving behaviour of the driver. The same holds true for the link length percentage corresponding to a given gradient category. In addition, for air-conditioner usage and heater usage, some drivers prefer rapid cooling/heating but others do not. Thus, in Model 2, a random coefficient is assigned to each average travel speed, air conditioning time, heating time and grade angle category, with a random intercept in terms of the driver level. For the 68 EVs in the present study, each EV is driven by no more than two drivers for both private EVs and company EVs, and mostly there is only one main driver for each vehicle. Although we cannot ensure that the same vehicle is driven by the same driver for each trip, the performance of each EV may be similar with regard to the driver's habits because the travel patterns (origination and destination, number of trips) and travel routes are similar for daily trips. The regression results are presented in Table 2.

Table 2. Parameter estimation results for the four models.

Variable	Energy Consumption per km		Energy Consumption for an Entire Trip	
	Model 1	Model 2	Model 3	Model 4
	Coefficient (Standard Error)	Coefficient (Standard Error)	Coefficient (Standard Error)	Coefficient (Standard Error)
Air conditioning time per km (A_i)	0.0160 (0.0001) ***	0.0143 (0.0004) ***	n.a.	n.a.
Heating time per km (H_i)	0.0299 (0.0001) ***	0.0319 (0.0008) ***	n.a.	n.a.
Air conditioning time per trip (AC_i)	n.a.	n.a.	0.0142 (0.0001) ***	0.0124 (0.0004) ***
Heating time per trip (HT_i)	n.a.	n.a.	0.0320 (0.0001) ***	0.0316 (0.0007) ***
Average travel speed (V_i)	−0.0027 (0.0001) ***	−0.0034 (0.0001) ***	n.a.	n.a.
Product of speed and distance ($V_i * I_i$)	n.a.	n.a.	−0.0022 (0.0001) ***	−0.0022 (0.0001) ***
Travel distance (I_i)	n.a.	n.a.	0.1387 (0.0010) ***	0.1419 (0.0013) ***
Square of speed (V_i^2)	3×10^{-5} (2×10^{-6}) ***	5×10^{-5} (2×10^{-6}) ***	n.a.	n.a.
Product for square of speed and distance ($V_i^2 * I_i$)	n.a.	n.a.	3×10^{-5} (10^{-6}) ***	3×10^{-5} (8×10^{-7}) ***
Ambient temperature (T_i)	−0.0011 (0.0002) ***	−0.0014 (0.0002) ***	−0.0056 (0.0008) ***	−0.0078 (0.0007) ***
Square of temperature (T_i^2)	−0.0001 (10^{-5}) ***	−0.0001 (10^{-5}) ***	−0.0004 (5×10^{-5}) ***	−0.0003 (4×10^{-5}) ***
Cubic of temperature (T_i^3)	4×10^{-6} (2×10^{-7}) ***	3×10^{-6} (2×10^{-7}) ***	2×10^{-5} (10^{-6}) ***	10^{-5} (8×10^{-7}) ***
Percentage of link length at an angle <−9%	−0.3524 (0.0292) ***	−0.3289 (0.0568) ***	n.a.	n.a.
Percentage of link length at an angle −7%~−9%	−0.2827 (0.0186) ***	−0.2593 (0.0281) ***	n.a.	n.a.
Percentage of link length at an angle −5%~−7%	−0.1647 (0.0086) ***	−0.1629 (0.0148) ***	n.a.	n.a.
Percentage of link length at an angle −3%~−5%	−0.1375 (0.0046) ***	−0.1256 (0.0074) ***	n.a.	n.a.
Percentage of link length at an angle −1%~−3%	−0.0751 (0.0020) ***	−0.0773 (0.0038) ***	n.a.	n.a.
Percentage of link length at an angle 1%~3%	0.0743 (0.0019) ***	0.0685 (0.0036) ***	n.a.	n.a.
Percentage of link length at an angle 3%~5%	0.1564 (0.0044) ***	0.1340 (0.0075) ***	n.a.	n.a.
Percentage of link length at an angle 5%~7%	0.2363 (0.0092) ***	0.2080 (0.0140) ***	n.a.	n.a.
Percentage of link length at an angle 7%~9%	0.2693 (0.0167) ***	0.3163 (0.0304) ***	n.a.	n.a.
Percentage of link length at an angle >9% ($p_{>9\%}$)	0.4657 (0.0255) ***	0.4574 (0.0353) ***	n.a.	n.a.
Link length at an angle <−9% ($G_{<-9\%}$)	n.a.	n.a.	−0.5461 (0.0230) ***	−0.3556 (0.0648) ***
Link length at an angle −7%~−9% ($G_{-7\% \sim -9\%}$)	n.a.	n.a.	−0.2789 (0.0165) ***	−0.2340 (0.0277) ***
Link length at an angle −5%~−7% ($G_{-5\% \sim -7\%}$)	n.a.	n.a.	−0.1915 (0.0089) ***	−0.1836 (0.0156) ***
Link length at an angle −3%~−5% ($G_{-3\% \sim -5\%}$)	n.a.	n.a.	−0.1166 (0.0045) ***	−0.1362 (0.0103) ***
Link length at an angle −1%~−3% ($G_{-1\% \sim -3\%}$)	n.a.	n.a.	−0.0840 (0.0018) ***	−0.0738 (0.0041) ***
Link length at an angle 1%~3% ($G_{1\% \sim 3\%}$)	n.a.	n.a.	0.0718 (0.0018) ***	0.0715 (0.0038) ***
Link length at an angle 3%~5% ($G_{3\% \sim 5\%}$)	n.a.	n.a.	0.1821 (0.0045) ***	0.1583 (0.0096) ***
Link length at an angle 5%~7% ($G_{5\% \sim 7\%}$)	n.a.	n.a.	0.2615 (0.0093) ***	0.2165 (0.0173) ***
Link length at an angle 7%~9% ($G_{7\% \sim 9\%}$)	n.a.	n.a.	0.2293 (0.0160) ***	0.2602 (0.0383) ***
Link length at an angle >9% ($G_{>9\%}$)	n.a.	n.a.	0.6557 (0.022) ***	0.5298 (0.0523) ***
Intercept	0.1822 (0.0014) ***	0.1907 (0.0021) ***	0.1383 (0.0039) ***	0.1370 (0.0045) ***
Random Parameters				
	Standard Deviation (Standard Error)	Standard Deviation (Standard Error)	Standard Deviation (Standard Error)	Standard Deviation (Standard Error)
V_i coefficient	n.a.	0.0004 (4×10^{-5}) ***	n.a.	n.a.
I_i coefficient	n.a.	n.a.	n.a.	0.0073 (0.0007) ***
A_i coefficient	n.a.	0.0032 (0.0003) ***	n.a.	n.a.
H_i coefficient	n.a.	0.0067 (0.0006) ***	n.a.	n.a.
AC_i coefficient	n.a.	n.a.	n.a.	0.0035 (0.0003) ***
HT_i coefficient	n.a.	n.a.	n.a.	0.0058 (0.0005) ***
$p_{<-9\%}$ coefficient	n.a.	0.2902 (0.0460) ***	n.a.	n.a.
$p_{-7\% \sim -9\%}$ coefficient	n.a.	0.1096 (0.0263) ***	n.a.	n.a.
$p_{-5\% \sim -7\%}$ coefficient	n.a.	0.0698 (0.0140) ***	n.a.	n.a.
$p_{-3\% \sim -5\%}$ coefficient	n.a.	0.0376 (0.0094) ***	n.a.	n.a.
$p_{-1\% \sim -3\%}$ coefficient	n.a.	0.0231 (0.0035) ***	n.a.	n.a.
$p_{1\% \sim 3\%}$ coefficient	n.a.	0.0219 (0.0036) ***	n.a.	n.a.
$p_{3\% \sim 5\%}$ coefficient	n.a.	0.0387 (0.0078) ***	n.a.	n.a.
$p_{5\% \sim 7\%}$ coefficient	n.a.	0.0623 (0.0182) ***	n.a.	n.a.
$p_{7\% \sim 9\%}$ coefficient	n.a.	0.1326 (0.0290) ***	n.a.	n.a.
$p_{>9\%}$ coefficient	n.a.	0.1178 (0.0484)	n.a.	n.a.
$G_{<-9\%}$ coefficient	n.a.	n.a.	n.a.	0.3856 (0.0584) ***
$G_{-7\% \sim -9\%}$ coefficient	n.a.	n.a.	n.a.	0.1171 (0.0360)
$G_{-5\% \sim -7\%}$ coefficient	n.a.	n.a.	n.a.	0.0823 (0.0197) ***
$G_{-3\% \sim -5\%}$ coefficient	n.a.	n.a.	n.a.	0.0687 (0.0093) ***
$G_{-1\% \sim -3\%}$ coefficient	n.a.	n.a.	n.a.	0.0271 (0.0034) ***
$G_{1\% \sim 3\%}$ coefficient	n.a.	n.a.	n.a.	0.0250 (0.0033) ***
$G_{3\% \sim 5\%}$ coefficient	n.a.	n.a.	n.a.	0.0619 (0.0091) ***
$G_{5\% \sim 7\%}$ coefficient	n.a.	n.a.	n.a.	0.0950 (0.0208) ***
$G_{7\% \sim 9\%}$ coefficient	n.a.	n.a.	n.a.	0.2060 (0.0344) ***
$G_{>9\%}$ coefficient	n.a.	n.a.	n.a.	0.2715 (0.0635) ***
Intercept	n.a.	0.0125 (0.0013) ***	n.a.	0.0232 (0.0024) ***
R^2	0.7799	0.8303	0.9501	0.9649
$R^2_{adjusted}$	0.7798	0.8302	0.9501	0.9649
AIC	−170,380	−178,829	−49,214	−60,857
MSE	0.0179	0.0140	0.0168	0.0118
Observations	39,477	39,477	39,477	39,477

Note: * $p < 0.1$; ** $p < 0.05$; *** $p < 0.01$; n.a. indicates a variable not included in the model.

As shown in Table 2, all of the parameters estimated in Models 1 and 2 are highly significant. The signs and magnitudes of the parameters in these two models are similar. The significant standard deviations of V_i and the link length percentage corresponding to each gradient category reflect a notable heterogeneity among different drivers. The fitness of each model was evaluated based on the adjusted R^2 and Akaike's Information Criterion value (AIC). An improvement of more than 3% was achieved in Model 2, which indicates a more appropriate model specification. The mean square error (MSE) of the estimated energy consumption for an entire trip is calculated, which also shows a better effective of estimation for Model 2.

In Models 3 and 4, both l_i and $V_i * l_i$ are used to account for the work opposing the rolling resistance; $V_i^2 * l_i$ is used to consider the aerodynamic friction loss; the link lengths corresponding to the different gradient categories for the trip are used to interpret the energy consumed for hill climbing; the service times of the air conditioner and heater during the trip (AC_i and HT_i , respectively) are used to explain the auxiliary load consumption; and, once again, the influence of the ambient temperature is represented by a third-order polynomial in T_i . Moreover, similar to Model 2, the heterogeneity among drivers is considered in Model 4. Specifically, a random intercept and random coefficients for travel distance, air conditioning time, heating time, and link length at different grade angles are considered for heterogeneity among different drivers.

Similar to Models 1 and 2, all the parameters in Models 3 and 4 are highly significant. An improvement of 1.48% was achieved in Model 4. While the small MSE and AIC also show Model 4 to be more effective.

All four models show that the impact of heating is about twice that of air conditioning per minute. From the results of Models 3 and 4, it will consume about 0.14 kWh of electricity for every kilometre driven. The product of speed and distance ($V_i * l_i$) shows a negative impact on energy consumption and a kilometre increase in travel distance will decrease the influence of average travel speed by $0.0022V_i$. The significant random coefficients of heating time and air conditioning time indicate that thermal comfort habits vary among drivers significantly. The sign and magnitude of gradient coefficients for these four models are similar and highly significant. As gradient angle rises, energy consumption/generation increases linearly with a sharply increase at an angle of 8%.

The significant standard deviations of the random coefficients related to the link lengths at different grade angles, the average travel speed, and travel distance in Models 2 and 4 reflect significant heterogeneity in driving characteristics among the drivers. Trips with the same link length but different grade angles or average travel speeds showed different energy consumption characteristics because of differences in driving behaviour. With this unobserved heterogeneity, Models 2 and 4 show better fitness ratings compared with Models 1 and 3, respectively. The high fitness ratings and the very small MSE of the four models confirm that the proposed model can effectively estimate the energy consumption of EVs based on sparse GPS observation, no matter which dependent variable is used, either the average energy consumption per kilometer or the energy consumption for an entire trip.

For the energy consumption of an entire trip, all investigated factors directly influence the energy consumption. By contrast, for the energy consumption per kilometre, the investigated factors (such as the service time of the air conditioner and the link length percentage corresponding to each gradient interval) are the spatially averaged values of those for an entire trip. Thus, the spatial averaging process results in a relative reduction in the extent of correlation between the energy consumption and the investigated factors.

5. Conclusions

To improve the accuracy of energy consumption estimation based on sparse GPS observations, an electricity consumption model was proposed based on the kinetic characteristics and unique attributes of EVs. The average energy consumption per kilometre and the energy consumption for an entire trip were each treated as the dependent variable in separate analyses. Sparse GPS observations of 68 EVs in Aichi Prefecture, Japan were collected, and two types of regression models were used for

model calibration. The present work is novel because (1) a relatively comprehensive model for energy consumption estimation is proposed considering work opposing the rolling resistance, aerodynamic friction losses, energy consumption/generation depending on the grade of the route, auxiliary load consumption, and additional energy losses arising from the unstable power output of EVs and (2) two different dependent variables are examined for better understanding the mechanism of estimation error. Results reveal that the proposed method demonstrates a great potential for application in using sparse GPS observations to predict the energy consumption of EVs.

Among the results for the four proposed models, the differences in MSE between the first two models and the second two models reflect the disadvantages of sparse observations for estimating the average energy consumption per kilometre. Due the spatial averaging process, the extent of the correlation between the energy consumption and the investigated factors is reduced.

By contrast, Models 2 and 4, in which the heterogeneity between drivers is considered, no matter whether the average energy consumption per kilometre or the energy consumption for an entire trip is taken as the dependent variable, show very high fitness values (of more than 96%) and highly significant parameter estimations, implying appropriate model specification and a high potential for application in using sparse GPS observations to predict the energy consumption of EVs.

Acknowledgments: The authors thank the Japan Automobile Research Institute (JARI) and the Japan Digital Road Map Association for providing the GPS dataset and the digital road map data with the road gradients, respectively. This study was supported by the National Natural Science Foundation of China (Grant No. 51378091); the Fundamental Research Funds for the Central Universities of China (Grant No. DUT15QY14); a Grant-in-Aid for Scientific Research (No. 25289164) from the Ministry of Education, Culture, Sports, Science, and Technology of Japan and the Japan Society for the Promotion of Science; and a research grant from the Japan Digital Road Map Association.

Author Contributions: Jiangbo Wang and Kai Liu contributed to all aspects of this study, including data collection, data processing, map match processing, model construction, discussion of the results, and the writing of the paper. Toshiyuki Yamamoto contributed to the review of the paper and the interpretation of the results.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Weldon, P.; Morrissey, P.; O'Mahony, M. Environmental impacts of varying electric vehicle user behaviours and comparisons to internal combustion engine vehicle usage—An Irish case study. *J. Power Sources* **2016**, *319*, 27–38. [[CrossRef](#)]
2. Cuma, M.U.; Koroglu, T. A comprehensive review on estimation strategies used in hybrid and battery electric vehicles. *Renew. Sustain. Energy Rev.* **2015**, *42*, 517–531. [[CrossRef](#)]
3. Ahn, K.; Rakha, H.; Trani, A.; Van, A. Estimating vehicle fuel consumption and emissions based on instantaneous speed and acceleration levels. *J. Transp. Eng.* **2002**, *128*, 182–190. [[CrossRef](#)]
4. Liaw, B.Y.; Dubarry, M. From driving cycle analysis to understanding battery performance in real-life electric hybrid vehicle operation. *J. Power Sources* **2007**, *174*, 76–88. [[CrossRef](#)]
5. Wu, X.; Freese, D.; Cabrera, A.; Kitch, W.A. Electric vehicles' energy consumption measurement and estimation. *Transp. Res. Part D* **2015**, *34*, 52–67. [[CrossRef](#)]
6. He, Z.; Gao, M.; Wang, C.; Wang, L.; Liu, Y. Adaptive state of charge estimation for li-ion batteries based on an unscented kalman filter with an enhanced battery model. *Energies* **2013**, *6*, 4134–4151. [[CrossRef](#)]
7. Xing, Y.; Ma, E.W.; Tsui, K.L.; Pecht, M. Battery management systems in electric and hybrid vehicles. *Energies* **2011**, *4*, 1840–1857. [[CrossRef](#)]
8. Jaguemont, J.; Boulon, L.; Dubé, Y. A comprehensive review of lithium-ion batteries used in hybrid and electric vehicles at cold temperatures. *Appl. Energy* **2016**, *164*, 99–114. [[CrossRef](#)]
9. Liu, G.; Lu, L.; Li, J.; Ouyang, M. Thermal modelling of a LiFePO₄/graphite battery and research on the influence of battery temperature rise on EV driving range estimation. In Proceedings of the Vehicle Power and Propulsion Conference (VPPC), Beijing, China, 15–18 October 2013; pp. 1–5.
10. Kambly, K.; Bradley, T.H. Geographical and temporal differences in electric vehicle range due to cabin conditioning energy consumption. *J. Power Sources* **2015**, *275*, 468–475. [[CrossRef](#)]

11. Burgess, S.C.; Choi, J.M.J. A parametric study of the energy demands of car transportation: A case study of two competing commuter routes in the UK. *Transp. Res. Part D* **2003**, *8*, 21–36. [[CrossRef](#)]
12. Gerssen-Gondelach, S.J.; Faaij, A.P.C. Performance of batteries for electric vehicles on short and longer term. *J. Power Sources* **2012**, *212*, 111–129. [[CrossRef](#)]
13. Kambly, K.; Bradley, T.H. Estimating the HVAC energy consumption of plug-in electric vehicles. *J. Power Sources* **2014**, *259*, 117–124. [[CrossRef](#)]
14. Valentina, R.; Viehl, A.; Bringmann, O.; Rosenstiel, W. HVAC system modelling for range prediction of Electric Vehicles. In Proceedings of the Intelligent Vehicles Symposium, Dearborn, MI, USA, 8–11 June 2014; pp. 1145–1150.
15. Travasset-Baro, O.; Rosas-Casals, M.; Jover, E. Transport energy consumption in mountainous roads. A comparative case study for internal combustion engines and electric vehicles in Andorra. *Transp. Res. Part D* **2015**, *34*, 16–26. [[CrossRef](#)]
16. Greenwood, I.D.; Dunn, R.C.M.; Raine, R.R. Estimating the effects of traffic congestion on fuel consumption and vehicle emissions based on acceleration noise. *J. Transp. Eng.* **2007**, *133*, 96–104. [[CrossRef](#)]
17. Sun, Z.; Hao, P.; Ban, X.J.; Yang, D. Trajectory-based vehicle energy/emissions estimation for signalized arterials using mobile sensing data. *Transp. Res. Part D* **2015**, *34*, 27–40. [[CrossRef](#)]
18. Liu, K.; Wang, J.B.; Yamamoto, T.; Morikawa, T. Modelling the multilevel structure and mixed effects of the factors influencing the energy consumption of electric vehicles. *Appl. Energy* **2016**, *183*, 1351–1360. [[CrossRef](#)]
19. Kim, E.; Lee, J.; Shin, K.G. Real-time prediction of battery power requirements for electric vehicles. In Proceedings of the 4th International Conference on Cyber-Physical Systems, Philadelphia, PA, USA, 8–11 April 2013; pp. 1–7.
20. Rauh, N.; Franke, T.; Krems, J.F. Understanding the impact of electric vehicle driving experience on range anxiety. *Human Factors Ergon. Soc.* **2014**, *57*, 177–187. [[CrossRef](#)]
21. Tang, T.; Huang, H.; Shang, H. Influences of the driver's bounded rationality on micro driving behavior, fuel consumption and emissions. *Transp. Res. Part D* **2015**, *41*, 423–432. [[CrossRef](#)]
22. Díaz, A.; Serradilla, F.; Naranjo, J.E.; Anaya, J.J.; Jiménez, F. Modelling the driving behavior of electric vehicles using smartphones and neural networks. *IEEE Intell. Trans. Syst. Mag.* **2014**, *6*, 44–53. [[CrossRef](#)]
23. Tang, S.; Yu, C.; Wang, X.; Guo, X.; Si, X. Remaining useful life prediction of lithium-ion batteries based on the wiener process with measurement error. *Energies* **2014**, *7*, 520–547. [[CrossRef](#)]
24. Liu, D.; Wang, H.; Peng, Y.; Xie, W.; Liao, H. Satellite lithium-ion battery remaining cycle life prediction with novel indirect health indicator extraction. *Energies* **2013**, *6*, 3654–3668. [[CrossRef](#)]
25. Ozkurt, C.; Camci, F.; Atamuradov, V.; Odorry, C. Integration of sampling based battery state of health estimation method in electric vehicles. *Appl. Energy* **2016**, *175*, 356–367. [[CrossRef](#)]
26. You, G.; Park, S.; Oh, D. Real-time state-of-health estimation for electric vehicle batteries: A data-driven approach. *Appl. Energy* **2016**, *176*, 92–103. [[CrossRef](#)]
27. Fiori, C.; Ahn, K.; Rakha, H.A. Power-based electric vehicle energy consumption model: Model development and validation. *Appl. Energy* **2016**, *168*, 257–268. [[CrossRef](#)]
28. Xu, G.; Li, W.; Xu, K.; Song, Z. An intelligent regenerative braking strategy for electric vehicles. *Energies* **2011**, *4*, 1461–1477. [[CrossRef](#)]
29. Li, L.; Li, X.; Wang, X.; Song, J.; He, K.; Li, C. Analysis of downshift's improvement to energy efficiency of an electric vehicle during regenerative braking. *Appl. Energy* **2016**, *176*, 125–137. [[CrossRef](#)]
30. Qiu, C.; Wang, G. New evaluation methodology of regenerative braking contribution to energy efficiency improvement of electric vehicles. *Appl. Energy* **2016**, *119*, 389–399. [[CrossRef](#)]
31. Van Sterkenburg, S.; Rietveld, E.; Rieck, F.; Veenhuizen, B.; Bosma, H. Analysis of regenerative braking efficiency—A case study of two electric vehicles operating in the Rotterdam area. In Proceedings of the Vehicle Power and Propulsion Conference (VPPC), Chicago, IL, USA, 6–9 September 2011; pp. 1–6.
32. Zhang, R.; Yao, E. Electric vehicles' energy consumption estimation with real driving condition data. *Transp. Res. Part D* **2015**, *41*, 177–187. [[CrossRef](#)]
33. Wu, X.; Dong, J.; Lin, Z. Cost analysis of plug-in hybrid electric vehicles using GPS-based longitudinal travel data. *Energy Policy* **2014**, *68*, 206–217. [[CrossRef](#)]
34. Wu, X.; Avquzzaman, M.; Lin, Z. Analysis of plug-in hybrid electric vehicles' utility factors using GPS-based longitudinal travel data. *Transp. Res. Part C* **2015**, *57*, 1–12. [[CrossRef](#)]

35. Cauwer, C.D.; Mierlo, J.V.; Coosemans, T. Energy consumption prediction for electric vehicles based on real-world data. *Energies* **2015**, *8*, 8573–8593. [[CrossRef](#)]
36. Brady, J.; O'Mahony, M. Development of a driving cycle to evaluate the energy economy of electric vehicles in urban areas. *Appl. Energy* **2016**, *177*, 165–178. [[CrossRef](#)]
37. Oshyani, M.F.; Sundberg, M.; Karlström, A. Consistently estimating link speed using sparse GPS data with measured errors. *Procedia Soc. Behav. Sci.* **2014**, *111*, 1227–1236. [[CrossRef](#)]
38. Rahmani, M.; Koutsopoulos, H.N. Path inference from sparse floating car data for urban networks. *Transp. Res. Part C* **2013**, *30*, 41–54. [[CrossRef](#)]
39. Quddus, M.; Washington, S. Shortest path and vehicle trajectory aided map-matching for low frequency GPS data. *Transp. Res. Part C* **2015**, *55*, 328–339. [[CrossRef](#)]
40. Hyodo, T.; Watanabe, D.; Wu, M.C. Estimation of energy consumption equation for electric vehicle and its implementation of driving behavior. In Proceedings of the 13th World Conference on Transport Research, Rio de Janeiro, Brazil, 15–18 July 2013; pp. 1–12.
41. Guzzella, L.; Sciarretta, A. Vehicle propulsion system: Introduction to modelling and optimization. *IEEE Trans. Comput. Aided Des. Integr. Circuits Syst.* **2007**, *26*, 67–79.
42. Wang, J.B.; Liu, K.; Yamamoto, T.; Morikawa, T. Improving estimation accuracy of electric vehicle energy consumption considering the effects of ambient temperature. *Energy Procedia* **2017**, in press.
43. Luke, D.A. *Multilevel Modelling*; Sage Publishing House: Thousand Oaks, CA, USA, 2004; pp. 18–70.



© 2017 by the authors; licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).