Article

Bench-Scale Cultivation of Microalgae *Scenedesmus almeriensis* for CO₂ Capture and Lutein Production

Antonio Molino ¹ , Sanjeet Mehariya ^{1,2} , Despina Karatza ², Simeone Chianese ^{2,*} ,
Angela Iovine ^{1,2}, Patrizia Casella ¹, Tiziana Marino ² and Dino Musmarra ²

¹ ENEA, Italian National Agency for New Technologies, Energy and Sustainable Economic Development, Department of Sustainability-CR Portici. P. Enrico Fermi, 1, 80055 Portici (NA), Italy

² Department of Engineering, University of Campania “Luigi Vanvitelli”, Real Casa dell’Annunziata, Via Roma 29, 81031 Aversa (CE), Italy

* Correspondence: simeone.chianese@unicampania.it; Tel.: +39-081-5010237

Received: 18 June 2019; Accepted: 21 July 2019; Published: 22 July 2019

Abstract: In this study, *Scenedesmus almeriensis* as green microalga was cultivated on bench-scale for carbon dioxide (CO₂) capture and lutein production. The autotrophic cultivation of *S. almeriensis* was carried out by using a vertical bubble column photo-bioreactor (VBC-PBR) with a continuous flow of a gaseous mixture of oxygen (O₂), nitrogen (N₂), and CO₂, the latter in content of 0.0–3.0 %v/v. The liquid phase was batch. *S. almeriensis* growth was optimized. In addition, lutein extraction was carried out by using accelerated solvent extraction with ethanol as Generally Recognized as Safe (GRAS) solvent at 67 °C and 10 MPa. Upon optimization of CO₂ concentration, the maximum biomass productivity, equal to 129.24 mg·L^{−1}·d^{−1}, was achieved during the cultivation by using a content of CO₂ equal to 3.0 %v/v and it allowed to obtain a lutein content of 8.54 mg·g^{−1}, which was 5.6-fold higher in comparison to the analogous process carried out without CO₂ addition. The ion chemical analysis in the growth medium showed that by gradually increasing CO₂ content, the nutrient consumption during the growth phase also increased. This study may be of potential interest for lutein extraction at industrial scale, since it is focused on pigment production from a natural source with a concomitantly CO₂ capture.

Keywords: microalgae; autotrophic cultivation; lutein; nutraceutical; accelerated solvent extraction; generally recognized as safe (GRAS) solvent; CO₂ capture rate; CO₂ conversion efficiency

1. Introduction

Microalgae cultivation is widely accepted as a valid method for carbon dioxide (CO₂) capture from industrial plants, and for the extraction of high-value products, such as carotenoids and fatty acids [1–8]. Microalgae-based CO₂ biofixation and biomass production are strongly dependent on the microalgae strain selection and the adopted growth conditions [5]. *Scenedesmus almeriensis*, being the highest lutein natural producer, has attracted growing interest and it represents the only commercialized microalgae for pigment extraction [9–12]. Lutein is classified as a primary xanthophyll because of the presence of two hydroxyl functional groups in the structure [13–15]. It acts as a light energy harvesting compound, which improves the photosynthesis efficiency and it prevents photodamage [16]. A daily lutein intake of 1 mg/kg body weight was suggested by the European Food Safety Authority (EFSA) [17], which could provide several health benefits. Moreover, lutein also acts as an antioxidant, anti-inflammatory, and colorant, which promotes its application for nutraceutical and pharmaceutical purposes [9]. Lutein is accumulated in the macula of the human eye retina and it is able to prevent or ameliorate cardiovascular diseases [18].

An enhanced production of lutein from microalgae can be achieved through a proper design of suitable culture strategies. The main parameters typically considered for potential microalgal producers of lutein are lutein content and biomass productivity. As reported by several authors, lutein content can be improved by optimizing the main physico-chemical (CO_2 content, inoculum concentration, light intensity, temperature, and pH) and hydrodynamic (flow rate, distribution by mixing, and CO_2 mass transfer) parameters [1,7,9,14,15,19–29]. Furthermore, under autotrophic growth conditions, microalgae cultivation is free of contamination from external sources, and the pH, if it is necessary, can also be regulated by feeding CO_2 [15]. Autotrophic cultivation of microalgae could offer several environmental benefits, such as CO_2 sequestration for a reduced greenhouse gas (GHG) emission [15,29–31]. The autotrophic growth requires inorganic carbon sources under illumination, which could potentially be derived from sun light, thus optimizing the overall production cost.

Xie et al. [14] evaluated the effect of CO_2 concentration on microalgae biomass and lutein production from *Desmodesmus* sp. F51, and they found that by fixing CO_2 concentration at 0.03, 2.5, 5.0, 7.5, 10.0, and 12.5%, biomass productivity and specific growth rate increased with increasing CO_2 concentration from 0.03% to 2.5%, and they showed a decrease when CO_2 concentration was further increased to 12.5% [14]. Therefore, in this study, a CO_2 content of 3 %v/v as a maximum value was selected.

The extraction of intracellular compounds from microalgae biomass by using chemical solvents is the most reliable method to extract compounds by microalgae. Extraction efficiency and lutein recovery by organic solvents are higher than those associated with other physical methods. However, the effectiveness of the used solvent relies intensely on microalgae strains and on physical properties of microalgae biomass. Additionally, after the solvent extraction, lutein could be used in nutraceutical and pharmaceutical industries, while the exhausted biomass could be used in an integrated biorefinery for bioenergy production [32–34].

The effect of different CO_2 contents, in the range of 0–3 %v/v, on biomass and lutein production, and on average CO_2 capture rate and CO_2 conversion efficiency, was investigated. Biomass harvesting was carried out through vacuum filtration, while the subsequent solvent extraction of lutein was performed by using the accelerated solvent extraction (ASE) technique. Ethanol, as Generally Recognized as Safe (GRAS) solvent, was used for the extraction step, operating at 67 °C, 10 MPa. Extraction was performed on mechanically pretreated *S. almeriensis* biomass. Lutein analysis was carried out by means of u-HPLC analysis.

2. Materials and Methods

2.1. Microalgae and Growth Medium

Microalgae *S. almeriensis* were supplied by AlgaRes Srl, Rome, Italy, and used as the inoculum for cultivation under laboratory conditions. Microalgae cells were cultivated using a modified Mann and Myers medium [19,35], which consisted of: NaNO_3 (1.0 g/L), K_2HPO_4 (0.1 g/L), $\text{MgSO}_4 \cdot 7\text{H}_2\text{O}$ (1.2 g/L), and CaCl_2 (0.3 g/L). Also, a micronutrient solution of 10 mL was added into 990 mL of Mann and Myers medium. The micronutrients stock solution contained Na_2EDTA (0.001 mg/L), MnCl_2 (1.4 mg/L), $\text{ZnSO}_4 \cdot 7\text{H}_2\text{O}$ (0.33 mg/L), $\text{FeSO}_4 \cdot 2\text{H}_2\text{O}$ (2 mg/L), $\text{CuSO}_4 \cdot 5\text{H}_2\text{O}$ (0.002 mg/L), and $\text{Co}(\text{NO}_3)_2 \cdot 6\text{H}_2\text{O}$ (0.007 mg/L).

2.2. Photo-Bioreactor

S. almeriensis was cultivated in a vertical bubble column photo-bioreactor (VBC-PBR), made of Plexiglas, with a working volume of 28.5 L (effective height: 680 mm; external diameter: 250 mm; thickness: 10 mm) and with the volume to surface ratio (V/S) of 56.5 L/m². The VBC-PBR was equipped with control and monitoring systems for monitoring and regulating gaseous mixture flow rate, temperature, pH, and light intensity. VBC-PBR was fed by a gaseous mixture ($\text{N}_2/\text{O}_2/\text{CO}_2$) from cylinders. Gaseous mixture flow rate was controlled by using Bronkhorst controllers (The Netherlands),

with flow control accuracy of 0.5%. The bottom of the reactor was equipped with 6 sintered steel spargers, installed through 6 filleted holes (1/2"), to feed the gaseous mixture into the photo-bioreactor. The top of the reactor was equipped with a temperature sensor (thermocouple) and with a pH sensor. Temperature measurement was used to drive the temperature control system by modifying the flow rate of a cooling fluid flowing into an AISI 316L coaxial pipe (diameter = 60.3 mm, thickness = 1 mm). A temperature control system allowed the regulation of the temperature inside the reactor with a precision of ± 1 °C in the range of 15–35 °C, thanks to a heat pump.

The lighting system consisted of a semi-cylinder, located at a distance of 100 mm from the VBC-PBR with blue, white, and red lights from a selective LED system (only blue/only white/only red, or a mix of them), with a light intensity in the range of 0–5000 lux on the surface of the VBC-PBR. The diameter of the lighting system was 350 mm, which was controlled and regulated by SCADA (Supervisory Control and Data Acquisition). The SCADA system was equipped with a touch-screen, custom software and PC to collect and record experimental data of temperature, gas flow rate, pH, and light intensity. A schematization of the experimental set-up in Figure 1 is sketched.

Figure 1. Experimental set-up schematization.

2.3. Growth Conditions

Cultivation of microalgae was carried out by using a modified Mann and Myers medium with the above mentioned concentration (Section 2.1.). During investigations, a desired amount of inoculum was added to achieve an optical density of 0.6–0.7 at 420 nm. Each investigation was carried out by using a working volume of 28.5 L. The microalgae growth was performed under white light with a lux intensity on the VBC-PBR surface of 4000 lux, and by continuously feeding, for all the cultivation time, a gaseous mixture stream consisting of O₂, N₂, and CO₂ with a flow rate of 300 mL·min^{−1}. The CO₂ content was varied in the range of 0–3.0 %v/v (O₂ = 21 %v/v). Cultivation was carried out by keeping temperature constant at 28 °C. Each experimental condition was investigated three times, and for each condition, the standard deviation (SD) value was calculated.

2.4. Average CO₂ Capture Rate and CO₂ Conversion Efficiency

Average CO₂ capture rate, R_{CO_2} (gCO₂·L^{−1}·d^{−1}), can be assessed by considering the elemental carbon content of the microalgae cell and the biomass productivity, according to the following equation [36]:

$$R_{CO_2} = C_C \cdot P \cdot \left(\frac{M_{CO_2}}{M_C} \right) \quad (1)$$

where C_c is the carbon content of the microalgae cell (% wt), P is the biomass productivity ($g_{\text{biomass}} \cdot L^{-1} \cdot d^{-1}$), M_{CO_2} is the molecular weight of CO_2 , and M_C is the molecular weight of carbon.

Average CO_2 capture efficiency can be assessed according to the following equation [37]:

$$E_{CO_2} = \frac{R_{CO_2} \cdot V_{PBR} \cdot t}{\rho_{CO_2} V_{CO_2}} \times 100 \quad (2)$$

where R_{CO_2} , V_{PBR} , V_{CO_2} , and ρ_{CO_2} are the average CO_2 capture rate ($g_{CO_2} \cdot L^{-1} \cdot d^{-1}$), the volume of the VBC-PBR (L), total CO_2 consumed (L) during the cultivation time t (d), and the density of CO_2 ($g \cdot L^{-1}$), respectively.

2.5. Analytical Methods

2.5.1. Determination of Algal Cell Concentration and Dry Cell Weight

S. almeriensis cell growth was monitored by determining the absorbance of each sample at 420 and 690 nm for Chlorophyll-*a*, and 480 and 620 nm for Chlorophyll-*b*, by using a UV/Visible spectrophotometer (Multiskan, Thermo Fisher Scientific, USA). The biomass dry cell weight (DCW) was calculated using the absorbance values at different biomass concentrations evaluated during the growth phase, obtaining a calibration curve between absorbance and concentration as showed in Equation (3).

$$DCW = (0.0867 \cdot A) - 0.1868 \quad (3)$$

where DCW is concentration of biomass on dry cell weight (g/L) and A is the total absorbance obtained from the sum of the absorbance values obtained for the four chlorophyll wavelengths.

The final dry weight was determined through cell culture dewatering by a vacuum filtration system, using vacuum filters with a pore size of 0.45 μm (Sigma-Aldrich, USA); microalgal pellets from dewatering were lyophilized for 24 h.

2.5.2. Accelerated Solvent Extraction

Lutein extraction was carried out from mechanically pre-treated biomass of *S. almeriensis* cells, by using Dionex-ASE 200 extractor (Salt Lake City, UT, USA). The pretreatment was performed at optimized conditions, according to the procedure described elsewhere [38]. Four consecutive extraction cycles (single extraction cycle = 20 min) were performed by using ethanol at optimized extraction conditions, 67 °C and 10 MPa, for the complete biomass discoloring, as reported in a previous work [39]. At the end of each extraction cycle, extracts were collected into 40 mL amber glass vials by flushing the system with 6.6 mL of fresh solvent, and the system was purged for 1 minute with nitrogen (Purity $\geq 99.999\%$).

2.5.3. Nutrient Consumption Chemical Analysis

The nutrient (anions and cations) concentrations were analyzed using an ion Chromatograph (Dionex™ ICS-1100, Thermo Scientific, Massachusetts, USA), as reported by Pruvost et al. [40], at the beginning and at the end of the growth period. The Dionex ICS-1100 was an integrated ion chromatography system equipped with a pump, injection valve, and conductivity detector. Several nutrients such as Mg^{2+} , SO_4^{2-} , Na^+ , NO_3^- , NO_2^- , Ca^{2+} , Cl^- , K^+ , and PO_4^{3-} , which are essential for growth of microalgae, were analyzed.

2.5.4. Lutein Analysis

The extract obtained after each extraction cycle was equally transferred into two different vials by adding BHT at 0.1 % wt as antioxidant for gravimetric analysis and saponification. The total lutein content was gravimetrically quantified, after the complete removal of the solvent using a Zymark TurboVap evaporator (Zymark, Hopkinton, MA, USA). Lutein analysis consisted of two steps: The first

one was the saponification of samples to avoid the overlap of the spectra with the species present in the carotenoid family (lipids and chlorophylls) [41–43]; the second one was the measurement by using u-HPLC technology (Agilent 1290 Infinity II). The detailed procedure is reported elsewhere [41–43].

3. Results and Discussion

3.1. Effect of CO₂ Content on Culture Medium pH

For each growth condition investigated, during the days of microalgal cultivation, a slight variation of pH was observed. In particular, pH increased from the initial value of 7.5 at the beginning of the cultivation, to the final value of 8.5 at the end of the cultivation; therefore, for the CO₂ concentration range investigated (0–3.0 %v/v), the pH of the culture medium was marginally affected by the CO₂ content, as reported by several authors [44,45]. The increase of the pH value during the cultivation can be attributed to the alkalization of the medium as a result of CO₂ biofixation during photosynthesis: Carbonate and bicarbonate, and hydroxide contents increased, while CO₂ concentration decreased [46].

3.2. Effect of CO₂ Content on Biomass Concentration

The effect of CO₂ on the concentration of the *S. almeriensis* and on biomass productivity, i.e., the biomass produced per reactor liter and per day, are shown in Figures 2 and 3, respectively.

By increasing the cultivation time, the biomass concentration increased until the achievement of a maximum value (Figure 2). By increasing CO₂ content, an increase of both biomass productivity, with the consequence reduction of the cultivation time required for the achievement of the maximum value, and of the concentration of the biomass were observed, despite the concentration of the microalgae fed with a gaseous mixture with a CO₂ content of 1.5 %v/v and the one fed with a gaseous mixture with a CO₂ content of 3.0 %v/v being comparable, even if the cultivation time decreased. The observed increase in biomass concentration reflected an efficient photosynthesis rate, promoting an upregulated expression of RuBisCO in the presence of a determined inorganic carbon content [47]. However, the optimum CO₂ content also contributed to maintain pH close to the neutral value. For high CO₂ adaptation, cells temporarily reduced the synthesis of organic carbon and provided more ATP to assure intracellular pH stability through gene regulation and increasing the energy allocation proportion PSI/PSII [29].

With a CO₂ content of 0 %v/v (O₂ = 21 %v/v – N₂ = 79 %v/v), a maximum concentration of biomass equal to 0.07 g·L^{−1} after 11 days of cultivation was observed, while it increased to 0.72 g·L^{−1} after 18 days with a content of CO₂ of 0.5 %v/v. With CO₂ contents of 1.5 %v/v and of 3 %v/v, the maximum biomass concentrations equal to 0.95 g·L^{−1} after a cultivation time of 16 days, and to 0.92 mg·L^{−1} after a cultivation time of 10 days, were measured, respectively. By increasing CO₂ content from 0 to 3 %v/v, biomass productivity increased from about 4 mg·L^{−1}·d^{−1} to about 130 mg·L^{−1}·d^{−1}, with productivities of about 39 mg·L^{−1}·d^{−1} and 65 mg·L^{−1}·d^{−1} at CO₂ contents of 0.5 %v/v and 1.5 %v/v, respectively. Passing from 0 %v/v to 3 %v/v, biomass productivity increased of about 32-fold.

Cheng et al. [48] reported that the amount of CO₂ present in the air (0.04%) is inadequate to achieve high cell density and on the other hand, an excess may inhibit the carbonic anhydrase enzyme, which in turn may reduce biomass productivity. Sepulveda et al. [49] reported that *S. almeriensis* was one of the most productive strains when using it in CO₂ capture processes, with a biomass productivity of 1.0 g·L^{−1}·day^{−1} and with 2.8 g·L^{−1}·day^{−1} of CO₂ consumed. Acien et al. [50] reported a consumption of CO₂ of 2.31 gCO₂·g_b^{−1} for *S. almeriensis*.

Figure 2. Effect of CO₂ content on *S. almeriensis* biomass concentration during cultivation.

Figure 3. Effect of CO₂ content on *S. almeriensis* biomass productivity.

3.3. Effect of CO₂ Content on Carbon Content, Average CO₂ Capture Rate, and CO₂ Conversion Efficiency

Carbon content, average CO₂ capture rate, and CO₂ conversion efficiency, including biomass productivity, are shown in Table 1. As reported, the highest carbon element of microalgae cells (C_C) and the highest average CO₂ capture rate (R_{CO_2}) were found with the highest CO₂ content (3 %v/v), while the highest CO₂ conversion efficiency (E_{CO_2}) was found with the lowest CO₂ content (0.5 %v/v).

Table 1. Carbon elemental, average CO₂ capture rate, and CO₂ capture efficiency.

CO ₂ Content (%v/v)	C _C (% w/w)	P (g _{biomass} L ⁻¹ d ⁻¹)	R _{CO2} (g _{CO2} L ⁻¹ d ⁻¹)	E _{CO2} (%)
0.5	43.4	0.039	0.06	44.5
1.5	42.4	0.065	0.10	24.3
3.0	49.9	0.129	0.24	28.4

Average CO₂ capture rates assessed in the present work are comparable with the ones available in the literature for *Scenedesmus sp.*; however, it should be considered that different growth conditions and fluid dynamics were used. Chaudhary et al. [37] investigated CO₂ capture rate through *Scenedesmus obliquus* cultivation by using an airlift bubble column photo-bioreactor (PBR) (working volume = 7 L), supplied with gas (air + CO₂ 5 %v/v) at a flow rate of 1.4 L·min⁻¹ and irradiated with cool white fluorescent light (3 tubes × 24 W), finding an average CO₂ capture rate of 0.13 g_{CO2}·L⁻¹·d⁻¹. CO₂ capture rate through *Scenedesmus obliquus* cultivation by using tubular-type PBR (working volume = 1.8 L), supplied with gas (air + CO₂ 12 %v/v) at a gas volume per liquid volume per min of 0.3 and irradiated with 3200 lux brightness provided by 40 W fluorescent daylight type lamps, was also investigated by Radmann et al. [51]; they found a biomass productivity of 0.6 g_{biomass}·L⁻¹·d⁻¹ and a CO₂ capture rate of 0.11 g_{CO2}·L⁻¹·d⁻¹. Jin et al. [52] investigated CO₂ capture rate through *Scenedesmus sp.* cultivation by using a bubble column PBR (working volume = 1 L), supplied with gas (air + CO₂ 10 %v/v) at a gas volume per liquid volume per min of 0.2 and irradiated with a light intensity of 200 μmol·m⁻²·s⁻¹, finding an average CO₂ capture rate of 0.46 g_{CO2}·L⁻¹·d⁻¹. Ong et al. [53] found a CO₂ capture rate of 0.021 g_{CO2}·L⁻¹·d⁻¹ for *Chlorella sp.* by using a vertical bubble column (working volume = 40 L) supplied with gas (air + CO₂ 5 %v/v) at a gas volume per liquid volume per min of 0.25 and irradiated with a light intensity of 1500 μmol·m⁻²·s⁻¹. Hsueh et al. [53] found a CO₂ capture rate of 0.141 g_{CO2}·L⁻¹·d⁻¹ for *Thermosynechococcus sp.* by using a bubble column (working volume = 40 L) supplied with gas (air + CO₂ 10 %v/v) at 1 L·min⁻¹ and irradiated with a light intensity of 10000 lux. Nayak et al. [54] reported that the CO₂ biofixation rate of *Scenedesmus sp.*, when aerated with more than 1 %v/v CO₂ by using a bubble column photo-bioreactor (working volume = 0.5), was in the range of 0.27–0.37 g·L⁻¹·d⁻¹.

In terms of CO₂ capture efficiency, *S. almeriensis* performance are comparable with performances of several microalgal species [55,56].

3.4. Role of CO₂ Content on Nutrient Consumption

Nutrients are essential for microalgae cell growth, and a similar concentration of nutrients was kept in each growth phase. The concentration of the main ions of the growth medium at the beginning of the cultivation are reported in Table 2. The concentration of NO₃⁻ ions was the highest with respect to the rest of nutrients. It is worth highlighting that in the case of growth with a CO₂ content of 0.5 %v/v, nutrient concentration was slightly lower because the growth was continued from the 0.0 %v/v CO₂ content step.

Table 2. Initial concentration of nutrients during the *S. almeriensis* cultivation.

Nutrients (mg/L)	CO ₂ Content (%v/v)			
	0.0	0.5	1.5	3.0
Mg ²⁺	100.44	100.25	98.805	109.13
SO ₄ ²⁻	451.28	432.27	459.06	442.47
Na ⁺	259.45	235.82	265.57	268.94
NO ₃ ⁻	620.58	589.12	680.73	622.24
Ca ²⁺	99.35	95.32	98.48	96.19
Cl ⁻	165.78	161.87	185.80	205.22
K ⁺	38.8	37.98	47.78	48.56
PO ₄ ³⁻	47.58	25.68	47.88	47.21

Figure 4 illustrates the effect of CO₂ content on nutrient consumption, measured at the end of the growth of *S. almeriensis*. Data highlighted a complete consumption of phosphate ions, which could limit the cell growth. The increase of CO₂ content increased the nutrient consumption rate. However, the longer cultivation times (i.e., 20 days for CO₂ = 0.5 %v/v; 16 days for CO₂ = 1.5 %v/v; 13 days for CO₂ = 3.0 %v/v) also promoted the nutrient intake. Among all the supplied nutrients, nitrate and phosphate were highly consumed during the growth phase. The possible explanation for this phenomenon is that a nitrogen source is essential for protein synthesis, and lutein exists as a nitrogenous macromolecule (i.e., light-harvesting complexes; LHCII) in microalgae [15]. NO₃[−] and PO₄^{3−} ions are the most important nutrients for cell proliferation during growth of microalgae [57], as confirmed by the present study. However, the consumption of NO₃[−] ions was 5.0, 59.88, 77.26, and 87.22% during the growth with CO₂ contents of 0.0, 0.5, 1.5, and 3.0 %v/v, respectively. This observation can be justified by considering a limited carbon source, which leads to a stress condition on microalgae growth cells, causing a lower biological consumption of nutrients. At the end of the growth, a lower consumption of both Na⁺ and Cl[−] ions was observed, in comparison to the consumption of other nutrients, with a consumption below 25%. The consumption of Cl[−] ions decreased by increasing CO₂ content from 0.5 %v/v to 3.0 %v/v, which could be explained by considering a lower cultivation time. Similar results were observed during the cultivation of *Chlorella vulgaris* [58]. Chen et al. [15] evaluated the effect of nitrate and they reported that a sufficient amount of nitrogen in the medium was required to enhance lutein accumulation in the *Chlorella sorokiniana* Mb-1 strain. More importantly, it could be possible that the lutein content may depend on the residual nitrogen concentration [14].

Figure 4. Effect of CO₂ content on nutrient consumption efficiency during cultivation of *S. almeriensis*. Standard deviation was less than 5% in all operative conditions.

3.5. Extraction Yield and Lutein Production from *S. almeriensis*

The increase of CO₂ content of the gaseous mixture from 0.0 %v/v to 3.0 %v/v improved the extraction yield and the lutein content, as shown in Figure 5. The harvested *S. almeriensis* biomass during the growth with a content of CO₂ of 0.0 %v/v showed extraction yield of about 172.28 mg·g^{−1} with a lutein content of 1.51 mg·g^{−1}. With a content of CO₂ of 0.5 %v/v, an increase of the extraction yield of 1.4-fold and a lutein content of 3.1-fold higher than that measured in absence of CO₂ were found. The highest extraction yield and the highest lutein content, equal to 328.05 mg·g^{−1} and 8.54 mg·g^{−1}, respectively, were obtained by feeding microalgae with a gaseous mixture containing

a CO₂ concentration of 3.0 %v/v. The increase of lutein content in biomass growth in stressed conditions might indicate that lutein could play a role in protecting cells from photodamage [20].

Figure 5. Effect of CO₂ content on extraction yield and lutein content from *S. almeriensis*.

3.6. Comparison of Biomass Productivity and Lutein Content

Biomass productivity and lutein content under the optimal growth condition defined in this study, including the comparison with literature data, are reported in Table 3. Heterotrophic and mixotrophic cultivations support higher biomass productivity; a feasible lutein production from a mixotrophic microalgae culture, which has been rarely mentioned in the literature, is also shown—however, lutein content is lower than the one of most microalgae autotrophic cultivation (Table 3). The biomass productivity is lower during autotrophic cultivation of different microalgae strains, while a significant amount of lutein can be produced. Moreover, autotrophic cultivation brings several advantages such as capture of CO₂, helping in reduction of the GHG and allowing the development of integrated biorefinery based on flue gas carbon sequestration through microalgae, and the simultaneous production of commercially valuable microalgal products, such as lutein and biodiesel [7]. Furthermore, autotrophic cultivation of microalgae might use sun as an economic source of light, which could be an effective strategy to economize the microalgal bioprocess [59]. Recently, Patel et al. [59] proposed the mixotrophic cultivation of *Chlorella protothecoides*, which could enhance the biomass productivity. Therefore, integration of different strategies could be a potential tool for the production of higher amounts of lutein with other bioactive compounds.

Interestingly, a significant amount of lutein was attained in this study during autotrophic cultivation of *S. almeriensis*, which is the highest among the ones reported in Table 3.

Table 3. Biomass productivity and lutein content comparison.

Microalgal Strain	Operation Mode	Cultivating Conditions	Biomass Productivity (g/L/day)	Lutein Content (mg/g)	References
<i>Chlorella protothecoides</i>	Batch	Heterotrophic	1.99	1.98	[28]
<i>Coccomyxa acidophila</i>	Batch	Mixotrophic	0.26	3.50	[21]
<i>Chlorella sorokiniana</i>	Batch	Autotrophic	0.84	3.0	[23]
<i>Scenedesmus</i> sp.	Batch	Mixotrophic	0.38	1.05	[60]
<i>Chlorella sorokiniana</i> Mb-1	Batch	Mixotrophic	1.03	3.86	[15]
<i>Scenedesmus obliquus</i> FSP-3	Batch	Autotrophic	0.92	4.52	[25]
<i>Chlorella zofingiensis</i>	Batch	Autotrophic	0.45	7.2	[61]
<i>Scenedesmus almeriensis</i>	Continuous	Autotrophic	0.87	5.5	[27]
<i>Scenedesmus almeriensis</i>	Continuous	Autotrophic	0.72	5.3	[26]
<i>Desmodesmus</i> sp. F51	Fed-batch	Autotrophic	0.65	5.5	[62]
<i>Coccomyxa onubensis</i>	Semi-continuous	Autotrophic	0.55	6.2	[63]
<i>Muriellopsis</i> sp.	Batch	Autotrophic	0.04	4.3	[64]
<i>Chlorella zofingiensis</i>	Batch	Autotrophic	0.88	3.4	[64]
<i>Chlorella minutissima</i> MCC-27	Batch	Autotrophic	0.57	6.05	[24]
<i>Chlorella minutissima</i>	Batch	Autotrophic	0.67	6.37	[7]
<i>Scenedesmus almeriensis</i>	Batch	Autotrophic	0.13	8.54	This study

4. Conclusions

The present study shows the role of CO₂ content on cultivation of *S. almeriensis* for biomass and lutein production; moreover, CO₂ capture rate and CO₂ conversion efficiency for *S. almeriensis* were also assessed. The optimal amount of inorganic carbon source improved the photosynthetic efficiency. By increasing the CO₂ content, the biomass productivity increased; the highest biomass concentration of about 0.94 g·L⁻¹ was obtained with a content of CO₂ of 1.5 %v/v, with a direct correlation with the extraction yield and the lutein content. Moreover, a similar trend for nutrient consumption was also found. The nutrient chemical analysis shows that a content of CO₂ of 3.0 %v/v better supports nutrient intake during the growth phase, while consumptions of nitrate and phosphate have been found as the highest ones for each test. The increase of CO₂ content increased the extraction yield, as well as the lutein content. With a CO₂ content of 3 %v/v, the extraction yield and lutein content were about 328 mg·g⁻¹ and 8 mg·g⁻¹ of dry biomass, respectively. It is worth pointing out that due to the impressive lutein content, *S. almeriensis* could be a suitable candidate for potential commercial production of microalgae-derived natural lutein.

This study could positively contribute to the present scientific literature showing the sustainable integration of CO₂ sequestration with the concomitant microalgae cultivation for the production of lutein and of other high value-added chemicals.

Author Contributions: Conceptualization, D.M. and A.M.; Data Curation, S.M. and A.I.; Formal Analysis, A.I.; Investigation, S.M.; Methodology, S.C., D.K., A.I., P.C., and A.M.; Writing—Original Draft, S.M. and T.M.; Writing—Review and Editing, S.C. and D.M.; Project Administration, A.M.; Resources, A.M.; Supervision, D.M. and A.M.

Funding: This research was funded by a Bio Based Industries Joint Undertaking under the European Union's Horizon 2020 research and innovation program, grant agreement No. 745695 (VALUEMAG).

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Cerón, M.C.; Campos, I.; Sánchez, J.F.; Acien, F.G.; Molina, E.; Fernández-Sevilla, J.M. Recovery of lutein from microalgae biomass: Development of a process for *Scenedesmus almeriensis* biomass. *J. Agric. Food Chem.* **2008**, *56*, 11761–11766. [CrossRef] [PubMed]
2. Cheng, J.; Li, K.; Zhu, Y.; Yang, W.; Zhou, J.; Cen, K. Transcriptome sequencing and metabolic pathways of astaxanthin accumulated in *Haematococcus pluvialis* mutant under 15% CO₂. *Bioresour. Technol.* **2017**, *228*, 99–105. [CrossRef] [PubMed]

3. Chiu, S.Y.; Kao, C.Y.; Chen, C.H.; Kuan, T.C.; Ong, S.C.; Lin, C.S. Reduction of CO₂ by a high-density culture of *Chlorella* sp. in a semicontinuous photobioreactor. *Bioresour. Technol.* **2008**, *99*, 3389–3396. [[CrossRef](#)] [[PubMed](#)]
4. Chiu, S.-Y.; Kao, C.-Y.; Tsai, M.-T.; Ong, S.-C.; Chen, C.-H.; Lin, C.-S. Lipid accumulation and CO₂ utilization of *Nannochloropsis oculata* in response to CO₂ aeration. *Bioresour. Technol.* **2009**, *100*, 833–838. [[CrossRef](#)] [[PubMed](#)]
5. Choi, Y.Y.; Joun, J.M.; Lee, J.; Hong, M.E.; Pham, H.M.; Chang, W.S.; Sim, S.J. Development of large-scale and economic pH control system for outdoor cultivation of microalgae *Haematococcus pluvialis* using industrial flue gas. *Bioresour. Technol.* **2017**, *244*, 1235–1244. [[CrossRef](#)] [[PubMed](#)]
6. de Assis, T.C.; Calijuri, M.L.; Assemany, P.P.; de Paula, A.S.A.; Martins, M.A. Using atmospheric emissions as CO₂ source in the cultivation of microalgae: Productivity and economic viability. *J. Clean. Prod.* **2019**, *215*, 1160–1169. [[CrossRef](#)]
7. Dineshkumar, R.; Dash, S.K.; Sen, R. Process integration for microalgal lutein and biodiesel production with concomitant flue gas CO₂ sequestration: a biorefinery model for healthcare, energy and environment. *RSC Adv.* **2015**, *5*, 73381–73394. [[CrossRef](#)]
8. Lam, M.K.; Lee, K.T.; Mohamed, A.R. Current status and challenges on microalgae-based carbon capture. *Int. J. Greenh. Gas Control* **2012**, *10*, 456–469. [[CrossRef](#)]
9. Fernández-Sevilla, J.M.; Acien Fernández, F.G.; Molina Grima, E. Biotechnological production of lutein and its applications. *Appl. Microbiol. Biotechnol.* **2010**, *86*, 27–40. [[CrossRef](#)]
10. Granado-Lorencio, F.; Herrero-Barbudo, C.; Acien-Fernández, G.; Molina-Grima, E.; Fernández-Sevilla, J.M.; Pérez-Sacristán, B.; Blanco-Navarro, I. In vitro bioaccessibility of lutein and zeaxanthin from the microalgae *Scenedesmus almeriensis*. *Food Chem.* **2009**, *114*, 747–752. [[CrossRef](#)]
11. Lin, J.H.; Lee, D.J.; Chang, J.S. Lutein in specific marigold flowers and microalgae. *J. Taiwan Inst. Chem. Eng.* **2015**, *49*, 90–94. [[CrossRef](#)]
12. Lin, J.H.; Lee, D.J.; Chang, J.S. Lutein production from biomass: Marigold flowers versus microalgae. *Bioresour. Technol.* **2015**, *184*, 421–428. [[CrossRef](#)] [[PubMed](#)]
13. Bowen, P.E.; Herbst-Espinosa, S.M.; Hussain, E.A.; Stacewicz-Sapuntzakis, M. Esterification Does Not Impair Lutein Bioavailability in Humans. *J. Nutr.* **2018**, *132*, 3668–3673. [[CrossRef](#)] [[PubMed](#)]
14. Xie, Y.; Zhao, X.; Chen, J.; Yang, X.; Ho, S.H.; Wang, B.; Chang, J.S.; Shen, Y. Enhancing cell growth and lutein productivity of *Desmodesmus* sp. F51 by optimal utilization of inorganic carbon sources and ammonium salt. *Bioresour. Technol.* **2017**, *244*, 664–671. [[CrossRef](#)] [[PubMed](#)]
15. Chen, C.Y.; Ho, S.H.; Liu, C.C.; Chang, J.S. Enhancing lutein production with *Chlorella sorokiniana* Mb-1 by optimizing acetate and nitrate concentrations under mixotrophic growth. *J. Taiwan Inst. Chem. Eng.* **2017**, *79*, 88–96. [[CrossRef](#)]
16. Ruban, A.V.; Berera, R.; Iliaia, C.; Van Stokkum, I.H.M.; Kennis, J.T.M.; Pascal, A.A.; Van Amerongen, H.; Robert, B.; Horton, P.; Van Grondelle, R. Identification of a mechanism of photoprotective energy dissipation in higher plants. *Nature* **2007**, *450*, 575–578. [[CrossRef](#)] [[PubMed](#)]
17. EFSA Panel on Food Additives and Nutrient Sources added to Food (ANS) Scientific Opinion on the re-evaluation of lutein (E 161b) as a food additive. *EFSA J.* **2010**, *8*, 1678. [[CrossRef](#)]
18. Utomo, R.P.; Chang, Y.R.; Lee, D.J.; Chang, J.S. Lutein recovery from *Chlorella* sp. ESP-6 with coagulants. *Bioresour. Technol.* **2013**, *139*, 176–180. [[CrossRef](#)]
19. Barceló-Villalobos, M.; Serrano, C.G.; Zurano, A.S.; García, L.A.; Maldonado, S.E.; Peña, J.; Fernández, F.G.A. Variations of culture parameters in a pilot-scale thin-layer reactor and their influence on the performance of *Scenedesmus almeriensis* culture. *Bioresour. Technol. Reports* **2019**, *6*, 190–197. [[CrossRef](#)]
20. Del Campo, J.A.; Rodríguez, H.; Moreno, J.; Vargas, M.Á.; Rivas, J.; Guerrero, M.G. Lutein production by *Muriellopsis* sp. in an outdoor tubular photobioreactor. *J. Biotechnol.* **2001**, *85*, 289–295. [[CrossRef](#)]
21. Casal, C.; Cuaresma, M.; Vega, J.M.; Vilchez, C. Enhanced productivity of a lutein-enriched novel acidophile microalga grown on urea. *Mar. Drugs* **2011**, *9*, 29–42. [[CrossRef](#)] [[PubMed](#)]
22. Chen, C.Y.; Liu, C.C. Optimization of lutein production with a two-stage mixotrophic cultivation system with *Chlorella sorokiniana* MB-1. *Bioresour. Technol.* **2018**, *262*, 74–79. [[CrossRef](#)] [[PubMed](#)]
23. Cordero, B.F.; Obraztsova, I.; Couso, I.; Leon, R.; Vargas, M.A.; Rodriguez, H. Enhancement of lutein production in *Chlorella sorokiniana* (chlorophyta) by improvement of culture conditions and random mutagenesis. *Mar. Drugs* **2011**, *9*, 1607–1624. [[CrossRef](#)] [[PubMed](#)]

24. Dineshkumar, R.; Dhanarajan, G.; Dash, S.K.; Sen, R. An advanced hybrid medium optimization strategy for the enhanced productivity of lutein in *Chlorella minutissima*. *Algal Res.* **2015**, *7*, 24–32. [[CrossRef](#)]
25. Ho, S.H.; Chan, M.C.; Liu, C.C.; Chen, C.Y.; Lee, W.L.; Lee, D.J.; Chang, J.S. Enhancing lutein productivity of an indigenous microalga *Scenedesmus obliquus* FSP-3 using light-related strategies. *Bioresour. Technol.* **2014**, *152*, 275–282. [[CrossRef](#)] [[PubMed](#)]
26. Sánchez, J.F.; Fernández, J.M.; Acien, F.G.; Rueda, A.; Pérez-Parra, J.; Molina, E. Influence of culture conditions on the productivity and lutein content of the new strain *Scenedesmus almeriensis*. *Process Biochem.* **2008**, *43*, 398–405. [[CrossRef](#)]
27. Sánchez, J.F.; Fernández-Sevilla, J.M.; Acien, F.G.; Cerón, M.C.; Pérez-Parra, J.; Molina-Grima, E. Biomass and lutein productivity of *Scenedesmus almeriensis*: Influence of irradiance, dilution rate and temperature. *Appl. Microbiol. Biotechnol.* **2008**, *79*, 719–729. [[CrossRef](#)] [[PubMed](#)]
28. Wei, D.; Chen, F.; Chen, G.; Zhang, X.W.; Liu, L.J.; Zhang, H. Enhanced production of lutein in heterotrophic *Chlorella protothecoides* by oxidative stress. *Sci. China Ser. C Life Sci.* **2008**, *51*, 1088–1093. [[CrossRef](#)]
29. Zhao, B.; Su, Y. Process effect of microalgal-carbon dioxide fixation and biomass production: A review. *Renew. Sustain. Energy Rev.* **2014**, *31*, 121–132. [[CrossRef](#)]
30. Yen, H.W.; Hu, I.C.; Chen, C.Y.; Ho, S.H.; Lee, D.J.; Chang, J.S. Microalgae-based biorefinery - From biofuels to natural products. *Bioresour. Technol.* **2013**, *135*, 166–174. [[CrossRef](#)]
31. Salih, F.M. Microalgae Tolerance to High Concentrations of Carbon Dioxide: A Review. *J. Environ. Prot. (Irvine. Calif.)* **2011**, *02*, 648–654. [[CrossRef](#)]
32. Mehariya, S.; Patel, A.K.; Obulisamy, P.K.; Punniyakotti, E.; Wong, J.W.C. Co-digestion of food waste and sewage sludge for methane production: Current status and perspective. *Bioresour. Technol.* **2018**, *265*, 519–531. [[CrossRef](#)] [[PubMed](#)]
33. Siciliano, A.; Limonti, C.; Mehariya, S.; Molino, A.; Calabrò, V. Biofuel production and phosphorus recovery through an integrated treatment of agro-industrial waste. *Sustain.* **2018**, *11*, 52. [[CrossRef](#)]
34. Nobre, B.P.; Villalobos, F.; Barragán, B.E.; Oliveira, A.C.; Batista, A.P.; Marques, P.A.S.S.; Mendes, R.L.; Sovová, H.; Palavra, A.F.; Gouveia, L. A biorefinery from *Nannochloropsis* sp. microalga - Extraction of oils and pigments. Production of biohydrogen from the leftover biomass. *Bioresour. Technol.* **2013**, *135*, 128–136. [[CrossRef](#)] [[PubMed](#)]
35. Mann, J.E.; Myers, J. on Pigments, Growth, and Photosynthesis of *Phaeodactylum Tricornutum*. *J. Phycol.* **1968**, *4*, 349–355. [[CrossRef](#)] [[PubMed](#)]
36. de Moraes, M.G.; Costa, J.A.V. Biofixation of carbon dioxide by *Spirulina* sp. and *Scenedesmus obliquus* cultivated in a three-stage serial tubular photobioreactor. *J. Biotechnol.* **2007**, *129*, 439–445. [[CrossRef](#)]
37. Chaudhary, R.; Dikshit, A.K.; Tong, Y.W. Carbon-dioxide biofixation and phycoremediation of municipal wastewater using *Chlorella vulgaris* and *Scenedesmus obliquus*. *Environ. Sci. Pollut. Res.* **2018**, *25*, 20399–20406. [[CrossRef](#)] [[PubMed](#)]
38. Mehariya, S.; Iovine, A.; Di Sanzo, G.; Larocca, V.; Martino, M.; Leone, G.; Casella, P.; Karatza, D.; Marino, T.; Musmarra, D.; et al. Supercritical Fluid Extraction of Lutein from *Scenedesmus almeriensis*. *Molecules* **2019**, *24*, 1324. [[CrossRef](#)]
39. Molino, A.; Rimauro, J.; Casella, P.; Cerbone, A.; Larocca, V.; Chianese, S.; Karatza, D.; Mehariya, S.; Ferraro, A.; Hristoforou, E.; et al. Extraction of astaxanthin from microalga *Haematococcus pluvialis* in red phase by using generally recognized as safe solvents and accelerated extraction. *J. Biotechnol.* **2018**, *283*, 51–61. [[CrossRef](#)]
40. Pruvost, J.; Van Vooren, G.; Le Gouic, B.; Couzinet-Mossion, A.; Legrand, J. Systematic investigation of biomass and lipid productivity by microalgae in photobioreactors for biodiesel application. *Bioresour. Technol.* **2011**, *102*, 150–158. [[CrossRef](#)]
41. Molino, A.; Iovine, A.; Casella, P.; Mehariya, S.; Chianese, S.; Cerbone, A.; Rimauro, J.; Musmarra, D. Microalgae Characterization for Consolidated and New Application in Human Food, Animal Feed and Nutraceuticals. *Int. J. Environ. Res. Public Health* **2018**, *15*, 2436. [[CrossRef](#)] [[PubMed](#)]
42. Molino, A.; Mehariya, S.; Iovine, A.; Larocca, V.; Di Sanzo, G.; Martino, M.; Casella, P.; Chianese, S.; Musmarra, D. Extraction of Astaxanthin and Lutein from Microalga *Haematococcus pluvialis* in the Red Phase Using CO₂ Supercritical Fluid Extraction Technology with Ethanol as Co-Solvent. *Mar. Drugs* **2018**, *16*, 432. [[CrossRef](#)] [[PubMed](#)]

43. Sanzo, G.; Mehariya, S.; Martino, M.; Larocca, V.; Casella, P.; Chianese, S.; Musmarra, D.; Balducchi, R.; Molino, A. Supercritical Carbon Dioxide Extraction of Astaxanthin, Lutein, and Fatty Acids from *Haematococcus pluvialis* Microalgae. *Mar. Drugs* **2018**, *16*, 334. [[CrossRef](#)] [[PubMed](#)]
44. Cabello, J.; Morales, M.; Revah, S. Carbon dioxide consumption of the microalga *Scenedesmus obtusiusculus* under transient inlet CO₂ concentration variations. *Sci. Total Environ.* **2017**, *584–585*, 1310–1316. [[CrossRef](#)] [[PubMed](#)]
45. Ji, C.; Wang, J.; Li, R.; Liu, T. Modeling of carbon dioxide mass transfer behavior in attached cultivation photobioreactor using the analysis of the pH profiles. *Bioprocess Biosyst. Eng.* **2017**, *40*, 1079–1090. [[CrossRef](#)] [[PubMed](#)]
46. Shiraiwa, Y.; Goyal, A.; Tolbert, N.E. Alkalization of the medium by unicellular green algae during uptake dissolved inorganic carbon. *Plant Cell Physiol.* **1993**, *34*, 649–657. [[CrossRef](#)]
47. Cheng, J.; Li, K.; Yang, Z.; Zhou, J.; Cen, K. Enhancing the growth rate and astaxanthin yield of *Haematococcus pluvialis* by nuclear irradiation and high concentration of carbon dioxide stress. *Bioresour. Technol.* **2016**, *204*, 49–54. [[CrossRef](#)]
48. Cheng, L.; Zhang, L.; Chen, H.; Gao, C. Carbon dioxide removal from air by microalgae cultured in a membrane-photobioreactor. *Sep. Purif. Technol.* **2006**, *50*, 324–329. [[CrossRef](#)]
49. Sepulveda, C.; Gómez, C.; El Bahraoui, N.; Acién, G. Comparative evaluation of microalgae strains for CO₂ capture purposes. *J. CO₂ Util.* **2019**, *30*, 158–167. [[CrossRef](#)]
50. Acién, F.G.; Fernández, J.M.; Magán, J.J.; Molina, E. Production cost of a real microalgae production plant and strategies to reduce it. *Biotechnol. Adv.* **2012**, *30*, 1344–1353. [[CrossRef](#)]
51. Radmann, E.M.; Camerini, F.V.; Santos, T.D.; Costa, J.A.V. Isolation and application of SOX and NOX resistant microalgae in biofixation of CO₂ from thermoelectricity plants. *Energy Convers. Manag.* **2011**, *52*, 3132–3136. [[CrossRef](#)]
52. Jin, H.F.; Lim, B.R.; Lee, K. Influence of nitrate feeding on carbon dioxide fixation by microalgae. *J. Environ. Sci. Heal. Part A Toxic/Hazardous Subst. Environ. Eng.* **2006**, *41*, 2813–2824. [[CrossRef](#)] [[PubMed](#)]
53. Ong, S.C.; Kao, C.Y.; Chiu, S.Y.; Tsai, M.T.; Lin, C.S. Characterization of the thermal-tolerant mutants of *Chlorella* sp. with high growth rate and application in outdoor photobioreactor cultivation. *Bioresour. Technol.* **2010**, *101*, 2880–2883. [[CrossRef](#)] [[PubMed](#)]
54. Nayak, M.; Karemore, A.; Sen, R. Performance evaluation of microalgae for concomitant wastewater bioremediation, CO₂ biofixation and lipid biosynthesis for biodiesel application. *Algal Res.* **2016**, *16*, 216–223. [[CrossRef](#)]
55. Rodolfi, L.; Zittelli, G.C.; Bassi, N.; Padovani, G.; Biondi, N.; Bonini, G.; Tredici, M.R. Microalgae for oil: Strain selection, induction of lipid synthesis and outdoor mass cultivation in a low-cost photobioreactor. *Biotechnol. Bioeng.* **2009**, *102*, 100–112. [[CrossRef](#)]
56. Chiu, S.Y.; Tsai, M.T.; Kao, C.Y.; Ong, S.C.; Lin, C.S. The air-lift photobioreactors with flow patterning for high-density cultures of microalgae and carbon dioxide removal. *Eng. Life Sci.* **2009**, *9*, 254–260. [[CrossRef](#)]
57. Lam, M.K.; Lee, K.T. Potential of using organic fertilizer to cultivate *Chlorella vulgaris* for biodiesel production. *Appl. Energy* **2012**, *94*, 303–308. [[CrossRef](#)]
58. Hadj-Romdhane, F.; Zheng, X.; Jaouen, P.; Pruvost, J.; Grizeau, D.; Croué, J.P.; Bourseau, P. The culture of *Chlorella vulgaris* in a recycled supernatant: Effects on biomass production and medium quality. *Bioresour. Technol.* **2013**, *132*, 285–292. [[CrossRef](#)]
59. Patel, A.K.; Joun, J.M.; Hong, M.E.; Sim, S.J. Effect of light conditions on mixotrophic cultivation of green microalgae. *Bioresour. Technol.* **2019**, 245–253. [[CrossRef](#)]
60. Yen, H.W.; Sun, C.H.; Ma, T.W. The comparison of lutein production by *scenedesmus* sp. in the autotrophic and the mixotrophic cultivation. *Appl. Biochem. Biotechnol.* **2011**, *164*, 353–361. [[CrossRef](#)]
61. Del Campo, J.A.; Rodríguez, H.; Moreno, J.; Vargas, M.Á.; Rivas, J.; Guerrero, M.G. Accumulation of astaxanthin and lutein in *Chlorella zofingiensis* (Chlorophyta). *Appl. Microbiol. Biotechnol.* **2004**, *64*, 848–854. [[CrossRef](#)] [[PubMed](#)]
62. Xie, Y.; Ho, S.H.; Chen, C.N.N.; Chen, C.Y.; Ng, I.S.; Jing, K.J.; Chang, J.S.; Lu, Y. Phototrophic cultivation of a thermo-tolerant *Desmodesmus* sp. for lutein production: Effects of nitrate concentration, light intensity and fed-batch operation. *Bioresour. Technol.* **2013**, *144*, 435–444. [[CrossRef](#)] [[PubMed](#)]

63. Vaquero, I.; Ruiz-Domínguez, M.C.; Márquez, M.; Vilchez, C. Cu-mediated biomass productivity enhancement and lutein enrichment of the novel microalga *Coccomyxa onubensis*. *Process Biochem.* **2012**, *47*, 694–700. [[CrossRef](#)]
64. Del Campo, J.A.; García-González, M.; Guerrero, M.G. Outdoor cultivation of microalgae for carotenoid production: Current state and perspectives. *Appl. Microbiol. Biotechnol.* **2007**, *74*, 1163–1174. [[CrossRef](#)] [[PubMed](#)]

Sample Availability: Samples of the compounds are available from the authors.

© 2019 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).