

Supplementary Material

High-Performance Washable PM_{2.5} Filter Fabricated with Laser-Induced Graphene

Anh-Phan Nguyen ¹, Won-Kyu Kang ², Jungbae Lee ² and Jung-Bin In ^{1,2,*}

¹ Department of Intelligent Energy and Industry, Chung-Ang University, Seoul 06974, Korea; anhpn@cau.ac.kr

² Soft Energy Systems and Laser Applications Laboratory, School of Mechanical Engineering, Chung-Ang University, Seoul 06974, Korea; zk273rvlb@cau.ac.kr (W.-K.K.); skzzjd@cau.ac.kr (J.L.)

* Correspondence: jbin@cau.ac.kr




Figure S1. Composition of generated PM (after dilution).

Citation: Nguyen, A.-P.; Kang, W.-K.; Lee, J.; In, J.-B. High-Performance Washable PM_{2.5} Filter Fabricated with Laser-Induced Graphene. *Materials* **2021**, *14*, 5551. <https://doi.org/10.3390/ma14195551>

Academic Editor: Wiesław Stręk

Received: 27 August 2021

Accepted: 21 September 2021

Published: 24 September 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Submitted for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).




Figure S2. Collection efficiency of different filters for different PM sizes, with 12 V bias voltage.




Figure S3. Digital image of the air filtration setup.