

Supplementary Information

Performance Enhancement in Powder-Fabricated $\text{Cu}_2(\text{ZnSn})\text{Se}_4$ Solar Cell by Roll Compression

Jaehyun Park ¹, Hyobin Nam ¹, Bong-Geun Song ¹, Darya Burak ¹, Ho Seong Jang ^{1,2}, Seung Yong Lee ^{1,2}, So-Hye Cho ^{1,2,*} and Jong-Ku Park ^{1,*}

¹ Materials Architecturing Research Center, Korea Institute of Science and Technology, Hwarangno 14-gil 5, Seongbuk-gu, Seoul 02792, Republic of Korea

² Division of Nanoscience and Technology, KIST School, Korea University of Science and Technology, Seoul 02792, Republic of Korea

* Correspondence: sohyec@kist.re.kr (S.-H.C.); jkpark@kist.re.kr (J.-K.P.)

Citation: Park, J.; Nam, H.; Song, B.-G.; Burak, D.; Jang, H.S.; Lee, S.Y.; Cho, S.-H.; Park, J.-K. Performance Enhancement in Powder-Fabricated $\text{Cu}_2(\text{ZnSn})\text{Se}_4$ Solar Cell by Roll Compression. *Materials* **2023**, *16*, 1076. <https://doi.org/10.3390/ma16031076>

Academic Editor: Eunsoon Oh

Received: 02 November 2022

Revised: 17 January 2023

Accepted: 22 January 2023

Published: 26 January 2023



Copyright: © 2023 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).




Figure S1. (a) j - V curves and (b) device performance parameters of pressed CZTSe cells under AM 1.5G illumination (solid lines) and in the dark (dotted lines).




Figure S2. (a) j - V curves and (b) device performance parameters of unpressed CZTSe cells under AM 1.5G illumination (solid lines) and in the dark (dotted lines).