Fagus_sylvatica_10F

Processing Report

07 November 2018



Survey Data



Fig. 1. Camera locations and image overlap.

Number of images:	45	Camera stations:	45
Flying altitude:	3.07 m	Tie points:	44,379
Ground resolution:	0.671 mm/pix	Projections:	110,741
Coverage area:	6.43 m²	Reprojection error:	0.515 pix

Camera Model	Resolution	Focal Length	Pixel Size	Precalibrated
Canon EOS 70D (15 mm)	5472 x 3648	15 mm	4.17 x 4.17 µm	No

Table 1. Cameras.

Camera Calibration



Fig. 2. Image residuals for Canon EOS 70D (15 mm).

Canon EOS 70D (15 mm)

45 images

Type	Resolution	Focal Length	Pixel Size
Fisheye	**5472 x 3648**	**15 mm**	**4.17 x 4.17 µm**

	Value	Error	F	K1	K2	P1	P2
F	**3756.07**	0.22	1.00	-0.65	0.61	-0.31	-0.03
K1	**-0.0380284**	0.00011		1.00	-0.87	0.12	0.02
K2	**0.00388534**	0.00012			1.00	-0.26	0.00
P1	**0.00082671**	2.1e-05				1.00	0.07
P2	**-0.000109803**	9e-06					1.00

Table 2. Calibration coefficients and correlation matrix.

Ground Control Points



Fig. 3. GCP locations and error estimates.
Z error is represented by ellipse color. X,Y errors are represented by ellipse shape.
Estimated GCP locations are marked with a dot or crossing.

Count	X error (mm)	Y error (mm)	Z error (mm)	XY error (mm)	Total (mm)
4	0.459835	2.263	0.0554908	2.30925	2.30992

Table 3. Control points RMSE.

Label	X error (mm)	Y error (mm)	Z error (mm)	Total (mm)	Image (pix)
point 1	-0.36471	2.15876	0.0405096	2.18972	0.004 (45)
point 2	0.777379	-3.28237	-0.0944363	3.37449	0.004 (45)
point 3	-0.314301	-0.924694	0.0146421	0.976759	0.004 (45)
point 4	-0.0983678	2.0483	0.0392845	2.05104	0.004 (45)
Total	**0.459835**	**2.263**	**0.0554908**	**2.30992**	**0.004**

Table 4. Control points.

Label	X error (mm)	Y error (mm)	Z error (mm)	Total (mm)	Image (pix)
target 1					105.025 (16)
target 2					0.100 (7)
target 3					0.200 (23)
target 4					0.521 (24)
target 5					0.297 (32)
target 6					0.345 (34)
target 8					0.770 (14)
target 9					0.654 (14)
target 10					0.387 (30)
target 11					0.784 (7)
target 12					0.253 (3)
target 13					0.353 (19)
target 14					0.460 (22)
target 15					0.735 (16)
target 16					0.876 (15)
target 7					0.004 (45)
point 5					0.004 (45)
point 6					0.004 (45)
point 7					0.004 (45)
point 8					0.004 (45)
point 9					0.004 (45)
point 10					0.004 (45)
point 11					0.004 (45)

Label	X error (mm)	Y error (mm)	Z error (mm)	Total (mm)	Image (pix)
point 12					0.004 (45)
point 13					0.004 (45)
point 14					0.004 (45)
point 15					0.004 (45)
point 16					0.004 (45)
Total					

Table 5. Check points.

Scale Bars

Label	Distance (m)	Error (m)
target 5_target 6	0.147531	-0.000469302
target 8_target 7	0.149772	0.00177153
target 9_target 10	0.147378	-0.000622397
target 11_target 12	0.147678	-0.000322165
target 13_target 14	0.147809	-0.000191017
target 15_target 16	0.147796	-0.00020354
Total		**0.00080908**

Table 6. Control scale bars.

Label	Distance (m)	Error (m)
point 1_point 2	0.114607	
point 1_point 3	0.198006	
point 1_point 4	0.273044	
Total		

Table 7. Check scale bars.

Digital Elevation Model



Fig. 4. Reconstructed digital elevation model.

Resolution:	unknown
Point density:	unknown

Processing Parameters

General	
Cameras	45
Aligned cameras	45
Markers	33
Scale bars	9
Coordinate system	Local Coordinates (m)
Rotation angles	Yaw, Pitch, Roll
Point Cloud	
Points	44,379 of 47,256
RMS reprojection error	0.0856806 (0.515313 pix)
Max reprojection error	0.259069 (18.9099 pix)
Mean key point size	4.73979 pix
Point colors	3 bands, uint8
Key points	No
Average tie point multiplicity	2.60325
Alignment parameters	
Accuracy	High
Generic preselection	Yes
Key point limit	40,000
Tie point limit	4,000
Adaptive camera model fitting	Yes
Matching time	6 minutes 16 seconds
Alignment time	21 seconds
Depth Maps	
Count	45
Reconstruction parameters	
Quality	Medium
Filtering mode	Aggressive
Processing time	59 minutes 25 seconds
Dense Point Cloud	
Points	2,101,202
Point colors	3 bands, uint8
Reconstruction parameters	
Quality	Medium
Depth filtering	Aggressive
Depth maps generation time	59 minutes 25 seconds
Dense cloud generation time	21 minutes 23 seconds
Software	
Version	1.4.4 build 6848
Platform	Windows 64