Abies_alba_1F

Processing Report

07 November 2018

Survey Data



Fig. 1. Camera locations and image overlap.

Number of images:	39	Camera stations:	39
Flying altitude:	2.89 m	Tie points:	40,539
Ground resolution:	0.672 mm/pix	Projections:	98,312
Coverage area:	2.23 m²	Reprojection error:	0.47 pix

Camera Model	Resolution	Focal Length	Pixel Size	Precalibrated
Canon EOS 70D (15 mm)	5472 x 3648	15 mm	4.17 x 4.17 µm	No

Table 1. Cameras.

Camera Calibration



Fig. 2. Image residuals for Canon EOS 70D (15 mm).

Canon EOS 70D (15 mm)

39 images

Type	Resolution	Focal Length	Pixel Size
Fisheye	**5472 x 3648**	**15 mm**	**4.17 x 4.17 µm**

	Value	Error	F	K1	P1	P2
F	**3752.65**	0.15	1.00	-0.30	-0.13	-0.04
K1	**-0.0338296**	4.6e-05		1.00	-0.47	0.08
P1	**0.000798579**	1.8e-05			1.00	0.02
P2	**-8.55959e-05**	7.9e-06				1.00

Table 2. Calibration coefficients and correlation matrix.

Ground Control Points



Fig. 3. GCP locations and error estimates.
Z error is represented by ellipse color. X,Y errors are represented by ellipse shape.
Estimated GCP locations are marked with a dot or crossing.

Count	X error (mm)	Y error (mm)	Z error (mm)	XY error (mm)	Total (mm)
4	5.37496	3.39604	0.677806	6.35793	6.39396

Table 3. Control points RMSE.

Label	X error (mm)	Y error (mm)	Z error (mm)	Total (mm)	Image (pix)
point 1	-5.34091	-3.33932	0.428492	6.31348	0.004 (39)
point 2	8.95648	5.66204	-1.17331	10.6609	0.004 (39)
point 3	-2.18243	-1.49685	0.377636	2.67324	0.004 (39)
point 4	-1.43313	-0.825869	0.367179	1.69433	0.003 (39)
Total	**5.37496**	**3.39604**	**0.677806**	**6.39396**	**0.004**

Table 4. Control points.

Label	X error (mm)	Y error (mm)	Z error (mm)	Total (mm)	Image (pix)
target 1					0.666 (11)
target 2					1.008 (23)
target 3					0.704 (11)
target 4					0.375 (12)
target 5					0.415 (18)
target 6					0.492 (25)
target 8					0.958 (18)
target 9					0.753 (13)
target 10					0.820 (13)
target 11					0.326 (14)
target 13					0.832 (17)
target 14					0.532 (13)
target 15					0.692 (17)
target 16					0.532 (15)
target 7					0.004 (39)
point 5					0.004 (39)
point 6					0.004 (39)
point 7					0.004 (39)
point 8					0.004 (39)
point 9					0.004 (39)
point 10					0.004 (39)
point 11					0.004 (39)
point 12					0.005 (39)

Label	X error (mm)	Y error (mm)	Z error (mm)	Total (mm)	Image (pix)
point 13					0.004 (39)
point 14					0.004 (39)
point 15					0.005 (39)
point 16					0.004 (39)
Total					

Table 5. Check points.

Scale Bars

Label	Distance (m)	Error (m)
target 5_target 6	0.148324	0.000324335
target 9_target 10	0.14771	-0.000289654
target 13_target 14	0.148329	0.000328566
target 15_target 16	0.148115	0.000115235
target 8_target 7	0.147455	-0.000544607
Total		**0.000348403**

Table 6. Control scale bars.

Label	Distance (m)	Error (m)
point 1_point 2	0.0903695	
point 1_point 3	0.18918	
point 1_point 4	0.276687	
Total		

Table 7. Check scale bars.

Digital Elevation Model



Fig. 4. Reconstructed digital elevation model.

Resolution:	unknown
Point density:	unknown

Processing Parameters

General	
Cameras	39
Aligned cameras	39
Markers	31
Scale bars	8
Coordinate system	Local Coordinates (m)
Rotation angles	Yaw, Pitch, Roll
Point Cloud	
Points	40,539 of 42,855
RMS reprojection error	0.0941578 (0.470481 pix)
Max reprojection error	0.284406 (25.3547 pix)
Mean key point size	4.03987 pix
Point colors	3 bands, uint8
Key points	No
Average tie point multiplicity	2.50167
Alignment parameters	
Accuracy	High
Generic preselection	Yes
Key point limit	40,000
Tie point limit	4,000
Adaptive camera model fitting	Yes
Matching time	5 minutes 34 seconds
Alignment time	12 seconds
Depth Maps	
Count	39
Reconstruction parameters	
Quality	Medium
Filtering mode	Aggressive
Processing time	46 minutes 14 seconds
Dense Point Cloud	
Points	2,261,729
Point colors	3 bands, uint8
Reconstruction parameters	
Quality	Medium
Depth filtering	Aggressive
Depth maps generation time	46 minutes 14 seconds
Dense cloud generation time	12 minutes 16 seconds
Software	
Version	1.4.4 build 6848
Platform	Windows 64