

Electrically Polarized Graphene-blended Spacers for Organic Fouling Reduction in Forward Osmosis

Numan Yanar ¹, Yejin Liang ¹, Eunmok Yang ¹, Hosik Park ^{2,*}, Moon Son ^{3,*} and Heechul Choi ^{1,*}

¹ School of Earth Sciences and Environmental Engineering, Gwangju Institute of Science and Technology (GIST), 123-Cheomdangwagi-ro, Buk-gu, Gwangju 61005, Korea; numanyanar@gm.gist.ac.kr (N.Y.); liangyejin@gist.ac.kr (Y.L); yang1990@gist.ac.kr (E.Y.)

² Green Carbon Research Center, Chemical Process Division, Korea Research Institute of Chemical Technology (KRICT), Daejeon 34114, Korea

³ School of Urban and Environmental Engineering, Ulsan National Institute of Science and Technology, 50, UNIST-gil, Eonyang-eup, Ulju-gun, Ulsan 44919, Korea

* Correspondence: Correspondence: hcchoi@gist.ac.kr (H.C.); moonson619@unist.ac.kr (M.S.); hspark@kRICT.re.kr (H.P.); Tel.: +82-62-715-2441; Fax: +82-62-715-2423 (H.C.)



Figure S1. Engineered osmosis system.