

Supplementary Data

Fabrication and Characterization of Nanostructured Rock Wool as a Novel Material for Efficient Water-Splitting Application

Sahar A. El-Gharbawy ^{1,2}, Mawaheb Al-Dossari ³, Mohamed Zayed ⁴, Heba A. Saudi ¹, Mohamed Y. Hassaan ¹, Nada Alfryyan ⁵ and Mohamed Shaban ^{4,6,*}

¹ Department of Physics, Faculty of Science, Al-Azhar University (Girls' Branch), Nasr City, Cairo 11884, Egypt; fouads5649@gmail.com (S.A.E.-G.); heba_saudi@azhar.edu.eg (H.A.S.); myhassaan@yahoo.com (M.Y.H.)

² Housing and Building National Research Center, 87 El-Tahrir St., Dokki, Giza 1770, Egypt

³ Department of Physics, Faculty of Science, King Khalid University, Abha 62529, Saudi Arabia; mdsori@kku.edu.sa

⁴ Nanophotonics and Applications (NPA) Lab, Department of Physics, Faculty of Science, Beni-Suef University, Beni-Suef 62514, Egypt; m.zayed88ph@yahoo.com

⁵ Department of Physics, College of Sciences, Princess Nourah bint Abdulrahman University, P.O. Box 84428, Riyadh 11671, Saudi Arabia; naalfryyan@pnu.edu.sa

⁶ Physics Department, Faculty of Science, Islamic University of Madinah, P.O. Box 170, Al Madinah Al Monawara 42351, Saudi Arabia

* Correspondence: mssfadel@aucegypt.edu




Figure S1. HR-TEM of the (A) $RW_{0.063}$ and (B–D) $RW_{>0.3}$ after hydrothermal technique at 140 °C and annealing; the inset of (D) shows SAED pattern of $RW_{>0.3}$.