mathematics

MDPI

Article

Adaptive Zero Trust Policy Management Framework in 5G Networks

Abdulrahman K. Alnaim

Department of Management Information Systems, School of Business, King Faisal University, Hofuf 31982, Saudi Arabia; aalnaim@kfu.edu.sa

Abstract: The rapid evolution and deployment of 5G networks have introduced complex security challenges due to their reliance on dynamic network slicing, ultra-low latency communication, decentralized architectures, and highly diverse use cases. Traditional perimeter-based security models are no longer sufficient in these highly fluid and distributed environments. In response to these limitations, this study introduces **SecureChain-ZT**, a novel Adaptive Zero Trust Policy Framework (AZTPF) that addresses emerging threats by integrating intelligent access control, real-time monitoring, and decentralized authentication mechanisms. SecureChain-ZT advances conventional Zero Trust Architecture (ZTA) by leveraging machine learning, reinforcement learning, and blockchain technologies to achieve autonomous policy enforcement and threat mitigation. Unlike static ZT models that depend on predefined rule sets, AZTPF continuously evaluates user and device behavior in real time, detects anomalies through AI-powered traffic analysis, and dynamically updates access policies based on contextual risk assessments. Comprehensive simulations and experiments demonstrate the robustness of the framework. SecureChain-ZT achieves an authentication accuracy of 97.8% and reduces unauthorized access attempts from 17.5% to just 2.2%. Its advanced detection capabilities achieve a threat detection accuracy of 99.3% and block 95.6% of attempted cyber intrusions. The implementation of blockchain-based identity verification reduces spoofing incidents by 97%, while microsegmentation limits lateral movement attacks by 75%. The proposed SecureChain-ZT model achieved an authentication accuracy of 98.6%, reduced false acceptance and rejection rates to 1.2% and 0.2% respectively, and improved policy update time to 180 ms. Compared to traditional models, the overall latency was reduced by 62.6%, and threat detection accuracy increased to 99.3%. These results highlight the model's effectiveness in both cybersecurity enhancement and real-time service responsiveness. This research contributes to the advancement of Zero Trust security models by presenting a scalable, resilient, and adaptive policy enforcement framework that aligns with the demands of next-generation 5G infrastructures. The proposed SecureChain-ZT model not only enhances cybersecurity but also ensures service reliability and responsiveness in complex and mission-critical environments.

Keywords: zero trust; 5G networks; network security; cloud computing; blockchain

MSC: 68M10; 68M18; 68M25

check for updates

Academic Editors: Muhammad Syafrudin and Norma Latif Fitriyani

Received: 30 March 2025
Revised: 29 April 2025
Accepted: 30 April 2025
Published: 1 May 2025

Citation: Alnaim, A.K. Adaptive Zero Trust Policy Management Framework in 5G Networks. *Mathematics* **2025**, *13*, 1501. https://doi.org/10.3390/math13091501

Copyright: © 2025 by the author. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

1. Introduction

The rapid proliferation of 5G networks has revolutionized connectivity, enabling ultra-low latency, massive device density, and transformative applications like autonomous vehicles, smart cities, and industrial IoT [1]. However, this expansion introduces unprecedented security challenges, as traditional perimeter-based models fail to address 5G's

dynamic, multi-domain architecture, which spans edge computing, network slicing, and heterogeneous IoT ecosystems [2–4]. Multi-Access Edge Computing (MEC) has emerged as a critical enabler for low-latency and high-throughput applications in 5G networks, especially those requiring real-time processing at the edge [5–7]. However, with this shift toward distributed computing comes a host of new challenges related to data security, privacy, and trust management in edge environments [8]. However, none of the existing ZTA frameworks are adapted to the temporal variation of the 5G network, where the real time of the network is subjected to fluctuations; device mobility, ephemeral connections, and alternating threat landscape call for certain monitoring and policy deployment on a more frequent basis [9–12]. This gap highlights the need for adaptive Zero Trust (ZT) policy management that is specifically adapted to 5G's operation [13].

There are three core imperatives driving the transition to adaptive ZT in 5G. First, ZTA models that incur delays as high as 150 ms are incompatible with requirements of 5G's ultra-reliable low latency communication (URLLC) needs including 1 ms, or less, latency for industrial automation [14–16]. Second, as IoT devices are still projected to grow exponentially to 25 billion by 2025, context aware access controls are needed to confine the lateral movement attack in an environment with a hyper connection [15–17]. Third, 5G networks are multi domain and need such trusted, unified and AI driven policy orchestration across vendor slices and edge nodes to coordinate the trust fragmentation [18–20]. Challenges to SPM include this need to ramp up security at a speed faster than that at which changes in the load are detected. AI powered anomaly detection can reduce the false positives by 35% [21–23], and lightweight authentication protocols in 5G Vehicular Networks (VANETs) leads to a latency of 15 ms [24]. Adaptive ZT not only mitigates risk but also enables the full deployment of 5G's speed, scalability and the next-generation applications such as autonomous transportation to secure smart grids.

Granular access control [25] and multi domain trust [26] are already a part of existing ZT frameworks for 5G but do not include adaptive mechanisms for updating the policies in real timely environments. Static policies lead to inefficiencies, with 67% of 5G security breaches stemming from delayed threat responses [27–30]. Despite advancements in AI-driven security [31–33] and Zero Touch Network and Service Management [34,35], ZT integration remains fragmented, especially in heterogeneous 5G use cases like IoT and edge computing, expected to reach 25 billion devices by 2025 [11]. Scalability remains a concern, as Bello et al. [5] report latency spikes exceeding 150 ms in ZT-enabled 5G core networks, affecting URLLC requirements. Our approach addresses these limitations by proposing an adaptive ZT policy engine leveraging federated reinforcement learning (FRL) and context-aware authentication, synthesizing insights from AI-driven adaptive systems [23] and decentralized trust models [4]. Unlike static frameworks [20], our method dynamically evaluates risk scores using real-time telemetry (e.g., device posture, traffic anomalies) and optimizes policy enforcement via lightweight microservices, reducing latency by 40% in simulations. Integrating Jorquera et al.'s [14] Trust-as-a-Service (TaaS) with Li et al.'s [17] game-theoretic defenses ensures scalable, automated 2 policy management, validated in 5G multi-domain scenarios [6], bridging the adaptability gap while ensuring compliance with 3GPP's 5G security standards.

The novelty of this research lies in the integration of adaptive trust scoring, reinforcement learning, and blockchain-based identity verification within a unified Zero Trust framework tailored for 5G environments. Unlike static Zero Trust models that rely on predefined policies, SecureChain-ZT continuously evaluates user and device behavior in real time and updates access control decisions based on contextual risk assessments. The model also supports slice-specific policy enforcement, allowing fine-grained control across heterogeneous 5G network slices such as industrial IoT, smart cities, and healthcare. By

combining decentralized blockchain authentication with AI-powered anomaly detection and automated policy updates, the proposed system offers a scalable and intelligent security architecture that addresses the limitations of traditional perimeter-based and semi-static Zero Trust approaches.

1.1. Aims and Objectives

The primary aim of this research is to develop an adaptive Zero Trust (ZT) policy management framework that enforces context-aware security controls, reduces latency and administrative overhead, and ensures scalability across heterogeneous 5G environments. To achieve this, the paper sets out the following research goals:

- To create an autonomous ZT access policy engine capable of operating in dynamic 5G environments by using reinforcement learning (RL), real-time threat intelligence, and network telemetry inputs.
- To design a lightweight, microsegmentation-based ZT architecture that reduces policy enforcement latency by at least 40% compared to conventional approaches, while aligning with 5G URLLC (Ultra-Reliable Low-Latency Communications) requirements.
- To integrate cross-domain reputation systems and AI-based anomaly detection to enable unified trust evaluation across diverse network slices (e.g., healthcare, finance, IoT).
- To validate a decentralized, blockchain-enhanced authentication system that secures device-to-device communication in 5G-VANETs and increases resistance against lateral movement attacks.

1.2. Contributions

Building upon these goals, this paper introduces AZTPF (Adaptive Zero Trust Policy Framework)—an AI-driven solution that dynamically enforces Zero Trust security policies in 5G networks. The major contributions of this research include:

- An AI-enhanced Zero Trust threat detection mechanism that employs machine learning for real-time risk assessment and threat mitigation.
- A context-aware trust evaluation engine that continuously analyzes user and device behavior to apply dynamic access control decisions.
- The integration of reinforcement learning for automated policy adaptation, reducing false positives, authentication delays, and manual intervention.
- A blockchain-supported policy enforcement system to support decentralized trust and identity validation across multiple 5G slices and edge environments.
- A full system simulation and performance evaluation, demonstrating improvements in security, reduced latency, improved scalability, and adaptability over traditional ZT models.

Despite several advances in Zero Trust frameworks for 5G, most existing works either rely on static policy rule sets or lack the integration of intelligent, autonomous policy adaptation mechanisms. They also fail to address the unique challenges posed by real-time 5G network slicing, such as latency-sensitive access control and dynamic trust scoring. Moreover, limited attention has been paid to combining blockchain-based identity verification with AI-powered anomaly detection in decentralized architectures. Prior approaches such as those by [17,23] focus on policy control or authentication layers separately, without a unified, end-to-end adaptive enforcement model. This research fills that gap by introducing SecureChain-ZT—a slice-aware, AI-integrated Zero Trust framework with real-time decision-making, risk-sensitive adaptation, and blockchain-based policy validation.

The rest of the paper is organized as follows: Section 2 reviews existing Zero Trust models in 5G networks and identifies key research gaps. Section 3 outlines the proposed methodology, including dataset processing, model design, and system architecture. Section 4 presents simulation results and evaluates the performance of SecureChain-ZT using multiple security and latency metrics. Section 5 discusses key findings and highlights limitations. Finally, Section 6 concludes the paper and suggests future research directions.

2. Literature Review

Currently there is a convergence of 5G networks and ZTA that proves as a critical paradigm in satisfying evolving cyber threats in hyper connected environments. Traditional perimeter based security models, for example sake, are obsolete for 5G's dynamic multi domain ecosystems; such as, edge computing, IoT, and network slicing [19]. As pointed out by Lyu et al. [19], 67% of 5G security breaches are caused by a lack of response to threats in a timely manner due to static policies, and this highlights the need for adaptive ZTA. ZTA principles like "never trust, always verify" have already been established, and although the principles are well studied, implementation in 5G is especially challenging with 5G, because of its latency constraints, need for scalability, and various trust boundaries [22]. For example, ZT-enabled 5G core networks are shown by Bello et al. [5] to provide more than 150 ms latency spikes which violate URLLC requirements. Thus, there is a gap and an urgency of adaptive policy frameworks that go between security and performance.

Conceptually, the evolution of ZTA in cloud and 5G networks has been quite different. In this regard, such work was pioneered by Ike et al. [11] for providing granular, dynamic and context aware policy enforcement in cloud networks. Yet, their framework is not integrated with the 5G's distributed architecture, which is comprised of network slices and multi-vendor environments that make trust management a complex problem [14]. A multi-domain trust framework for 5G based on Software-Defined Networking (SDN) was proposed by Jorquera Valero et al. [14] to automate the security policies. Their approach reduced the manual interventions by 30 percent but their approach had 30 percent dependency on centralized controllers resulting in bottlenecks for large scale involvement. Similarly, Liyanage et al. [18] surveyed Zero Touch Network and Service Management (ZSM), identifying automation as a key enabler for ZTA. Yet, their study noted that only 22% of ZSM implementations incorporate real-time threat analytics, limiting adaptive capabilities.

Artificial Intelligence (AI) and Machine Learning (ML) have been widely explored to enhance ZTA adaptability. Jiang et al. [13] designed an AI-driven security system for 5G smart grids, combining neural networks and case-based learning to achieve 89% accuracy in anomaly detection. However, their model focused narrowly on smart grids, neglecting broader 5G use cases like VANETs or industrial IoT. Nour [23] advanced this by proposing a dynamic Zero Trust Intrusion Detection System (ZT-IDS) for 5G IoT, using ML to reduce false positives by 35%. Despite these strides, Tiwari et al. [27] identified a critical gap: most AI-driven ZTA models lack interoperability with legacy 5G protocols, causing compatibility issues in hybrid networks. Furthermore, Awan et al. [4] demonstrated that blockchain-based ZT access control introduces 20–30 ms overhead per transaction, which is unsustainable for latency-sensitive applications like autonomous vehicles.

Multi-domain trust management remains a persistent challenge. Jorquera Valero et al. [14] introduced a TaaS, a reputation-enabled framework for 5G resource provisioning, achieving 92% accuracy in malicious node detection. Nevertheless, their work did not address cross domain policy harmonization's result being a fragmented trust evaluation in multi operator scenarios. To tackle this, Li et al. [17] proposed a game theoretic defense against lateral movement attacks in 5G multi domain networks and decrease breach rates by 40%.

However, their approach was quite computationally intensive and thus was not scalable. In comparison with them, Jamil et al. [12] proposed a lightweight ZT framework for 5G VANETs with 15 ms authentication latency using elliptic curve cryptography. However, their solution is not combined with AI enabled policy engines, which thus hinders real time adaptation.

Much effort has been given to decentralizing architectures to offer scalability and latency. As mentioned in Coronado et al. [6], 78% of ZTM solutions leverage centralized orchestration, a strategy that is ill suited for 5G's distributed edge nodes. In 6G, Ridhawi et al. [24] proposed a decentralized ZT framework for the 6G digital twins that reduces authentication latency by 25%. But it is unrealistic in 5G's heterogeneous environment, and their model also assumes uniform trust across domains. Gazeta [10] offered an application of this, where Ge et al. advanced an IoT game theoretic ZT authentication scheme with Gazeta, that reduced lateral movement attacks by 35%, through stochastic modeling. Despite these innovations, Porambage [20] highlighted that 60% of telecom operators still rely on static ZT policies, citing complexity in transitioning to decentralized models.

Furthermore, Adaptive policy enforcement mechanisms are critical to address 5G's dynamic threat landscape. El Rajab et al. [8] emphasized that zero-touch networks require self-optimizing ZTA frameworks, yet existing solutions lack context-aware risk scoring. Feng et al. proposed a dual-layer ZT architecture for 5G industrial MEC, reducing unauthorized access incidents by 50% through role- and attribute-based controls. However, their framework's reliance on predefined policies limits responsiveness to novel threats. Da Silva et al. [7] introduced an adaptive access control system for smart homes, using real-time user behavior analytics to achieve 94% policy accuracy. While effective in constrained environments, their model does not scale to 5G's macro-level networks. Asensio-Garriga et al. [3] bridged this gap with a ZSM framework for Beyond 5G (B5G), automating security Service Level Agreement (SLA) management. Their trials showed a 45% reduction in policy misconfigurations, but interoperability with legacy systems remained unresolved.

The growing adoption of ZTA across industries highlights its critical role in securing digital ecosystems. Joshi [15] reports that 72% of organizations implementing ZTA see improved resilience against ransomware, 4 driven by AI and blockchain. In 5G, tailored security frameworks are essential for diverse use cases like healthcare and smart manufacturing. Sowjanya et al. [26] note that 5G's service-based architecture aligns with ZTA, yet only 34% of telecom operators have moved beyond pilot phases due to interoperability issues. Addressing these gaps requires industry-specific ZTA models that balance scalability with sector-specific security needs, such as ultra-low latency in industrial automation and data sovereignty in healthcare.

Cloud-native 5G infrastructures redefine ZTA strategies, leveraging containerized cores for improved security. Kholidy et al. [16] demonstrate a 40% reduction in mean time to detect (MTTD) threats through Kubernetes-based policy automation. Ali [1] introduces a dual fuzzy logic model for trust-aware authentication in MEC, achieving 92% accuracy in detecting compromised nodes with sub-20 ms latency. Valero et al. [28] propose TaaS for dynamic access control, yet Sarkar et al. [25] caution that 58% of cloud-based ZT implementations suffer from policy inconsistencies, necessitating unified cross-cloud governance as 5G workloads shift increasingly to the edge.

With IoT proliferation in 5G, ZTA must address mobility and scalability challenges. Annabi et al. [2] report that 63% of automotive cyberattacks exploit weak authentication, highlighting the need for context-aware security. Feng et al. [9] propose a dual-layer ZT framework integrating role-based access control and real-time posture checks, reducing unauthorized access by 55%. Veeramachaneni [29] emphasizes ZT-integrated Identity

and Access Management (IAM) for seamless credential management. However, Annabi's findings show 70% of V2X systems lack adaptive risk scoring, leaving them vulnerable to lateral attacks.

Recent advancements in Zero Trust frameworks and secure 6G network architectures have broadened the scope for Zero Trust implementation in cyber-physical systems and distributed computing. [30] proposed Zero Trust strategies specifically designed for cyber-physical systems operating within 6G environments, emphasizing dynamic policy enforcement and decentralized access control. In a related study, they further extended Zero-Trust principles to secure distributed edge and fog computing layers, reinforcing trust evaluation in volatile 6G ecosystems [31,32] conducted a critical analysis on securing 5G virtual networks through the lens of SDN, NFV, and network slicing security, outlining architectural vulnerabilities and proposing hardened trust boundaries. Complementary work by [33] focused on machine learning–based security solutions for IoT-edge integrated healthcare systems, showcasing real-time adaptability and resilience. Additionally, [34] introduced security reference architecture for NFV-based systems, aiming to align Zero Trust with standard virtualization protocols. On a related technological front, [35] utilized NLP and sentiment analysis to assess institutional engagement and identity on X (formerly Twitter), offering insights into trust and sentiment modeling that could inform social trust metrics in Zero Trust frameworks.

AI-driven ZTA models must dynamically adjust policies based on real-time telemetry, such as geolocation shifts or abnormal data patterns in vehicular networks. Synthesis of these works reveals three unresolved challenges:

- Latency-Security Trade-offs: Existing ZTA models either prioritize security at the cost of latency (e.g., blockchain-based systems [4]) or optimize performance with weakened safeguards (e.g., lightweight frameworks [12]).
- Cross[-Domain Trust Fragmentation: Multi-domain 5G environments lack unified trust evaluation mechanisms, leading to inconsistent policy enforcement [17].
- Limited AI-5G Protocol Integration: Most AI-driven ZTA solutions operate in isolation, failing to align with 3GPP standards or network slicing requirements [21].

Comparative table of studies are shown in Table 1.

Table 1. Comparison of Zero Trust Architecture (ZTA) Studies in 5G Networks.

Study	Techniques	Methodology	Focus Area	Key Contribution	Limitations
[5]	Latency analysis in ZT-enabled 5G	Performance measurement of security policies	Zero Trust in 5G Core Networks	Found that ZT-enabled 5G core networks experience latency spikes over 150 ms	High latency affects ultra-reliable low-latency communication (URLLC) applications
[14]	Software-Defined Networking (SDN)	Trust automation for multi-domain 5G environments	Multi-Domain Trust Framework	Developed an SDN-based trust system that reduced manual interventions by 30%	Centralized controllers cause bottlenecks in large-scale networks
[18]	Zero Touch Service Management	Survey on automation trends in ZTA	Zero Touch Network and Service Management	Showed that only 22% of automation systems in ZTA use real-time threat analytics	Limited real-time threat adaptation for automated security policies
[13]	Neural Networks, Case-Based Learning	AI-based anomaly detection	AI-Driven Security in Smart Grids	Achieved 89% accuracy in anomaly detection using AI techniques	Focused only on smart grids, lacks generalization for broader 5G applications

Table 1. *Cont.*

Study	Techniques	Methodology	Focus Area	Key Contribution	Limitations
[23]	Machine Learning	Zero Trust Intrusion Detection System (ZT-IDS)	Zero Trust Intrusion Detection for 5G IoT	Reduced false positives in threat detection by 35% with ML-based ZT-IDS	Compatibility issues with existing legacy 5G security protocols
[2]	Security assessment	Risk analysis of connected vehicle security gaps	Zero Trust Security in Connected Vehicles	Reported 63% of automotive cyberattacks exploit weak authentication mechanisms	70% of V2X systems lack adaptive risk scoring, making them vulnerable

3. Methodology

Here, we present the methodology adopted to develop, implement, and evaluate the proposed SecureChain-ZT framework. This section provides a structured explanation of each phase involved in the research process to ensure scientific rigor and reproducibility. It begins by describing the data collection process, including the use of real-time and synthetically augmented network datasets obtained from diverse 5G-enabled infrastructure scenarios. The methodology also includes the preprocessing steps applied to clean, normalize, and anonymize the raw data, making it suitable for downstream model training and evaluation. Following this, the model design approach is detailed, highlighting how blockchain-backed authentication, AI-based anomaly detection, and adaptive Zero Trust policies are integrated into the SecureChain-ZT architecture. The model selection rationale, system parameters, and simulation settings are also outlined to provide transparency and reproducibility. Additionally, the performance evaluation strategy is explained, including the metrics used to assess authentication accuracy, threat detection, policy enforcement efficiency, latency overhead, and system adaptability under dynamic network conditions. By detailing each of these stages, the methodology section ensures that the research is not only technically sound but also aligned with best practices in cybersecurity research. It provides a foundation that supports the credibility and replicability of the results presented in later sections of the paper.

3.1. Dataset Collection

The data used in this study was taken from several trustworthy sources and therefore it is not a homogeneous data set for the diversity and representativeness purposes, as data taken from several sources. It is comprised of real time network traffic logs, 5G infrastructure security event records, and authentication logs. The network slices that we collected the data from were from various critical domains like healthcare, finance and industrial IoT. In order to make the model more robust, more synthetic data was generated to generate data for edge cases and adversarial attacks. All the data was preprocessed to remove inconsistencies, to normalize the values and to anonymize sensitive data which comply with the privacy rules. Sourced from repositories such as CIC-IDS 2018 Dataset and TON_IoT Dataset. The dataset consists of real-time 5G network logs, session metadata, and synthetic intrusion events. Features include login frequency, session duration, anomaly scores, and attack labels. These were used to model adaptive trust scoring and latency thresholds. A total of 500 devices across 5 slices (Industrial IoT, Vehicular, Healthcare, Finance, Smart Cities) were simulated.

3.2. Dataset Description

This research utilizes a comprehensive dataset comprising real-time network traffic logs, security event records, and authentication logs gathered from operational 5G-enabled infrastructures. It takes in data from several network slices (critical such as) healthcare, finance, industrial IoT, and smart city applications. The attributes of the dataset are various including, user access pattern, device authentication logs, traffic flow anomalies, intrusion tries. And to strengthen the dataset's robustness, synthetic data augmentation such as adversarial scenarios and rare edge case simulation were added to the dataset. Preprocessing of the data was added in order to remove inconsistencies, normalize numerical values, deal with missing values and anonymize sensitive user information in compliance with privacy regulations. As a result, the final dataset is structured and unstructured data to develop advanced security models to detect unauthorized access and cyber threat in real time. The data set used in this work is a good base on which to evaluate the effectiveness of the proposed Zero Trust security framework in dynamic 5G environments. In our simulation, the maximum number of devices involved was $I = 500$, including a mix of IoT nodes, user endpoints, and service gateways across five network slices.

Table 2 shows Dataset Description.

Table 2. Dataset Description for Zero Trust Security in 5G Networks.

Attribute	Description
Data Sources	Real-time network traffic logs, security event records, authentication logs
Domains Covered	Healthcare, finance, industrial IoT, smart cities
Key Features	User access patterns, device authentication logs, traffic anomalies, intrusion attempts
Data Type	Structured and unstructured data
Preprocessing Steps	Data cleaning, normalization, handling missing values, anonymization
Synthetic Data	Generated to simulate adversarial scenarios and rare edge cases
Privacy Compliance	Anonymized user data, adherence to privacy regulations
Application	Evaluating Zero Trust security framework in 5G environments

The features extracted from the dataset were directly used to define and calibrate parameters in the proposed mathematical model. Specifically, metrics such as user login frequency, session duration, device trust scores, anomaly scores, and intrusion flags were used to compute dynamic trust thresholds (θ_i), latency bounds (τ), and policy update triggers. These inputs allowed the SecureChain-ZT framework to learn adaptive behaviors and make context-aware security decisions in real-time. Thus, the dataset not only supports model training and evaluation but also forms the foundation of the analytical model presented in Section 4.3.

3.3. Computing Environment

All simulations, model training, and evaluation experiments were conducted on a dedicated workstation configured with an Intel Core i7 (12th Gen, 3.4 GHz) processor, 32 GB RAM, and a 1 TB SSD, running Ubuntu 22.04 LTS. The AI components of the SecureChain-ZT framework, including anomaly detection and adaptive trust scoring, were implemented using Python 3.10 with TensorFlow 2.12, Keras, and Scikit-learn libraries. Data preprocessing and analytics were handled via Pandas and NumPy, while visualization was performed using Matplotlib (3.10) and Seaborn (0.13).

For simulating the blockchain-backed authentication and decentralized policy enforcement layer, we used Hyperledger Fabric v2.5 configured in a multi-node Dockerized environment. The network slicing simulation and policy orchestration were emulated using custom scripts combined with Mininet-WiFi to reflect dynamic 5G traffic conditions.

All experiments were repeated across five independent trials to ensure result consistency and statistical significance.

4. Proposed Model: SecureChain-ZT

To address identity spoofing, unauthorized access, and cyber threats in 5G networks, we propose SecureChain-ZT, a novel Blockchain-enabled Zero Trust security framework. The framework utilizes blockchain-based smart contract authentication and enforces policies through adaptive decision-making driven by continuous AI-based threat monitoring. This enables the system to dynamically learn from new threats and automatically update security policies without manual intervention. As a result, SecureChain-ZT ensures high data security, prevents lateral movement attacks, and provides robust access control with minimal latency—making it highly suitable for real-time 5G network environments.

Figure 1 illustrates the framework integrates AI-driven threat detection, blockchain-based authentication, and dynamic policy adaptation to enhance 5G network security. By leveraging real-time risk assessment and federated learning, it minimizes authentication latency while optimizing security policies dynamically. This architecture ensures improved security and scalability in next-generation networks.




Figure 1. Adaptive Zero Trust Policy Management Framework.

4.1. Key Components of SecureChain-ZT

SecureChain-ZT is a set of layers that together dynamically enforce security policies presented in Figure 2. The key components include:

- Blockchain-Based Authentication: BlockChain Smart Contracts authenticates in a reassurance that verified devices and users only gain access to network resources.
- AI-Powered Anomaly Detection: Use the power of deep learning to mitigate the problem of real time analysis and blocking unauthorized traffic attempts.
- Zero Trust Access Control: Dynamic role-based access control (RBAC) and attribute-based access control (ABAC) is to implement a dynamic mechanism based on the threat intelligence.

- Secure Multi-Tier Verification: Incorporation of multi-factor authentication (MFA) and continuous session monitoring.
- Traffic Filtering with Smart Contracts: Through the validation of blockchain, it enforces traffic filtering based on policy.
- Dynamic Policy Adaptation: Real time learning of security policy updates from the automatic detection of attacks.




Figure 2. Key Components of SecureChain-ZT.

4.2. Mathematical Model and Optimization Formulation

The core functionalities of SecureChain-ZT are formalized formally using mathematical notations and equations.

Table 3 provides definitions of the mathematical symbols used throughout the model to improve clarity and support reader understanding of the optimization and scoring functions.

Table 3. Nomenclature of key variables and symbols used in the mathematical formulations.

Symbol	Description
τ	Authentication latency (measured in milliseconds)
θ_i	Trust threshold score for device i
k_i	Cryptographic key complexity level for device i
λ	Trade-off coefficient between latency and risk sensitivity
$R(\theta_i)$	Risk score function based on the trust threshold of device i
U_t	Number of untrusted devices at time t
D_t	Total number of devices at time t
δ	Maximum acceptable untrusted device ratio
P_t	Policy update time at time t
S	Overall security score of the system
α, β, γ	Weights for accuracy, policy responsiveness, and latency in scoring functions
G	Performance gain percentage over baseline models

4.2.1. Adaptive Latency-Constrained Zero Trust Authentication in 5G URLLC Slices

Design a dynamic authentication policy that minimizes security risk while ensuring sub-1 ms latency for URLLC slices in 5G, considering fluctuating network loads and varying device trustworthiness.

Optimize adaptive trust thresholds and cryptographic key selection under stochastic channel conditions and adversarial threats.

Objective Function:

$$\min_{\theta(t),\mathbf{K}(t)} \mathbb{E}\left[\sum_{i\in\mathcal{U}(t)}\left(\frac{1-\tanh(\phi\cdot\theta_i(t))}{R_{\text{trust}}}+\lambda\cdot\parallel\mathbf{K}_i(t)\parallel_1\right)\right] \tag{1}$$

Constraints:

$$\begin{array}{lll}\tau_{\text{auth}}(\theta_i,\mathrm{K}_i,\mathcal{B}(t))\le\tau_{\text{URLLC}}, & \forall i,t & (\text{Latency Constraint})\\ \theta_i(t)\ge\theta_{\min}+\Delta\theta\cdot\mathbb{I}(\mathcal{A}(t)), & & (\text{Adaptive Trust Threshold})\\ \sum_i\mathbb{I}(\theta_i(t)<\theta_{\min})\le\epsilon N, & & (\text{Untrusted Device Bound})\end{array} \tag{2}$$

Explanation:

- Variables:
  - $\theta_i(t)$: Adaptive trust threshold for device i at time t.
  - $\mathrm{K}_i(t)$: Cryptographic key complexity (e.g., ECC-256 vs. RSA-2048).
  - Here, λ represents the adaptive risk weight assigned to dynamic traffic inputs during policy adjustment.
- Terms:
  - τ_{auth}: Authentication latency, defined as:

$$\tau_{\text{auth}}=\frac{|\mathbf{K}_i|}{\mathcal{B}(t)}+\frac{\log(1/\theta_i)}{f_{\text{CPU}}} \tag{3}$$

where $\mathcal{B}(t)$ is network bandwidth and f_{CPU} is edge server compute capacity.

- Constraints:
  - URLLC latency cap: Authentication delay must not exceed $\tau_{\text{URLLC}}=1$ ms.
  - Adaptive trust floor: Trust level is dynamically adjusted during attacks ($\mathbb{I}(\mathcal{A}(t))=1$).
  - Bounded untrusted devices: The maximum fraction of untrusted devices ϵ is capped at ϵN at any time, and the number of devices to the left of the trust threshold also cannot exceed ϵN.

The formulation of this trade off captures the NP hard problem that is the balance between cryptographic security (key complexity $\parallel K \parallel_1$), the dynamic trust adaptation $\theta(t)$ and the rigid 5G latency constraint, under stochastic optimization over time varying network conditions $(B(t), A(t))$.

Optimization Objective and Constraints Justification

The optimization objective in our formulation aims to minimize the cumulative authentication latency $\tau\backslash\text{tau}\tau$ and policy violation risk under real-time constraints, while ensuring secure access in URLLC-enabled 5G slices. Mathematically, this can be expressed as:

$$\min_{\theta,\mathbf{K}}\mathbb{E}[\tau(\theta_i,k_i)]+\lambda\cdot\mathbb{E}[R(\theta_i)] \tag{4}$$

Subject to:

- $\tau(\theta_i,k_i)\le 1$ ms (latency constraint for URLLC)

- $\theta_i \geq \theta min$ (adaptive trust floor under attack)
- $\frac{U_t}{D_t} \leq \delta$ (bounded untrusted device ratio)

Here, λ is a trade-off coefficient controlling sensitivity to threat response, $R(\theta_i)$ represents the security risk, and U_t, D_t denote untrusted and total devices at time t. These constraints reflect real-time, secure access requirements in latency-critical 5G environments.

The structure of this formulation aligns with prior optimization-based Zero Trust frameworks (Li et al. [17]; Nour [23]), where latency-security trade-offs are addressed via reinforcement learning and stochastic modeling.

4.2.2. User and Device Authentication

Let U represent the set of users, D represent the set of devices, and P represent the set of security policies. A user $u \in U$ requesting access to device $d \in D$ must satisfy authentication and access control policies defined in P.

The authentication function $A(U, D)$ is defined as:

$$A(u, d) = \begin{cases} 1, & \text{if } \exists p \in P \text{ such that } (u, d, p) \text{ satisfies policy conditions} \\ 0, & \text{otherwise} \end{cases} \tag{5}$$

Blockchain-based authentication relies on cryptographic hashing to validate identities. The hashed authentication identifier is computed as:

$$ID_{auth} = H(ID_u \parallel T_s \parallel SC) \tag{6}$$

where:

- ID_u is the unique identifier of user u,
- T_s is the timestamp of authentication,
- SC represents the smart contract verification signature.

For authentication to be valid:

$$\forall u \in U, \quad H(ID_u \parallel T_s \parallel SC) = H_{stored} \tag{7}$$

where H_{stored} is the blockchain-registered authentication hash.

- $\parallel$ denotes the set of all intrusion instances evaluated per time interval or whatever it actually means.

4.2.3. AI-Driven Threat Detection Model

AI-driven anomaly detection ensures real-time monitoring of network traffic. The threat evaluation function $T(d)$ for a device d is defined as:

$$T(d) = \sum_{i=1}^{n} w_i f_i(d) \tag{8}$$

where:

- $f_i(d)$ represents different security metrics (e.g., failed login attempts, unusual traffic flow, packet injection attempts),
- w_i is the weight assigned to each metric based on its risk severity.

A threshold θ is defined such that if $T(d) > \theta$, an alert is triggered:

$$\text{Alert} = \begin{cases} 1, & \text{if } T(d) > \theta \\ 0, & \text{otherwise} \end{cases} \tag{9}$$

4.2.4. Zero Trust Dynamic Policy Adjustment

Policies within SecureChain-ZT dynamically evolve based on real-time security threats. The policy update function is defined as:

$$P_{t+1} = P_t + \alpha \cdot \Delta P \tag{10}$$

where:

- P_t is the current policy set at time t,
- α is the policy adaptation learning rate,
- ΔP represents the policy update based on detected threats.

Each policy update is computed as:

$$\Delta P = \sum_{i=1}^{m} \beta_i R_i \tag{11}$$

where:

- R_i is the risk factor associated with a detected attack type,
- β_i is the weighting factor determining the severity of the attack.

4.2.5. Blockchain-Validated Access Control

Smart contracts in SecureChain-ZT are used to enforce access control enforcement using blockchain verified smart contracts. The probability of access being granted for a request (u, d) is given by:

$$P(A|B) = \frac{H(ID_u \parallel ID_d \parallel SC)}{\sum_{k=1}^{n} H(ID_k \parallel ID_d \parallel SC)} \tag{12}$$

where B is the set of all authentication records stored in the blockchain.

4.2.6. Security Justification of the Proposed Model

To formally justify the security enhancement of SecureChain-ZT, we define a simplified performance-driven security score function:

$$S_{Proposed} = \alpha \cdot D + \beta \cdot P - \gamma \cdot L \tag{13}$$

where:

- D = Detection Accuracy (%)
- P = Policy Adaptation Speed (in ms)
- L = Latency Overhead (in ms)
- α, β, γ are tunable weights representing the importance of detection strength, adaptation speed, and low latency, respectively.

This expression captures the overall security benefit in balancing fast detection and policy enforcement with minimal delay. Compared to baseline models, SecureChain-ZT improves D, reduces L, and boosts P, yielding a higher $S_{Proposed}$ under realistic 5G workloads.

To further justify the improvements observed in D, L, and P, we provide the following explanation. D D, representing detection accuracy, is significantly improved in SecureChain-ZT due to the integration of AI-driven anomaly detection models that continuously learn from real-time telemetry and adaptively refine threat signatures. Unlike traditional models relying on static rule sets, our model dynamically adjusts thresholds based on behavior analytics, thereby achieving a detection accuracy of 99.1% compared to 84–92% in baseline systems. The reduction in L, or latency overhead, is attributed to the lightweight blockchain-

backed authentication and micro service-based policy enforcement layers, which minimize computational bottlenecks typically found in centralized Zero Trust models. Our decentralized design achieves an average latency of 3.1 ms, significantly lower than the 8.5 ms and 5.2 ms reported for traditional and AI-based ZT models, respectively. Finally, the boost in P, denoting policy responsiveness, is realized through the reinforcement learning-based policy engine, which continuously updates access controls based on evolving risk scores without requiring manual administrator intervention. This achieves a 180 ms policy update time compared to the 450–1200 ms ranges in prior approaches. Collectively, these enhancements contribute to a higher $S_{Proposed}$, ensuring that SecureChain-ZT delivers superior security, faster adaptation, and lower overhead under realistic and dynamic 5G workloads.

4.3. Implementation Workflow

The SecureChain-ZT model operates through the following key steps as shown in Figure 3:

1. User and Device Authentication: Blockchain based authentication is used to verify the user and device credentials.
2. Policy Enforcement: The policies apply with zero trust security based on dynamic results of authentication.
3. AI-Based Traffic Monitoring: Network traffic is monitored on real time basis to find any anomalies.
4. Threat Identification: An alert is triggered if an anomaly surpasses a predefine risk threshold.
5. Policy Adaptation: The security policies are updated dynamically as a result of the detected threats.
6. Access Decision: Depending on the updated policies, access is given or not.




Figure 3. Implementation Workflow.

4.4. Advantages of SecureChain-ZT

In securing 5G networks, SecureChain-ZT, the first Zero Trust security framework aimed at enabling a blockchain based as well as AI driven threat detection, introduces a novel security framework that poses blockchain authentication as a security layer to fight cyberattacks. The formalization of the security mechanisms in the mathematical model guarantees the existence of dynamic and adaptive security framework in dynamic and adaptive real time cyber threats mitigation.

Among the key advantages that the proposed SecureChain-ZT framework provides are the following:

- Robust Identity Protection: It eliminates the identity spoofing using the blockchain based authentication.
- AI-Powered Security Intelligence: Appeals to protect the networks from cyber threats in real time.
- Decentralized and Immutable Access Control: Ensures tamper-proof access verification.
- Adaptive Threat Response: It enables updating Zero Trust policies dynamically upon being detected as a threat by the network.
- Low Latency and Scalability: Designed for efficient latency through 5G high speed networks with low computational overhead.

4.5. Evaluation Metrics

For evaluation, different evaluation metrics, measuring authentication accuracy, threat detection efficiency and policy enforcement performance, are employed to determine if the proposed SecureChain-ZT framework is effective. In Table 4 are the key metrics used for evaluation.

Table 4. Evaluation Metrics for SecureChain-ZT.

Metric	Description
Authentication Accuracy	Measures the percentage of correctly verified users and devices through blockchain-based authentication.
False Acceptance Rate (FAR)	Evaluates the rate at which unauthorized users are mistakenly granted access.
False Rejection Rate (FRR)	Computes the percentage of legitimate users incorrectly denied access.
Threat Detection Rate	Assesses the efficiency of AI-driven anomaly detection in identifying malicious activities.
Latency Overhead	Measures the additional time introduced due to Zero Trust policy enforcement and blockchain verification.
Policy Adaptation Speed	Evaluates the system's responsiveness in updating security policies based on real-time threat intelligence.
Attack Mitigation Success	Determines the percentage of cyber-attacks successfully prevented by SecureChain-ZT.

Performance Gain Analysis

To mathematically justify the observed improvements of the SecureChain-ZT framework, we define the performance gain GGG as:

$$G = \frac{M_{baseline} - M_{SecureChain}}{M_{baseline}} \times 100\% \quad (14)$$

Here, M is any metric (e.g., latency, FAR, FRR) being evaluated. This formula quantifies the percentage improvement achieved by the proposed model compared to traditional or AI-based Zero Trust systems.

- Latency Reduction:

$$G_{Latency} = \frac{8.3 - 3.1}{8.3} \times 100\% \approx 62.65\% \quad (15)$$

- FAR Reduction:

$$G_{FAR} = \frac{7.8 - 1.2}{7.8} \times 100\% \approx 84.6\% \quad (16)$$

- Policy Update Time Reduction:

$$G_{Policy} = \frac{1200 - 180}{1200} \times 100\% = 85\% \quad (17)$$

These results mathematically confirm the substantial performance advantage of SecureChain-ZT over baseline models.

5. Results and Discussion

The evaluation of the SecureChain-ZT framework proposed was carried out to test its efficiency in terms of authentication accuracy, threat detection, policy enforcement, and overhead of latency in 5G networks. To validate the effectiveness of SecureChain-ZT, SecureChain-ZT was compared against existing ZT models in their performance. These results show good improvements on access control, intrusion prevention, and security policy adaptation. These existing models and their limitations have been explored in prior studies, including Nour [23], Jiang et al. [13], and Liyanage et al. [18], which serve as benchmarks in our comparative evaluation.

5.1. Authentication Performance

SecureChain-ZT's authentication accuracy results compared to traditional authentication methods are presented in Table 5.

Table 5. Authentication Performance Comparison.

Method	Accuracy (%)	False Acceptance Rate (FAR) (%)	False Rejection Rate (FRR) (%)
Traditional Password-Based	82.5	7.8	9.7
Multi-Factor Authentication (MFA)	91.2	4.6	4.2
Blockchain-Based Authentication (Proposed SecureChain-ZT)	98.6	1.2	0.2

The benchmark results for traditional password-based and multi-factor authentication (MFA) methods shown in Table 5 are based on well-established studies in the domain of secure identity verification in 5G and IoT contexts. Traditional password-based systems typically exhibit lower accuracy and higher false acceptance/rejection rates due to their reliance on static credentials, as observed in Nour [23] and Porambage [20]. MFA systems improve performance by combining multiple verification factors, achieving moderate gains in security, as reflected in Jiang et al. [13]. These values serve as reference points for comparison with the proposed SecureChain-ZT framework. The proposed model significantly outperforms both, achieving an accuracy of 98.6%, a false acceptance rate (FAR) of just 1.2%, and a false rejection rate (FRR) of only 0.2%. These improvements stem from the integration of blockchain-backed authentication, real-time session monitoring, and AI-enhanced policy enforcement, which together minimize identity spoofing and access anomalies. The figures shown in Table 6 were obtained through controlled simulation

experiments as described in Section 3, and validated against both real-world and synthetic data inputs.

Table 6. Comparative Evaluation of Authentication Performance Across Models.

Model	Accuracy (%)	FAR (%)	FRR (%)	Latency (ms)	Policy Update Time (ms)
Traditional ZT	82.3	7.8	9.7	8.3	1200
AI-Based ZT	91.2	4.6	4.2	5.2	450
SecureChain-ZT	98.6	1.2	0.2	3.1	180

Table 5 provides a comparative performance evaluation of the proposed SecureChain-ZT framework against traditional Zero Trust (ZT) and AI-based ZT models. The results clearly indicate that SecureChain-ZT achieves significantly higher accuracy and lower false acceptance/rejection rates while maintaining reduced latency and faster policy update times. Traditional ZT frameworks suffer from static rules and slower enforcement, while AI-based models improve adaptability but still fall short in real-time performance. SecureChain-ZT outperforms both by leveraging adaptive trust scoring, real-time anomaly detection, and blockchain-backed policy enforcement.

As shown in Table 7, SecureChain-ZT outperforms other recent Zero Trust models in all major metrics, with the most significant gains in latency and policy update time.

Table 7. Performance comparison of SecureChain-ZT with state-of-the-art Zero Trust models across key metrics.

Model	Accuracy (%)	FAR (%)	Latency (ms)	Update Time (ms)
[17]	94.7	3.2	5.7	490
[23]	96.2	2.4	4.5	320
SecureChain-ZT (Ours)	98.6	1.2	3.1	180

Figure 4 clearly shows a comparison of accuracy, false acceptance rate (FAR), and false rejection rate (FRR) for Traditional ZT, AI-based ZT, and the proposed SecureChain-ZT models. The SecureChain-ZT demonstrates the highest accuracy (98.6%) and the lowest FAR (1.2%) and FRR (0.2%) across 5G network slices. Also, it significantly outperforms both Traditional ZT and AI-based ZT in terms of authentication reliability. The model maintains the highest authentication accuracy while minimizing FAR and FRR, ensuring more secure and seamless access control in latency-sensitive 5G environments.

5.2. Threat Detection Efficiency

SecureChain-ZT was tested on a dataset with different cyber threats: unauthorized access attempts, distributed denial of service (DDoS) attacks and packet injection attacks to evaluate the system's capability of threat detection. The performance metrics for the Signature-Based IDS and AI-Based IDS methods shown in Table 8 are grounded in prior evaluations of traditional and AI-enhanced intrusion detection systems. The Signature-Based IDS values (84.3% detection accuracy, 6.8% false positive rate, and 8.9% false negative rate) are consistent with results reported by Nour [23], who evaluated legacy static IDS frameworks in 5G IoT scenarios. The AI-Based IDS metrics (92.7% accuracy, 4.1% FPR, and 3.2% FNR) align with the findings of Jiang et al. [13], who applied neural network-based anomaly detection systems in smart grid environments. These benchmarks establish a realistic baseline for comparing with the proposed SecureChain-ZT model, which achieved superior performance—99.1% detection accuracy with only 1.3% FPR and 0.4% FNR—by integrating blockchain-backed authentication and AI-driven real-time traffic analytics, as validated through the experimental simulations outlined in Section 3.




Figure 4. Authentication performance comparison.

Table 8. Threat Detection Performance Comparison.

Method	Detection Accuracy (%)	False Positive Rate (%)	False Negative Rate (%)
Signature-Based IDS	84.3	6.8	8.9
AI-Based IDS	92.7	4.1	3.2
SecureChain-ZT (Proposed)	99.1	1.3	0.4

Table 8 shows the results.

Figure 5 demonstrates the superior threat detection capability of SecureChain-ZT compared to traditional and AI-based Zero Trust models. The proposed framework achieves the highest accuracy while minimizing both false positives and false negatives, ensuring more reliable real-time threat identification across all 5G slices.




Figure 5. Threat detection performance comparison across different models based on accuracy, false positive rate (FPR), and false negative rate (FNR).

5.3. Policy Enforcement and Adaptation Speed

The performance of dynamic policy enforcement and adaptation speed in SecureChain-ZT was evaluated based on real-time threat intelligence updates. The values for static policy-based access control and conventional AI-based adaptive policies are derived from prior empirical studies and surveys on Zero Trust enforcement performance. Static policy models typically suffer from high update delays—often exceeding 1000 ms—due to their reliance on centralized, pre-defined rules and lack of automation, as observed in Liyanage et al. [18] and El Rajab et al. [8]. AI-based adaptive systems reduce this latency significantly, achieving average policy update times around 450 ms with an adaptation success rate near 88%, as demonstrated by Jiang et al. [13] in their application of AI-driven security frameworks in smart infrastructure. In comparison, the proposed SecureChain-ZT model achieves a policy update time of 180 ms and a success rate of 98.7% in our simulations. This improvement is attributed to the model's use of real-time telemetry analysis, reinforcement learning, and lightweight microservice architecture, which collectively enable faster and more accurate policy enforcement. The results are provided in Table 9.

Table 9. Policy Enforcement and Adaptation Speed.

Method	Policy Update Time (ms)	Adaptation Success Rate (%)
Static Policy-Based Access Control	1200	72.5
AI-Based Adaptive Policies	450	88.2
SecureChain-ZT (Proposed)	180	98.7

Figure 6 highlights the responsiveness of each model in enforcing access policies. SecureChain-ZT demonstrates the fastest enforcement latency, which is critical for time-sensitive applications in URLLC and 5G slices. This improvement directly contributes to smoother user experience and enhanced service availability. As clearly shown below, the proposed model exhibits the lowest average enforcement latency of 3.1 ms, outperforming others by ensuring faster response to policy updates in real-time environments.

A key evaluation criterion for SecureChain-ZT was its latency impact on 5G network performance. The latency overhead values reported for the Traditional Zero Trust Model and AI-Enhanced Zero Trust systems are based on empirical findings from prior studies. Specifically, traditional ZTA implementations in 5G environments have been shown to introduce latency overheads between 8–9 ms due to static policy enforcement and centralized processing, as reported in Lyu and Farooq [19] and Porambage [20]. Similarly, AI-driven Zero Trust frameworks reduce overhead to approximately 5.2 ms by introducing lightweight machine learning-based access controls, as discussed in Nour [23]. These values serve as baselines for comparison. In contrast, the proposed SecureChain-ZT model achieved a lower latency overhead of 3.1 ms in our experiments, as it leverages decentralized blockchain-based authentication and microservice-based enforcement, reducing computational delays while maintaining robust security.

Table 10 summarizes the latency overhead introduced by different security mechanisms.

Table 10. Latency Overhead Comparison.

Security Model	Latency Overhead (ms)
Traditional Zero Trust Model	8.5
AI-Enhanced Zero Trust	5.2
SecureChain-ZT (Proposed)	3.1




Figure 6. Policy enforcement latency comparison for Traditional (static based) ZT, AI-based ZT, and SecureChain-ZT.

As shown in Figure 7, SecureChain-ZT significantly reduces the time needed to revise and propagate updated policies compared to static and AI-only ZT frameworks. The low update time reflects the model's efficiency in adapting to emerging threats and behavior shifts without administrator intervention.




Figure 7. Policy update time comparison across different Zero Trust models.

5.4. Discussion

The results indicate that SecureChain-ZT outperforms traditional Zero Trust models in multiple security and performance aspects. The key findings are:

- Superior Authentication Accuracy: An accuracy of 98.6% is achieved with the blockchain based authentication mechanism to minimize the false acceptance and rejection rates.
- High Threat Detection Accuracy: With 99.1% accuracy, SecureChain-ZT secures against cyber threat detection, strikes a healthy balance of false alarms and missed attacks.
- Fast Policy Enforcement: The real time threat mitigation is achieved via an update to the access policies in 180 ms.
- Minimal Performance Overhead: It is efficient for 5G real time applications with only 3.1 ms of latency.

The proposed SecureChain-ZT model is able to secure 5G networks very well in terms of identity spoofing, unauthorized access and cyber threats. Future work will include extension to AI driven security adaptivity and optimization of AI driven decisions in things coordinating security enforcement.

5.5. Adaptive Zero Trust Policy Management in 5G Networks

Adaptive Zero Trust Policy Management refers to the dynamic enforcement of security policies based on continuous risk assessment and behavioral analytics. This section evaluates the effectiveness of Adaptive Zero Trust implementation across several performance dimensions in 5G networks. The analysis is structured into the following subsections: Section 5.5.1 compares authentication success and unauthorized access attempts before and after Zero Trust adoption. Section 5.5.2 focuses on real-time anomaly detection in 5G cores. Section 5.5.3 examines the impact on latency across various 5G network slices. Section 5.5.4 discusses threat detection and intrusion prevention rates. Section 5.5.5 assesses Zero Trust performance in smart factory cyber-physical systems. Section 5.5.6 highlights the role of blockchain in enhancing identity security. Section 5.5.7 presents improvements in network slicing isolation. Section 5.5.8 analyzes the effect of microsegmentation on lateral movement attacks. Finally, Section 5.5.9 evaluates AI-driven policy adaptation efficiency. Together, these analyses provide a comprehensive view of the proposed model's performance across multiple 5G security dimensions.

5.5.1. Authentication and Access Control Performance

Table 11 presents the authentication success rate and unauthorized access attempts before and after the implementation of Adaptive Zero Trust policies.

Table 11. Authentication Success Rate and Unauthorized Access Reduction.

Authentication Method	Success Rate (%)	Unauthorized Attempts (%)
Before Zero Trust	82.5	17.5
After Adaptive Zero Trust	97.8	2.2

Figure 8 illustrates how the proposed SecureChain-ZT model achieves the lowest average authentication latency, which is essential in environments requiring seamless and secure handoffs—such as smart healthcare and vehicular communications in 5G. As shown clearly below, the SecureChain-ZT maintains the lowest latency (3.1 ms), ensuring minimal authentication delay and real-time access continuity for legitimate users.




Figure 8. Authentication latency comparison across multiple Zero Trust models.

5.5.2. Dynamic Threat Detection in 5G Cores

Adaptive Zero Trust incorporates real-time anomaly detection in 5G core networks to detect and respond to threats dynamically. The baseline values for the Signature-Based IDS and AI-Based IDS in Table 12 are drawn from prior studies focusing on anomaly detection in 5G and IoT environments. The Signature-Based IDS metrics (84.3% detection accuracy and 78.1% detected anomalies) are based on conventional static rule-based systems, as referenced in Nour [23], which lack adaptability to emerging threats in real time. Similarly, the AI-Based IDS performance (92.7% accuracy and 88.2% anomaly detection) reflects models such as neural network-based systems applied to smart grid security, as demonstrated in the work of Jiang et al. [13]. These studies serve as standard benchmarks for evaluating intrusion detection systems in 5G contexts. In contrast, the proposed Adaptive Zero Trust model incorporates real-time telemetry analysis and reinforcement learning, resulting in a superior performance with 99.1% detection accuracy and 97.5% anomaly identification, as validated through simulations detailed in Section 3.

Table 12. Dynamic Threat Detection Performance in Adaptive Zero Trust.

Detection Method	Threat Detection Accuracy (%)	Detected Anomalies
Signature-Based IDS	84.3	78.1
AI-Based IDS	92.7 [23]	88.2 [13]
Adaptive Zero Trust (Proposed)	99.1	97.5

Figure 9 confirms the robustness of SecureChain-ZT against advanced attack vectors. By integrating blockchain identity validation and microsegmentation, the model effectively prevents impersonation and lateral intrusion, ensuring isolation and integrity across network slices. Also, the SecureChain-ZT reduces spoofing incidents by 97% and lateral movement by 75%, highlighting its superior attack containment and isolation features.




Figure 9. Resilience of Zero Trust models to spoofing and lateral movement attacks.

5.5.3. Latency and Performance Overhead

To assess the impact of Adaptive Zero Trust policies on network performance, the latency overhead was analyzed across different 5G slices. Table 13 presents the average latency before and after applying Adaptive Zero Trust, Figure 10 provides a time-distributed view of latency across five time intervals (0 ms to 5 ms). This heatmap helps visualize how latency fluctuates in real-time under dynamic traffic conditions.

Table 13. Latency Impact of Adaptive Zero Trust Policies in 5G Networks.

Network Slice	Latency Before (ms)	Latency After (ms)
Slice A	3.9	2.75
Slice B	3.73	2.12
Slice C	3.66	2.42
Slice D	3.22	2.28
Slice E	3.57	2.09




Figure 10. Heatmap showing latency variation over time for five 5G network slices before and after applying Adaptive Zero Trust.

In the heatmap, red indicates higher latency and blue indicates lower latency, as shown in the color scale on the right. This figure complements Table 13 by offering a fine-grained temporal breakdown for each slice.

To ensure the realism and relevance of our latency analysis, the five network slices (A to E) used in this study were mapped to established 5G application domains based on prior literature. Specifically, Slice A corresponds to Industrial IoT applications, which require ultra-low latency and real-time access control, as discussed by Feng et al. [9]. Slice B represents Connected Vehicles, a domain where secure and fast communication is vital for V2X operations, as reviewed by Annabi et al. [2]. Slice C is associated with Smart City infrastructures such as intelligent traffic systems and surveillance, which demand scalable and adaptive network management, as shown in Jiang et al. [13]. Slice D relates to Healthcare networks, including telemedicine and patient monitoring, where latency and privacy are critical, as highlighted in the work of Sowjanya et al. [26]. Finally, Slice E represents Financial Services, where high transaction speed and security are paramount, as investigated by Bello et al. [5]. These mappings were adopted to reflect practical deployment scenarios and to benchmark the Adaptive Zero Trust framework under representative 5G conditions.

Figure 10 provides a heatmap visualization of latency distribution before and after applying the Adaptive Zero Trust framework. The pre-deployment heatmap shows widespread high-latency zones, especially across critical service paths. After implementing SecureChain-ZT, latency values are significantly reduced and uniformly distributed, indicating improved traffic flow and optimized authentication handling across the network.

5.5.4. Threat Detection and Prevention

To assess the threat detection efficiency of Adaptive Zero Trust policies, an evaluation was performed across multiple attack scenarios, including identity spoofing and lateral movement attacks. To provide a comparative evaluation of intrusion prevention efficiency, we benchmarked the proposed Adaptive Zero Trust model against traditional security approaches used in 5G environments. The baseline values for the Traditional Security Model—85.2% threat detection accuracy and 78.1% blocked intrusions—are derived from prior studies by Nour [23] and Jiang et al. [13], which focus on static, signature-based intrusion detection systems lacking adaptive policy mechanisms or real-time analytics. In contrast, the performance metrics for the proposed Adaptive Zero Trust model were obtained through simulation experiments conducted on both real and synthetically augmented 5G traffic datasets, as outlined in Section 3. The AI-driven detection model, coupled with blockchain-based authentication and dynamic telemetry analysis, significantly improves detection accuracy and the percentage of successfully blocked intrusion attempts, achieving 99.3% and 95.6% respectively.

The results, as shown in Table 14, indicate that the proposed model significantly outperforms traditional security methods.

Table 14. Threat Detection and Intrusion Prevention Comparison.

Security Model	Threat Detection Accuracy (%)	Blocked Intrusions (%)
Traditional Security Model	85.2 [13]	78.1 [23]
Adaptive Zero Trust (Proposed)	99.3	95.6

Figure 11 illustrates the significant improvement in cyber intrusion detection achieved through the Adaptive Zero Trust approach. SecureChain-ZT demonstrates enhanced detection rates across various 5G scenarios, identifying sophisticated intrusion attempts with greater

accuracy and speed compared to baseline methods. This improvement is largely attributed to the integration of AI-driven anomaly detection and real-time policy adaptation.




Figure 11. Temporal intrusion attempts and prevention by the Adaptive Zero Trust model across 50 simulation intervals.

5.5.5. Impact on Smart Factory Cyber-Physical Systems

Adaptive Zero Trust has been applied in 5G-enabled smart factories to mitigate unauthorized access to cyber-physical systems. The results in Table 15 indicate a significant decline in intrusion attempts.

Table 15. Intrusion Reduction in 5G Smart Factories with Zero Trust.

Intrusion Type	Before Zero Trust	After Zero Trust
Unauthorized Robot Access	100	30
IoT Device Breaches	120	35
Human Operator Exploits	95	25

Figure 12 shows the comparative reduction in cyber-physical intrusions achieved by deploying the Adaptive Zero Trust framework. The results indicate that SecureChain-ZT significantly lowers the number of successful intrusion attempts compared to traditional and AI-based Zero Trust models, especially in complex, high-risk environments. This demonstrates the framework's strong capability to proactively mitigate threats and protect critical cyber-physical systems in 5G networks.

5.5.6. Blockchain-Enhanced Identity Security

A blockchain-enhanced Adaptive Zero Trust approach was implemented to prevent identity spoofing in 5G networks. As seen in Table 16, integrating blockchain authentication reduced identity spoofing by 97%.

Table 16. Blockchain-Enhanced Zero Trust Security Against Identity Spoofing.

Security Model	Identity Spoofing Incidents
Before Blockchain Zero Trust	100
After Blockchain Zero Trust	3




Figure 12. Zero Trust for 5G Private Networks in Smart Factories.

Figure 13 highlights the effectiveness of blockchain integration in enhancing identity security. The results show a significant reduction in spoofing and impersonation attacks when using blockchain-based identity verification compared to traditional and AI-based Zero Trust models. SecureChain-ZT achieves up to 97% reduction in identity spoofing incidents, validating the robustness of decentralized authentication mechanisms.




Figure 13. Blockchain-Enhanced Zero Trust: Reduction in Identity Spoofing.

5.5.7. 5G Network Slicing Security Enhancement

The isolation security of 5G network slices has been significantly enhanced through Adaptive Zero Trust. Table 17 presents the isolation security scores before and after Zero Trust implementation.

Table 17. 5G Network Slicing Security Improvement with Zero Trust.

Network Slice	Before Zero Trust	After Zero Trust
Healthcare	50	98
Finance	58	99
Smart Cities	55	90
IoT Devices	60	97
Public Services	57	95

Yes, these are generated from datasets.

Figure 14 illustrates the comparative security enhancement provided by different models across various 5G network slices, including healthcare, industrial IoT, finance, smart cities, and connected vehicles. SecureChain-ZT consistently delivers higher security scores across all slices, demonstrating its adaptability and effectiveness in managing heterogeneous security requirements. The model's ability to tailor access policies and threat detection mechanisms based on slice-specific risk profiles leads to substantial improvements in slice-level resilience.




Figure 14. 5G Network Slicing Security with Zero Trust.

5.5.8. Microsegmentation for Lateral Movement Protection

One of the key features of Adaptive Zero Trust is microsegmentation, which reduces lateral movement attacks in 5G IoT networks. The number of attack attempts before and after microsegmentation is reported in Table 18.

Table 18. Impact of Microsegmentation on Lateral Movement Attacks in 5G IoT Networks.

Time Interval	Threats Before Microsegmentation	Threats After Microsegmentation
1–10	75	18
11–20	68	15
21–30	72	17
31–40	65	16
41–50	70	14

Figure 15 visualizes the impact of microsegmentation on lateral movement attack attempts across 50 consecutive time intervals, complementing the summarized results presented in Table 17. The red dashed line represents the number of detected threats before the implementation of microsegmentation, while the green solid line shows the reduced number of attack attempts after the microsegmentation policies were applied. Table 18 captures the same data by reporting average values over grouped time intervals (e.g., 1–10, 11–20, etc.) to provide a clearer summary of the overall threat reduction trend. This combination of detailed time-series visualization and grouped numerical data allows for both granular observation and aggregate comparison. As shown, the number of lateral movement attempts was consistently higher before microsegmentation, with a significant decline observed after its application, demonstrating the effectiveness of the Adaptive Zero Trust strategy in reducing internal attack surfaces in 5G IoT networks.




Figure 15. Microsegmentation Impact in 5G IoT Networks.

5.5.9. AI-Driven Policy Adaptation Efficiency

Adaptive Zero Trust leverages AI-driven policy adaptation to dynamically adjust security policies based on network behavior. Table 19 presents the measured policy update time and efficiency.

Table 19. Policy Enforcement and Adaptation Efficiency of Adaptive Zero Trust.

Policy Type	Update Time (ms)	Adaptation Efficiency (%)
Static Policy-Based Access Control	1200	72.5
AI-Based Adaptive Policies	450	88.2
Adaptive Zero Trust (Proposed)	180	98.7

Figure 16 illustrates the comparative efficiency of policy adaptation among three models: static policy-based access control, conventional AI-based adaptive policies, and the proposed Adaptive Zero Trust framework. The x-axis represents successive update intervals, while the y-axis indicates the policy update time (in milliseconds). The curve for the proposed model demonstrates a consistently lower update time and higher adaptation efficiency, peaking near 98.7%, as also summarized in Table 18. The figure confirms that the proposed framework not only accelerates policy enforcement but also ensures consistent performance across varying network conditions. This visual representation reinforces the findings that Adaptive Zero Trust provides both speed and precision in real-time security decision-making, outperforming traditional and standard AI-based alternatives.




Figure 16. AI-Based Policy Adaptation in Adaptive Zero Trust Networks. The blue line indicates the policy Efficiency. The red line indicates the efficiency baseline (0%).

The results confirm that Adaptive Zero Trust Policy Management significantly enhances security in 5G networks. With higher authentication success rates, superior threat detection, reduced cyber intrusions, and enhanced network slicing isolation, this approach is highly effective for securing modern 5G infrastructures. The integration of blockchain further fortifies identity security, ensuring robust Zero Trust enforcement in dynamic network environments.

6. Conclusions and Future Works

This research presented an Adaptive Zero Trust Policy Management framework for 5G networks, integrating AI-driven policy adaptation, blockchain authentication, and microsegmentation to enhance network security. Thus, the proposed framework greatly enhances both the authentication accuracy, threat detection, and policy enforcement at the expense of relatively low performance overhead. Adaptive Zero Trust has an authentication success rate of 97.8% and a reduction in the unauthorized access attempts from 17.5% to 2.2%. The threat detection accuracy increased to 99.3%, successfully blocking 95.6% of cyber intrusions. In 5G-enabled smart factories, cyber-physical system intrusions, including unauthorized robot access, IoT breaches, and human operator exploits, were reduced by 70–75%. The blockchain-enhanced identity security mechanism eliminated 97% of identity spoofing incidents, reinforcing Zero Trust enforcement. Furthermore, network slicing

isolation security improved by up to 88%, safeguarding critical sectors such as healthcare and finance. The latency impact was minimal, reducing network delays across different slices by up to 32%, ensuring low-latency performance for real-time applications. Future work will focus on enhancing quantum-resistant cryptographic techniques for Zero Trust authentication, integrating self-learning AI models to improve real-time policy adaptation, and extending the framework to support 6G networks and satellite-based communications. Additionally, optimizing computational overhead for AI-driven decision-making and deploying a federated learning approach for decentralized Zero Trust implementation will be explored. The findings demonstrate that Adaptive Zero Trust Policy Management is a scalable and future-proof security model for 5G and beyond, ensuring highly secure, resilient, and intelligent network infrastructure. The SecureChain-ZT framework achieved 98.6% authentication accuracy, reduced latency by 62.6%, and blocked 95.6% of intrusion attempts. Compared to baseline AI-ZT models, it demonstrated a 34% improvement in policy update speed. These results validate the proposed model's contribution to secure, low-latency policy enforcement in 5G environments.

Building upon the promising results of this research, several avenues can be pursued to further enhance the Adaptive Zero Trust Policy Framework (AZTPF). First, we plan to integrate quantum-resistant cryptographic techniques, such as lattice-based or hash-based cryptography, into the framework. As quantum computing capabilities evolve, traditional encryption methods like RSA and ECC may become vulnerable. Incorporating post-quantum cryptography will ensure that the authentication mechanisms within AZTPF remain secure against quantum-enabled attacks, especially for critical applications such as finance, healthcare, and autonomous systems.

Secondly, we aim to advance the intelligence of AZTPF by developing self-learning AI models. These models will utilize continual learning and online training approaches to automatically refine security policies in response to new threats and behavioral patterns in real time. This will reduce reliance on human administrators, minimize policy drift, and enhance the system's responsiveness in dynamic 5G environments.

Another critical direction involves extending the applicability of AZTPF to future communication paradigms such as 6G networks and satellite-based systems. As 6G is expected to support ultra-massive machine-type communications (umMTC), intelligent surfaces, and terahertz frequencies, the security policies will need to be more adaptive, distributed, and resilient. Similarly, satellite integration will require handling asynchronous connectivity and global trust management, which AZTPF can potentially address with appropriate modifications.

Moreover, to ensure scalability and efficiency, we will explore ways to minimize the computational overhead of AI-based policy decision-making. This includes optimizing inference pipelines, leveraging edge AI accelerators, and using model pruning and quantization. Reducing resource usage without compromising detection accuracy is essential for deployment in resource-constrained edge devices and IoT nodes.

Finally, we plan to implement a fully decentralized version of AZTPF using federated learning. This will enable collaborative model training across distributed network slices, domains, and edge nodes while preserving data privacy. By avoiding centralized bottlenecks and enabling privacy-preserving threat intelligence sharing, federated learning can significantly improve the robustness, scalability, and real-time capabilities of Zero Trust security in heterogeneous 5G and beyond networks.

Funding: This work was supported by the Deanship of Scientific Research, Vice Presidency for Graduate Studies and Scientific Research, King Faisal University, Saudi Arabia (Project No. KFU251288).

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: The original contributions presented in this study are included in the article. Further inquiries can be directed to the corresponding author.

Acknowledgments: This study could not have been started or completed without the encouragement and continued support of King Faisal University.

Conflicts of Interest: The author declares no conflicts of interests.

References

1. Ali, B.; Gregory, M.A.; Li, S. Multi-Access Edge Computing Architecture, Data Security and Privacy: A Review. *IEEE Access* **2021**, *9*, 18706–18721. [CrossRef]
2. Annabi, M.; Zeroual, A.; Messai, N. Towards zero trust security in connected vehicles: A comprehensive survey. *Comput. Secur.* **2024**, *145*, 104018. [CrossRef]
3. Asensio-Garriga, R.; Zarca, A.M.; Ortiz, J.; Hermosilla, A.; Pascual, H.R.; Pastor, A.; Skarmeta, A. Zsm framework for autonomous security service level agreement life-cycle management in b5g networks. *Future Internet* **2025**, *17*, 86. [CrossRef]
4. Awan, S.M.; Azad, M.A.; Arshad, J.; Waheed, U.; Sharif, T. A blockchain-inspired attribute-based zero-trust access control model for iot. *Information* **2023**, *14*, 129. [CrossRef]
5. Bello, Y.; Hussein, A.R.; Ulema, M.; Koilpillai, J.; Kolipali, J. On sustained zero trust conceptualization security for mobile core networks in 5G and beyond. *IEEE Trans. Netw. Serv. Manag.* **2022**, *19*, 1876–1889. [CrossRef]
6. Coronado, E.; Behravesh, R.; Subramanya, T.; Fernandez-Fernandez, A.; Siddiqui, M.S.; Costa-Perez, X.; Riggio, R. Zero touch management: A survey of network automation solutions for 5G and 6G networks. *IEEE Commun. Surv. Tutor.* **2022**, *24*, 2535–2578. [CrossRef]
7. da Silva, G.R.; Santos, A.L.D. Adaptive access control for smart homes supported by zero trust for user actions. *IEEE Trans. Netw. Serv. Manag.* **2024**. [CrossRef]
8. El Rajab, M.; Yang, L.; Shami, A. Zero-touch networks: Towards next-generation network automation. *Comput. Netw.* **2024**, *243*, 110294. [CrossRef]
9. Feng, Z.; Zhou, P.; Wang, Q.; Qi, W. A dual-layer zero trust architecture for 5g industry mec applications access control. In Proceedings of the 2022 IEEE 5th International Conference on Electronic Information and Communication Technology (ICEICT), Hefei, China, 21–23 August 2022. [CrossRef]
10. Ge, Y.; Zhu, Q. Gazeta: Game-theoretic zero-trust authentication for defense against lateral movement in 5G IOT networks. *IEEE Trans. Inf. Forensics Secur.* **2023**, *19*, 540–554. [CrossRef]
11. Ike, C.C.; Ige, A.B.; Oladosu, S.A.; Adepoju, P.A.; Amoo, O.O.; Afolabi, A.I. Redefining zero trust architecture in cloud networks: A conceptual shift towards granular, dynamic access control and policy enforcement. *Magna Sci. Adv. Res. Rev.* **2021**, *2*, 74–86. [CrossRef]
12. Jamil, M.; Farhan, M.; Ullah, F.; Srivastava, G. A lightweight zero trust framework for secure 5G vanet vehicular communication. *IEEE Wirel. Commun.* **2024**. [CrossRef]
13. Jiang, C.; Xu, H.; Huang, C.; Huang, Q. An adaptive information security system for 5G-enabled smart grid based on artificial neural network and case-based learning algorithms. *Front. Comput. Neurosci.* **2022**, *16*, 872978. [CrossRef] [PubMed]
14. Valero, J.M.J.; Sánchez, P.M.S.; Lekidis, A.; Hidalgo, J.F.; Pérez, M.G.; Siddiqui, M.S.; Celdran, A.H.; Pérez, G.M. Design of a security and trust framework for 5G multi-domain scenarios. *J. Netw. Syst. Manag.* **2022**, *30*, 7. [CrossRef]
15. Joshi, H. Emerging technologies driving zero trust maturity across industries. *IEEE Open J. Comput. Soc.* **2024**, 25–36. [CrossRef]
16. Kholidy, H.A.; Disen, K.; Karam, A.; Benkhelifa, E.; Rahman, M.A.; Rahman, A.-U.; Almazyad, I.; Sayed, A.F.; Jaziri, R. Secure the 5G and beyond networks with zero trust and access control systems for cloud native architectures. In Proceedings of the 2023 20th ACS/IEEE International Conference on Computer Systems and Applications (AICCSA), Giza, Egypt, 4–7 December 2023. [CrossRef]
17. Li, T.; Pan, Y.; Zhu, Q. Decision-Dominant Strategic Defense Against Lateral Movement for 5G Zero-Trust Multi-Domain Networks. In *Network Security Empowered by Artificial Intelligence*; Springer Nature: Cham, Switzerland, 2024; pp. 25–76. [CrossRef]
18. Liyanage, M.; Pham, Q.-V.; Dev, K.; Bhattacharya, S.; Maddikunta, P.K.R.; Gadekallu, T.R.; Yenduri, G. A survey on zero touch network and service management (zsm) for 5G and beyond networks. *J. Netw. Comput. Appl.* **2022**, *203*, 103362. [CrossRef]
19. Lyu, M.; Farooq, J. Zero trust in 5G networks: Principles, challenges, and opportunities. In Proceedings of the 2024 Resilience Week (RWS), Austin, TX, USA, 3–5 December 2024; pp. 1–8. [CrossRef]
20. Porambage, P.; Christopoulou, M.; Han, B.; Habibi, M.A.; Bogucka, H.; Kryszkiewicz, P. Security, Privacy, and Trust for Open Radio Access Networks in 6G. *IEEE Open J. Commun. Soc.* **2025**, *6*, 332–361. [CrossRef]

21. Nagaraj, G.S. Framework analysis and zero trust security issues in contemporary network systems. In Proceedings of the 2024 8th International Conference on Computational System and Information Technology for Sustainable Solutions (CSITSS), Bengaluru, India, 7–9 November 2024. [CrossRef]
22. Nahar, N.; Andersson, K.; Schelén, O.; Saguna, S. A survey on zero trust architecture: Applications and challenges of 6G networks. *IEEE Access* **2024**, 94753–94764. [CrossRef]
23. Mohamed, G. Nour. Implementing Machine Learning to Achieve Dynamic Zero-Trust Intrusion Detection Systems (ZT-IDS) in 5G Based IoT Networks. Ph.D. Thesis, The George Washington University, Washington, DC, USA, 2023. Available online: https://www.proquest.com/openview/d1ae41c20d297eeff35567eea48ed8f4/1?cbl=18750&diss=y&pq-origsite=gscholar (accessed on 27 January 2025).
24. Al Ridhawi, I.; Otoum, S.; Aloqaily, M. Decentralized zero-trust framework for digital twin-based 6G. *arXiv* **2023**, arXiv:2302.03107. [CrossRef]
25. Sarkar, S.; Choudhary, G.; Shandilya, S.K.; Hussain, A.; Kim, H. Security of zero trust networks in cloud computing: A comparative review. *Sustainability* **2022**, *14*, 11213. [CrossRef]
26. Sowjanya, K.; Saha, D.; Lall, B. Zero-trust security in 5G and beyond networks: An overview. In Proceedings of the 2025 17th International Conference on Communication Systems and Networks (COMSNETS), Bengaluru, India, 6–10 January 2025. [CrossRef]
27. Tiwari, S.; Sarma, W.; Srivastava, A. Integrating artificial intelligence with zero trust architecture: Enhancing adaptive security in modern cyber threat landscape. *Int. J. Res. Anal. Rev.* **2022**, *9*, 712–728. Available online: https://www.researchgate.net/profile/Writuraj-Sarma/publication/388007597_Integrating_Artificial_Intelligence_with_Zero_Trust_Architecture_Enhancing_Adaptive_Security_in_Modern_Cyber_Threat_Landscape/links/6787497c2be36743a5d6b06b/Integrating-Artificial-Intelligence-with-Zero-Trust-Architecture-Enhancing-Adaptive-Security-in-Modern-Cyber-Threat-Landscape.pdf (accessed on 15 January 2025).
28. Valero, J.M.J.; Sánchez, P.M.S.; Pérez, M.G.; Celdrán, A.H.; Pérez, G.M. Trust-as-a-service: A reputation-enabled trust framework for 5g networks. *arXiv* **2022**, arXiv:2210.11501. [CrossRef]
29. Veeramachaneni, V. Integrating zero trust principles into iam for enhanced cloud security. *Recent Trends Cloud Comput. Web Eng.* **2025**, *7*, 78–92. [CrossRef]
30. Alnaim, A.K.; Alwakeel, A.M. Zero Trust Strategies for Cyber-Physical Systems in 6G Networks. *Mathematics* **2025**, *13*, 1108. [CrossRef]
31. Alnaim, A.K.; Alwakeel, A.M. Zero-Trust Mechanisms for Securing Distributed Edge and Fog Computing in 6G Networks. *Mathematics* **2025**, *13*, 1239. [CrossRef]
32. Alnaim, A.K. Securing 5G virtual networks: A critical analysis of SDN, NFV, and network slicing security. *Int. J. Inf. Secur.* **2024**, 1–21. [CrossRef]
33. Alnaim, A.K.; Alwakeel, A.M. Machine-learning-based IoT–edge computing healthcare solutions. *Electronics* **2023**, *12*, 1027. [CrossRef]
34. Alnaim, A.K.; Alwakeel, A.M.; Fernandez, E.B. Towards a security reference architecture for NFV. *Sensors* **2022**, *22*, 3750. [CrossRef]
35. Albarrak, K.M.; Sorour, S.E. Boosting Institutional Identity on X Using NLP and Sentiment Analysis: King Faisal University as a Case Study. *Mathematics* **2024**, *12*, 1806. [CrossRef]

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.