

Editorial

Special Issue on Photonic Jet: Science and Application

Zengbo Wang ^{1,*}, Boris Luk'yanchuk ² and Igor V. Minin ³ 

¹ School of Computer Science and Electronic Engineering, Bangor University, Bangor LL57 1UT, UK

² Faculty of Physics, Lomonosov Moscow State University, 119991 Moscow, Russia; lukiyanchuk@nanolab.phys.msu.ru

³ Nondestructive Testing School, Tomsk Polytechnic University, 36 Lenin Avenue, 634050 Tomsk, Russia; prof.minin@gmail.com

* Correspondence: z.wang@bangor.ac.uk

Photonic jets (PJs) are important mesoscale optical phenomena arising from electromagnetic waves interacting with dielectric particles with sizes around several to several tens wavelengths ($\sim 2\text{--}40\lambda$). It generates a narrow, high-intensity beam at the shadow-side of the 'particle lenses' made from microspheres, cylinders (fibers), cubes, disks and others, even including biological cells and spider silks. A PJ has the capability to focus light beyond the classical diffraction limit, thus permitting many possibilities and applications: for example, super-resolution imaging, nanosensing, detection, patterning, trapping, manipulation, waveguiding, signal amplification (e.g., Raman, photoluminescence and second-harmonic generation) and high-efficiency signal collection, among others.

The earliest studies on PJ effects were reported in 2000 by Luk'yanchuk and co-workers [1,2]. They theoretically analyzed optical resonance and near-field effects [1], and verified experimentally [2]. By using 500 nm silica particles and a 248 nm-wavelength laser source, they obtained 100 nm hillocks ($\sim \lambda/2.5$) on a silicon surface [2]. Related works were carried by several groups between 2000 and 2004 [3,4]. Not knowing these works, Chen et al. reported in 2004 a theoretical subwavelength focusing effect by microcylinders and coined the terminology 'photonic nanojet' (PNJ) [5], which has since been widely used. A simplified term, 'photonic jet' (PJ), was also used by researchers in the field since 2005 [6,7]. In 2014, Minin et al. showed that a photonic jet can be formed from a three-dimensional particle of an arbitrary shape if the mesoscale condition is met [8,9]. In the past two decades, the field of PJ has undergone rapid growth and developments, driven by new innovations and discoveries. Among them, the most notable developments include the following: white-light microsphere nanoscope (2011) [10], spider silk superlens and metamaterial solid immersion lens (2016) [11,12], the discovery of photonic hooks (2016) [7,13], THz super-resolution imaging (2017) [14], single-cell biomagnifier (2019) [15], Plano-Convex-Microsphere (PCM) superlens (2020) [16,17], lipid droplets microlenses (2021) [18], PJ-mediated optogenetics (2022) [19] and others. More information on the past, present and future of PJ technology can be found in refs. [7,9,20–22].

This Special Issue focuses on the most recent advances and trends in PJ research. A total of 10 papers were selected and published, including a review of the field (one paper) [23], photonic hooks (three papers) [24–26], the modulation of PJ beam (three papers) [27–29], super-resolution imaging (three papers) [25,30,31], and scanning nanopatterning (one paper) [32]. Photonic hooks, field modulation and super-resolution imaging are the main topics in this Special Issue, which reflect the current research focus and trends. We highlight the key contribution and merit of the selected papers below according to the topics.

- Review on PJ-based trapping, sensing, and imaging

Li et al. reviewed the current types of microsphere lenses for PJ applications and their principles and applications in optical nano trapping, signal enhancement and super-resolution imaging, with particular emphasis on biological cells and tissues [23]. They



Citation: Wang, Z.; Luk'yanchuk, B.; Minin, I.V. Special Issue on Photonic Jet: Science and Application.

Photonics **2022**, *9*, 540. <https://doi.org/10.3390/photonics9080540>

Received: 28 July 2022

Accepted: 28 July 2022

Published: 1 August 2022

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2022 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

envisage that in vivo nanomanipulation and biodetection will be the future trends. This review is an important addition to the existing literature on PJ technology, with refined focuses on trapping, sensing and imaging.

- Photonic hooks (PHs)

A PH is a new type of self-bending PJ beam, with a curvature that is less than the wavelength and differs from Airy-family beams [33]. Such structured beams were theoretically predicted in 2016 [7] and experimentally demonstrated in 2019 [34] based on dielectric Janus particles with broken symmetries in its geometry. Other methods for generating PH include asymmetric beam excitation and two material-composition particles, among others [22,33,35]. In the current issue, Tang et al. proposed a new method of using patchy microcylinders (i.e., partially metal-coated) for the generation of PHs [24] having in mind [35]. By rotating the patchy microcylinders, PHs with different curvatures were successfully demonstrated, and a bending angle of 28.4 degree and curved-line width of 0.36λ were reported. Based on this work, the authors extended their work to patchy microspheres and experimentally demonstrated, for the first time, the effect of PHs on super-resolution imaging [25]. They showed that PHs generated by patchy microspheres provide an effective oblique illumination of imaging objects, which leads to the considerable improvement of near-field imaging contrast, thus providing a new mean to optimize microsphere-based super-resolution techniques. On the other hand, Yue et al. demonstrated a new concept of using PHs for photonic switching [26,36]. When two-wavelengths beams, 1310 nm and 1550 nm, pass through a right-trapezoid dielectric Janus particle, they were separated and guided to different routes because of different bending strengths [26], thus permitting effective photonic switching on microscale through a simple dielectric particle. Potential applications in photonic integrated circuit are envisaged.

- Modulation of PJ beams

The ability to control and modulate PJ beams is essential for developing next-generation PJ devices and technologies. In principle, modulations can be achieved by various means, including tuning the particle's size, refractive index, surrounding medium, incident beam pupil and beam structure [37], the composition of particles (e.g., liquid crystals [38] and metamaterials [14,39]) and more. Here, Sergeeva et al. presented a new method for modulating PJs by using standing waves, which were achieved by positioning aluminum oxide hemispheres on top of a silicon substrate with a separation distance. The gap distance was chosen to match the phase conditions for constructive interference between incident and reflected beams [27] for effective modulation. The work offers a new pathway to design PJ-based integrated photonic devices. On the other hand, Lin et al. designed and manufactured a spider-silk-based metal-dielectric dome microlenses, which showed great performance in PJ modulations by using different metal casings [28]. When gold casing was used, the focusing intensity was maximized and increased by a factor of three due to the surface's plasmon resonance. This microlens could be used to scan a biological target for large-area imaging with a conventional microscope. In addition, Bouaziz et al. demonstrated another PJ modulation method based on fiber tip parameter tuning [29]. They showed that PJs were obtained when light is coupled in the guide's fundamental mode and when the base diameter of the microlens is close to the core's diameter and modulated by the sharpness of the tip. When the base diameter of the microlens is larger than the fiber core, the focus point tends to move away from the external surface of the fiber and has a larger width. The results of this study can be used as guidelines for the tailored fabrication of shaped optical-fiber tips according to the targeted application.

- Super-resolution imaging

Since the first demonstration of microsphere-assisted super-resolution imaging in 2011, the technology received wide attention and constant development by researchers across the world [21]. The field of development and roadmap has been systematically reviewed and summarized in refs. [20–22,40]. Note there are two types of particles super-

lenses used for super-resolution imaging in the literature: microsphere superlens [10] and metamaterial solid-immersion superlens [12], and both have different super-resolution imaging mechanisms. For microsphere superlens, the super-resolution mechanism is a combined contribution of several effects, including PJ focus, the excitation of super-resonance and whisper gallery modes, as well as substrate and partial and inclined illumination effects [21]. They lead to the conversion of high-frequency evanescent waves that contain near-field nanoscale information into propagating waves, which then reach the far-field and contribute to the formation of a magnified virtual image. Herein, by conducting rigorous electromagnetic simulations, Boudokha et al. provided new insight and evidence that microspheres are a natural collector and converter of evanescent waves to propagating waves using whisper gallery modes [30]. However, the evanescent-to-propagation-conversion (ETPC) efficiency can vary significantly (10^{-7} to 10^{-1}) depending on used microspheres. On the other hand, Dhama et al. designed and fabricated TiO_2 metamaterial superlens in full-sphere shape for the first time and compared its imaging performance with commonly used BaTiO_3 (BTG) microspheres under the same imaging settings [31]. Their results showed that the meta-superlens performs consistently better over the widely used BTG superlens in terms of imaging contrast, clarity, the field of view and resolution, which was further supported by theoretical simulation. In addition, as mentioned above, photonic hook (PH)-induced super contrast imaging was for the first time demonstrated by using a patchy microsphere [25] and asymmetric Janus particles [41]. These works will contribute to developments of more powerful, robust, and reliable super-resolution imaging systems, which have potential in revolutionizing the optical microscopy.

- Scanning nanopatterning

Alongside laser cleaning, surface nanopatterning are among the earliest applications of PJ effects. To fabricate arbitrary nanopatterns, various approaches such as angular beam scanning [42] and scanning Plano-convex-microsphere superlens [17] have been developed. Herein, Luo et. al. demonstrated a new laser-direct nanowriting system based on a combination of microsphere lens with an AFM cantilever and scanned over the sample's surface [31]. Using femtosecond laser sources, arbitrary silicon oxide nanopatterns with a feature size of 310 nm and height of 120 were directly fabricated in a single step. The proposed method shows the potential for the fabrication of multifunctional surfaces and silicon photonics and integrated chips.

We hope that this Special Issue will provide readers with a useful and timely update on the status and future trends of PJ research and mesotronics [7,20–22,33,43–47]. We thank all authors, reviewers and the *photonics* editorial team for their valuable contributions that brought this Special Issue to life.

Author Contributions: Paper writing: Z.W.; recommendations for invited papers and technical discussions about the content: Z.W., B.L. and I.V.M. All authors have read and agreed to the published version of the manuscript.

Funding: This research was funded by the Welsh European Funding Office (WEFO); European ERDF grants, grant number CPE 81400 and SPARCII c81133; UK Royal society (IEC\R2\202178 and IEC\NSFC\181378); Russian Science Foundation (no. 20-12-00389); Russian Foundation for Basic Research (no. 21-57-10001 and no. 20-02-00715); and the Tomsk Polytechnic University Development Program.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Luk'yanchuk, B.; Zheng, Y.W.; Lu, Y. Laser cleaning of solid surface: Optical resonance and near-field effects. *High-Power Laser Ablation III* **2000**, 4065, 576–587.
2. Lu, Y.F.; Zhang, L.; Song, W.D.; Zheng, Y.W.; Luk'yanchuk, B.S. Laser writing of a subwavelength structure on silicon (100) surfaces with particle-enhanced optical irradiation. *JETP Lett.* **2000**, 72, 457–459. [\[CrossRef\]](#)
3. Münzer, H.J.; Mosbacher, M.; Bertsch, M.; Zimmermann, J.; Leiderer, P.; Boneberg, J. Local field enhancement effects for nanostructuring of surfaces. *J. Microsc.* **2001**, 202, 129–135. [\[CrossRef\]](#) [\[PubMed\]](#)
4. Chaoui, N.; Solis, J.; Afonso, C.N.; Fourrier, T.; Muehlberger, T.; Schrems, G.; Mosbacher, M.; Bäuerle, D.; Bertsch, M.; Leiderer, P. A high-sensitivity in situ optical diagnostic technique for laser cleaning of transparent substrates. *Appl. Phys. A* **2003**, 76, 767–771. [\[CrossRef\]](#)
5. Chen, Z.; Taflove, A.; Backman, V. Photonic nanojet enhancement of backscattering of light by nanoparticles: A potential novel visible-light ultramicroscopy technique. *Opt. Express* **2004**, 12, 1214. [\[CrossRef\]](#)
6. Leclerc, S.; Takakura, Y.; Meyrueis, P. Properties of a three-dimensional photonic jet. *Opt. Lett.* **2005**, 30, 2641–2643. [\[CrossRef\]](#)
7. Minin, I.V.; Minin, O.V. *Diffraction Optics and Nanophotonics: Resolution Below the Diffraction Limit*; Springer: Cham, Switzerland, 2016.
8. Minin, I.V.; Minin, O.V. Photonics of Isolated Dielectric Particles of Arbitrary Three-Dimensional Shape—A New Direction in Optical Information Technologies. *Vestnic NSU* **2014**, 12, 4.
9. Minin, I.V.; Minin, O.V.; Geints, Y. Localized EM and photonic jets from non-spherical and non-symmetrical dielectric mesoscale objects: Brief review. *Ann. Phys.* **2015**, 527, 491. [\[CrossRef\]](#)
10. Wang, Z.B.; Guo, W.; Li, L.; Luk'yanchuk, B.; Khan, A.; Liu, Z.; Chen, Z.C.; Hong, M.H. Optical virtual imaging at 50 nm lateral resolution with a white-light nanoscope. *Nat. Commun.* **2011**, 2, 218. [\[CrossRef\]](#)
11. Monks, J.N.; Yan, B.; Hawkins, N.; Vollrath, F.; Wang, Z. Spider Silk: Mother Nature's Bio-Superlens. *Nano Lett.* **2016**, 16, 5842–5845. [\[CrossRef\]](#)
12. Fan, W.; Yan, B.; Wang, Z.; Wu, L. Three-dimensional all-dielectric metamaterial solid immersion lens for subwavelength imaging at visible frequencies. *Sci. Adv.* **2016**, 2, e1600901. [\[CrossRef\]](#)
13. Yue, L.Y.; Minin, O.V.; Wang, Z.B.; Monks, J.N.; Salin, A.S.; Minin, I.V. Photonic hook: A new curved light beam. *Opt. Lett.* **2018**, 43, 771–774. [\[CrossRef\]](#)
14. Minin, I.V.; Minin, O.V. Terahertz artificial dielectric cuboid lens on substrate for super-resolution images. *Opt. Quantum Electron.* **2017**, 49, 326. [\[CrossRef\]](#)
15. Li, Y.C.; Liu, X.S.; Li, B.J. Single-cell biomagnifier for optical nanoscopes and nanotweezers. *Light Sci. Appl.* **2019**, 8, 61. [\[CrossRef\]](#)
16. Yan, B.; Song, Y.; Yang, X.B.; Xiong, D.X.; Wang, Z.B. Unibody microscope objective tipped with a microsphere: Design, fabrication, and application in subwavelength imaging. *Appl. Opt.* **2020**, 59, 2641–2648. [\[CrossRef\]](#)
17. Yan, B.; Yue, L.Y.; Monks, J.N.; Yang, X.B.; Xiong, D.X.; Jiang, C.L.; Wang, Z.B. Superlensing plano-convex-microsphere (PCM) lens for direct laser nano-marking and beyond. *Opt. Lett.* **2020**, 45, 1168–1171. [\[CrossRef\]](#)
18. Chen, X.X.; Wu, T.L.; Gong, Z.Y.; Guo, J.H.; Liu, X.S.; Zhang, Y.; Li, Y.C.; Ferraro, P.; Li, B.J. Lipid droplets as endogenous intracellular microlenses. *Light Sci. Appl.* **2021**, 10, 242. [\[CrossRef\]](#)
19. Guo, J.H.; Wu, Y.; Gong, Z.Y.; Chen, X.X.; Cao, F.; Kala, S.; Qiu, Z.H.; Zhao, X.Y.; Chen, J.J.; He, D.M.; et al. Photonic Nanojet-Mediated Optogenetics. *Adv. Sci.* **2022**, 9, 2104140. [\[CrossRef\]](#)
20. Luk'yanchuk, B.S.; Paniagua-Domínguez, R.; Minin, I.V.; Minin, O.V.; Wang, Z. Refractive index less than two: Photonic nanojets yesterday, today and tomorrow. *Opt. Mater. Express* **2017**, 7, 1820–1847. [\[CrossRef\]](#)
21. Wang, Z.; Luk'yanchuk, B. Super-resolution imaging and microscopy by dielectric particle-lenses. In *Label-Free Super-Resolution Microscopy*; Astratov, V., Ed.; Springer: Cham, Switzerland, 2019.
22. Minin, I.V.; Liu, C.Y.; Geints, Y.E.; Minin, O.V. Recent Advances in Integrated Photonic Jet-Based Photonics. *Photonics* **2020**, 7, 41. [\[CrossRef\]](#)
23. Li, H.; Song, W.Y.; Zhao, Y.; Cao, Q.; Wen, A.H. Optical Trapping, Sensing, and Imaging by Photonic Nanojets. *Photonics* **2021**, 8, 434. [\[CrossRef\]](#)
24. Tang, F.; Shang, Q.Q.; Yang, S.L.; Wang, T.; Melinte, S.; Zuo, C.; Ye, R. Generation of Photonic Hooks from Patchy Microcylinders. *Photonics* **2021**, 8, 466. [\[CrossRef\]](#)
25. Qingqing, Q.Q.; Tang, F.; Yu, L.Y.; Oubaha, H.; Caina, D.; Yang, S.L.; Melinte, S.; Zuo, C.; Wang, Z.B.; Ye, R. Super-Resolution Imaging with Patchy Microspheres. *Photonics* **2021**, 8, 513.
26. Yue, L.Y.; Wang, Z.B.; Yan, B.; Xie, Y.; Geints, Y.E.; Minin, O.V.; Minin, I.V. Near-Field Light-Bending Photonic Switch: Physics of Switching Based on Three-Dimensional Poynting Vector Analysis. *Photonics* **2022**, 9, 154. [\[CrossRef\]](#)
27. Sergeeva, K.A.; Sergeev, A.A.; Minin, O.V.; Minin, I.V. A Closer Look at Photonic Nanojets in Reflection Mode: Control of Standing Wave Modulation. *Photonics* **2021**, 8, 54. [\[CrossRef\]](#)
28. Lin, C.B.; Lin, Y.H.; Chen, W.Y.; Liu, C.Y. Photonic Nanojet Modulation Achieved by a Spider-Silk-Based Metal-Dielectric Dome Microlens. *Photonics* **2021**, 8, 334. [\[CrossRef\]](#)
29. Bouaziz, D.; Chabrol, G.; Guessoum, A.; Demagh, N.E.; Leclerc, S. Photonic Jet-Shaped Optical Fiber Tips versus Lensed Fibers. *Photonics* **2021**, 8, 373. [\[CrossRef\]](#)

30. Boudoukha, R.; Perrin, S.; Demagh, A.; Montgomery, P.; Demagh, N.E.; Lecler, S. Near-to Far-Field Coupling of Evanescent Waves by Glass Microspheres. *Photonics* **2021**, *8*, 73. [[CrossRef](#)]
31. Dhama, R.; Yan, B.; Palego, C.; Wang, Z.B. Super-Resolution Imaging by Dielectric Superlenses: TiO₂ Metamaterial Superlens versus BaTiO₃ Superlens. *Photonics* **2021**, *8*, 222. [[CrossRef](#)]
32. Luo, H.; Yu, H.B.; Wen, Y.D.; Zheng, J.N.; Wang, X.D.; Liu, L.Q. Direct Writing of Silicon Oxide Nanopatterns Using Photonic Nanojets. *Photonics* **2021**, *8*, 152. [[CrossRef](#)]
33. Minin, O.V.; Minin, I.V. *The Photonic Hook: From Optics to Acoustics and Plasmonics*; Springer: Cham, Switzerland, 2021.
34. Minin, I.V.; Minin, O.V.; Katyba, G.M.; Chernomyrdin, N.V.; Kurlov, V.N.; Zaytsev, K.I.; Yue, L.; Wang, Z.; Christodoulides, D.N. Experimental observation of a photonic hook. *Appl. Phys. Lett.* **2019**, *114*, 031105. [[CrossRef](#)]
35. Minin, I.V.; Minin, O.V.; Liu, C.Y.; Wei, H.D.; Geints, Y.E.; Karabchevsky, A. Experiments demonstration of a tunable photonic hook by a partially illuminated dielectric microcylinder. *Opt. Lett.* **2020**, *45*, 4899–4902. [[CrossRef](#)]
36. Geints, Y.E.; Minin, O.V.; Yue, L.Y.; Minin, I.V. Wavelength-Scale Photonic Space Switch Proof-of-Concept Based on Photonic Hook Effect. *Ann. Phys.* **2021**, *533*, 2100192. [[CrossRef](#)]
37. Yue, L.Y.; Yan, B.; Monks, J.N.; Wang, Z.B.; Tung, N.T.; Lam, V.D.; Minin, O.V.; Minin, I.V. Production of photonic nanojets by using pupil-masked 3D dielectric cuboid. *J. Phys. D Appl. Phys.* **2017**, *50*, 175102. [[CrossRef](#)]
38. Eti, N.; Giden, I.H.; Hayran, Z.; Rezaei, B.; Kurt, H. Manipulation of photonic nanojet using liquid crystals for elliptical and circular core-shell variations. *J. Mod. Opt.* **2017**, *64*, 1566–1577. [[CrossRef](#)]
39. Yue, L.; Yan, B.; Wang, Z. Photonic nanojet of cylindrical metalens assembled by hexagonally arranged nanofibers for breaking the diffraction limit. *Opt. Lett.* **2016**, *41*, 1336–1339. [[CrossRef](#)]
40. Wang, Z.; Luk'yanchuk, B.; Wu, L. Roadmap for label-free imaging with microsphere superlens and metamaterial solid immersion lens. *arXiv* **2021**, arXiv:2108.09153.
41. Minin, O.V.; Minin, I.V. Terahertz microscopy with oblique subwavelength illumination in near field. *Quant. Electron.* **2022**, *52*, 13–16. [[CrossRef](#)]
42. Guo, W.; Wang, Z.B.; Li, L.; Whitehead, D.J.; Luk'yanchuk, B.S.; Liu, Z. Near-field laser parallel nanofabrication of arbitrary-shaped patterns. *Appl. Phys. Lett.* **2007**, *90*, 243101. [[CrossRef](#)]
43. Minin, I.V.; Minin, O.V.; Cao, Y.; Yan, B.; Wang, Z.; Luk'yanchuk, B. Photonic lenses with whispering gallery waves at Janus particles. *Opto-Electron. Sci.* **2022**, *1*, 21008. [[CrossRef](#)]
44. Zhang, P.C.; Yan, B.; Gu, G.Q.; Yu, Z.T.; Chen, X.; Wang, Z.B.; Yang, H. Localized photonic nanojet based sensing platform for highly efficient signal amplification and quantitative biosensing. *Sens. Actuators B-Chem.* **2022**, *357*, 131401. [[CrossRef](#)]
45. Luk'yanchuk, B.; Bekirov, A.R.; Wang, Z.B.; Minin, I.V.; Minin, O.V.; Fedyanin, A.A. Optical phenomena in dielectric spheres several light wavelengths in size: A review. *Phys. Wave Phenom.* **2022**, *30*, 217–241.
46. Minin, O.V.; Minin, I.V. Optical Phenomena in Mesoscale Dielectric Particles. *Photonics* **2021**, *8*, 591. [[CrossRef](#)]
47. Minin, I.V.; Minin, O.V.; Luk'yanchuk, B.S. Mesotronic era of dielectric photonics. *Mesophotonics Phys. Syst. Mesoscale* **2022**, *12152*, 89–93.