

System of Material and Construction Parameters for a Reliable Simulation of Textile Surfaces in the Clothing Industry [†]

Ulrike Reinhardt * and Thomas Schneider

Faculty of Clothing Technology and Garment Engineering, Berlin School of Culture + Design, University of Applied Sciences—HTW Berlin, 12459 Berlin, Germany; thomas.schneider@htw-berlin.de

* Correspondence: ulrike.reinhardt@htw-berlin.de

[†] Presented at the 2nd International Electronic Conference on Processes: Process Engineering—Current State and Future Trends (ECP 2023), 17–31 May 2023. Available online: <https://ecp2023.sciforum.net/>.

Abstract: Garment simulation enables the reduction of physical prototypes, saving time, material and costs. Complete elimination of physical prototypes is not yet possible because simulation is not reliable enough for a robust fit analysis. In addition, predictions of the textile-physical behaviour of virtually available materials would be useful. A new approach is being developed to represent the material and construction properties of textile surfaces, their correlations and their influence on the simulation. Based on the material parameters, conditions for a reliable simulation and prediction of the material behaviour can be derived. This paper first focuses on the distinction between the material properties of the fibres and the construction properties of the yarn and surface.

Keywords: 3D simulation; virtual prototype; fit analysis; quality assurance; material parameters; material and construction properties

1. Introduction

In the clothing and textile industry, the goal of research and development is to create continuous digital process chains from product conception to production and quality control [1]. In particular, virtual product development, and thus the 3D simulation of textile surfaces and clothing products, plays a central role.

The implementation of 3D simulations in product development processes means minimizing costs and time, savings resources and optimizing communication between customers, suppliers and producers [2,3]. Accordingly, 3D simulation opens up economic potentials in terms of sustainability and resource efficiency and means added value for companies and end users. This essentially corresponds to the concept of Industry 4.0, which is characterised by

- Product individualization;
- Flexible and efficient production down to batch size 1;
- The involvement of customers and business partners in the value creation processes;
- The combination of production and high-quality services [4].

In the current product development cycle, simulation is primarily used to generate idealised and promotional representations. For fit analysis, an initial assessment can be made of the silhouette, proportions and design in terms of colours and surface texture. This allows the reduction of physical prototypes. The complete elimination of physical prototypes, as required by the end-to-end digital product development process mentioned above, requires reliable virtual fit analysis and optimisation. However, this is not possible if the simulation does not realistically enough represent the material behaviour.

Surveys have regularly confirmed that the fit of clothing is the most important purchase criterion for customers [5–8]. Therefore, virtual fit analysis and optimisation must be



Citation: Reinhardt, U.; Schneider, T. System of Material and Construction Parameters for a Reliable Simulation of Textile Surfaces in the Clothing Industry. *Eng. Proc.* **2023**, *37*, 69. <https://doi.org/10.3390/ECP2023-14632>

Academic Editor: Evangelos Tsotsas

Published: 17 May 2023



Copyright: © 2023 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

considered when implementing a consistent digital product development process. Predictions regarding the behaviour of materials that do not yet physically exist should also be targeted. In both cases, in addition to a realistic representation of the material behaviour, the numerical description of the material behaviour is essential. In the authors' opinion, this can only be achieved by optimising the integration of the material parameters of the textile surface into the simulation algorithms.

This paper gives an insight into the research field of the new approach for the determination of simulation-related textile-physical material parameters.

2. State of the Art

Software for the 3D simulation of clothing that are used in practice can be divided into two categories [3,9]:

1. Construction of garments on the avatar and subsequent unwinding of the shape into the plane (3D to 2D);
2. 2D construction of a cut, which is then virtually sewn and placed around the avatar (2D to 3D).
3. The first principle is very well suited for the implementation of products that are close to the body, such as clothing in the sports and medical sectors, but also in the automotive industry. The second principle has gained acceptance for clothing, as it can be used to visualise both close-to-body and far-from-body clothing. It has been implemented in numerous programmes over the years.
4. Normally, research focuses on questions of the reliability of the simulation and the correlation of the virtual representation of the simulation with reality.
5. According to Morlock et al. [10], three steps are defined for a reliable simulation:
6. the digitally available 2D sectional construction;
7. the avatar, which reflects the human body in terms of its dimensions and proportions;
8. the material parameters that describe the surface appearance and the deformation behaviour of the textile.
9. This project exclusively focuses on the textile-physical deformation behaviour of the material. It will therefore be discussed in more detail below:
10. The deformation behaviour of textile surfaces can be divided into two application cases [11]. While the simulation of technical textiles mainly considers drapability, i.e., the textile-physical behaviour under forced deformation, the behaviour under free deformation under the effect of gravity is decisive in the simulation of clothing. Therefore, different modelling models can be used for both applications. In the case of technical textiles, which are used, for example, for fibre composites, the simulation is mainly carried out with the help of FEM models [12]. This method is relatively computationally and time consuming [13]. For clothing, on the other hand, the so-called particle model is used, which allows simulations to be carried out in real time, taking into account the relatively short development cycles in the clothing industry. Among other things, the complex processes of wrinkle formation and the collisions of different surface levels are realised in a balanced relationship between computing time and computer capacity [13].
11. The work of Pierce, Cusick and Kawabata is particularly noteworthy in the study of clothing simulation and its fundamentals. Pierce laid the foundations for textile material simulation in the 1930s, when he studied the relationship between stiffness and weight and the drapability of textile surfaces. Cusick followed in the 1960s with his investigation of the influence of shear stiffness and bending length on the drape coefficient and developed the method still used today to determine the textile drop [14]. Kawabata and Niwa developed a system for objective handle identification and associated measuring systems and devices, thus making a considerable contribution to the objectification of subjectively perceived textile properties. This makes correlative comparisons with mechanical properties possible. In turn, it is thus possible to draw conclusions from the mechanical properties to the subjectively perceived, haptic

properties of the material [11]. This is particularly important because materials cannot be haptically assessed as long as they are only digitally depicted. This is a major challenge for product developers when dealing with simulated clothing, as they have to learn to evaluate a textile material based on its digital representation and parameters.

12. As already mentioned, the main objective of the research work mentioned above, as well as others, was to objectively and numerically describe the fall behaviour of textiles. Thus, they are considered the cornerstone for the simulation of textile surfaces. On this basis, Breen, House and Wozny developed the particle-based model for the simulation of textile surfaces [15] in 1994, which for the reasons described above, is most suitable for the simulation of clothing. In addition, alternative approaches to simulation algorithms, especially for technical textiles, have been presented [16–20].

3. Problems and Objectives

3.1. Textiles vs. Compact Materials

Compact materials, such as steel, are mechanically resistant to bending and are characterised by a continuum-mechanically coherent structure the bonding ratios of which can be defined at the atomic-molecular level. As compact materials, they predominantly exhibit linear-elastic deformation behaviour, which can be derived from the physical properties of the material or in conjunction with the workpiece geometry and described by means of material constants.

Textile materials, however, are not compact materials, but represent complex, anisotropic and flexible structures made of individual elements. They are composed of fibres or filaments that are joined together during processing, first to form yarns and then to form surfaces. Within these structures, the fibres come into contact with each other and are exposed to frictional forces under load. In order to describe the deformation behaviour of textile surfaces, it is necessary to take into account the material or fibre properties, the construction properties of the yarns and the surfaces, and the textile-physical properties of the textile surface. Furthermore, it should also be noted that textiles hardly exhibit linear-elastic deformation behaviour, which means that no material constants are available and can be used to describe the deformation behaviour.

3.2. Challenges in the Application of the Simulation Programmes

The commercially available clothing simulation programmes for different material parameters in relation to the surface to be simulated. Common to all programmes is the query for thickness, weight, elongation and bending stiffness. For the latter two properties, loads in the warp, weft and diagonal directions are considered in order to account for the anisotropic material behaviour of textile surfaces. It can be concluded that these material parameters play a significant role in the simulation algorithms, but the value of each individual parameter in relation to the simulation remains open and undefined. Therefore, it is not clear which parameters are included in the simulation calculations and with which share. Similarly, the way in which parameters are integrated into the simulation algorithms can only be guessed at. Unfortunately, there is limited information available on this, as software manufacturers are reluctant to disclose the underlying algorithms. Furthermore, no evaluation of the various simulation programmes is possible, even with regard to the quality assurance of textile products, which considerably limits the use of the software in quality assurance.

Studies show that different programs deliver different simulation results even when the framework conditions (2D section, avatar, material parameters) are identical [3,21–23]. On the other hand, very similar simulation results can be obtained despite the implementation of different material parameters [3]. The comparison of the physical with the virtual fitting shows that the simulation quality for a reliable fit analysis and optimisation is still insufficient, especially if physical prototypes are to be largely eliminated in the future or completely omitted for economic reasons. Significant discrepancies exist between the

physical and the simulated drape tests. These results lead to the conclusion that the physical material parameters are not sufficiently well implemented in the calculation algorithms. In particular, the anisotropy of the material appears not to be taken into account in the calculations, despite the fact that the bending stiffness and the elongation in the warp, weft and diagonal directions have been entered. So far, it is therefore not recognisable according to which criteria material parameters are selected and taken into account in the programmes.

It can be concluded from this that there is still a considerable need for basic research with regard to the simulation-relevant material parameters. From the authors' point of view, future work must concentrate on the definition and determination of simulation-relevant material parameters and the optimization of the calculation algorithms.

3.3. Objectives

Therefore, a new approach to describe the deformation behaviour of textile surfaces in the context of clothing simulation is being developed. This involves investigating the correlations between the fibre, yarn and surface properties. The aim is to clearly distinguish between fibre and construction properties. Initially, only the textile case is considered for deformation behaviour; i.e., the free deformation due to the effect of gravity. By comparing the relative properties of the fibre, yarn and surface, it is possible to show the property changes over the process stages and to represent the values of properties in terms of their influence on the simulation.

4. Methodology and Implementation

Previous research has mainly focused on the influence of yarn and surface properties on the textile case. From the authors' point of view, the material properties have not been sufficiently considered thus far. In the current project, the importance of the material properties for the simulation is investigated. At the same time, the connection between the material properties and the yarn and surface properties is considered. Therefore, the investigation of the textile case as a function of the fibre, yarn and surface properties is carried out by means of tests on the deformation behaviour of the material and corresponding correlation calculations. From the results, reasonable approaches for simulation optimisation can be derived.

The following considerations are decisive for the selection of the material to be investigated:

- the parameters influencing the investigation should be kept as manageable as possible;
- the fibre material used should show as little plastic deformation behaviour as possible;
- The constructions of yarns and surfaces should correspond to the respective basic constructions; i.e., single yarns and basic weaves.

Therefore, a surface made of untreated cotton was selected as the model material. The yarns used on the surface are single yarns in z-twist. The construction of the surface is characterised by a simple plain weave, the yarn systems of which have identical yarn constructions and have been processed with approximately the same yarn density.

The selected surface has been tested for material and construction properties according to relevant standards. The subsequent comparison between fibre, yarn and surface properties includes correlation calculations and graphical evaluations.

5. Conclusions and Outlook

Initial results allow conclusions to be drawn regarding the value of material and construction properties in relation to deformation behaviour.

The investigation for one model material will be extended to other materials in order to test the transferability to other textile surfaces.

Furthermore, the results of the work will allow conclusions to be drawn for the modelling of forced deformation behaviour. This is necessary for the simulation of clothing, taking into account the human movement process, and for the simulation of technical textiles.

This work will contribute to the further objectification of fit analysis and optimisation using garment simulation. This will make it possible to streamline product development processes in the apparel industry. In addition to the abovementioned resource savings, an exclusively digital product development without physical prototypes will make it possible to involve the customer in the product development process at an early stage, and thus meet the growing trend of product individualisation. Not only are design wishes taken into account, but the fit is also analysed and individually adapted to the customer's wishes. As a result, returns are avoided and the current aspect of sustainability in terms of resource efficiency and avoidance of overproduction is met. This creates an essential prerequisite for incorporating the simulation of textile structures into quality management systems and opening up quality assurance as part of a quality system for garment-specific concerns as well.

Author Contributions: U.R.: conceptualization, methodology, validation, formal analysis, investigation, writing—original draft preparation, writing—review and editing; T.S.: writing—review and editing, supervision. All authors have read and agreed to the published version of the manuscript.

Funding: This research received no external funding.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Not applicable.

Acknowledgments: Many thanks to the Textilforschungsinstitut Thüringen-Vogtland e.V. in Greiz, Germany, for their support in material testing and to the company Cotonea | Gebr. Elmer & Zweifel GmbH & Co. KG for providing the textile material.

Conflicts of Interest: The authors declare no conflict of interest.

References

1. Krzywinski, S. Digital process chain—From the product idea to production (keynote lecture). In Proceedings of the Digital Fashion Innovation (DFI) e-Symposium, Online, 28–30 September 2020.
2. Porterfield, A.; Lamar, T. Examining the effectiveness of virtual fitting with 3D garment simulation. *Int. J. Fash. Des. Technol. Educ.* **2017**, *10*, 320–330. [CrossRef]
3. Sayem, A.S.M. Virtual Fashion ID: A reality check. In *IFFTI Conference*; Manchester Fashion Institute: Manchester, UK, 2019.
4. Roth, A. Industrie 4.0—Hype oder Revolution? In *Einführung und Umsetzung von Industrie 4.0. Grundlagen, Vorgehensmodell und Use Cases aus der Praxis*; Roth, A., Ed.; Springer: Berlin/Heidelberg, Germany, 2016; pp. 1–15.
5. GermanFashion Modeverband. Welche der Folgenden Kriterien Sind Ihnen Persönlich bei der Auswahl Ihrer Bekleidung wichtig? 2022. Available online: <https://de.statista.com/statistik/daten/studie/1183356/umfrage/umfrage-auswahlkriterien-beim-modekonsum-corona-pandemie/> (accessed on 30 March 2023).
6. Statista. How Important is the Fit When you Choose Clothes for Yourself? 2017. Available online: <https://www.statista.com/forecasts/761150/importance-of-fit-to-us-consumers-when-choosing-clothes> (accessed on 30 March 2023).
7. Spiegel. Wie Wichtig ist Ihnen, Wenn Sie Kleidung Kaufen, Eine Gute Passform? In Statista. 2015. Available online: <https://de.statista.com/statistik/daten/studie/437466/umfrage/umfrage-zur-wichtigkeit-einer-guten-passform-als-kaufkriterium-fuer-kleidung/> (accessed on 30 March 2023).
8. Statista. Wie Wichtig ist Ihnen die Passform, Wenn Sie Kleidung für Sich Persönlich Aussuchen? In Statista. 2017. Available online: <https://de.statista.com/prognosen/781984/umfrage-zur-passform-als-auswahlkriterium-fuer-kleidung/> (accessed on 30 March 2023).
9. Sayem, A.S.M.; Kennon, R.; Clarke, N. 3D CAD systems for the clothing industry. *Int. J. Fash. Des. Technol. Educ.* **2010**, *3*, 45–53. [CrossRef]
10. Morlock, S.; Pirch, C.; Klepser, A.; Keinath, J. The Transformation of Fit Pattern with 3D towards the Future. In Proceedings of the Digital Fashion Innovation (DFI) e-Symposium, Online, 28–30 September 2020. Available online: <https://fashioninstitute.mmu.ac.uk/assets/uploads/2020/10/DFI2020-Book-of-Abstracts.pdf> (accessed on 30 March 2023).
11. Krzywinski, S.; Finnimore, E. Komplexe Prüfung von textilem Verhalten und Qualität. In *Prüfverfahren in der Textil- und Bekleidungstechnik*; Reumann, R.-D., Ed.; Springer: Berlin/Heidelberg, Germany, 2000; pp. 605–636.
12. Girdauskaite, L.; Haasemann, G.; Krzywinski, S. Modellierung und Simulation. In *Textile Werkstoffe für den Leichtbau. Techniken—Verfahren—Materialien—Eigenschaften*; Cherif, C., Ed.; Springer: Berlin/Heidelberg, Germany, 2011; pp. 573–636.
13. Volino, P.; Magnenat-Thalmann, N. Simulation Models. In *Virtual Clothing. Theory and Practice*; Springer: Berlin/Heidelberg, Germany, 2000; pp. 11–101.

14. Cusick, G. 46—The Dependence of Fabric Drape on Bending and Shear Stiffness. *J. Text. Inst. Trans.* **1965**, *56*, T596–T606. [[CrossRef](#)]
15. Breen, D.E.; House, D.H.; Wozny, M.J. A Particle-Based Model for Simulating the Draping Behavior of Woven Cloth. *Text. Res. J.* **1994**, *64*, 663–685. [[CrossRef](#)]
16. Orlik, J.; Pietsch, K.; Fassbender, A.; Sivak, O.; Steiner, K. Simulation and Experimental Validation of Spacer Fabrics Based on their Structure and Yarn's Properties. *Appl. Compos. Mater.* **2018**, *25*, 709–724. [[CrossRef](#)]
17. Orlik, J.; Panasenko, G.; Stavre, R. Asymptotic analysis of a viscous fluid layer separated by a thin stiff stratified elastic plate. *Appl. Anal.* **2019**, *100*, 589–629. [[CrossRef](#)]
18. Cirio, G.; Lopez-Moreno, J.; Otaduy, M.A. Efficient simulation of knitted cloth using persistent contacts. In Proceedings of the 14th ACM SIGGRAPH/Eurographics Symposium on Computer Animation; Barbič, J., Deng, Z., Eds.; ACM: New York, NY, USA, 2015; pp. 55–61.
19. Bai, R.; Chen, B.; Colmars, J.; Boisse, P. Physics-based evaluation of the drapability of textile composite reinforcements. *Compos. Part B Eng.* **2022**, *242*, 110089. [[CrossRef](#)]
20. Kaddaha, M.A.; Younes, R.; Lafon, P. New Geometrical Modelling for 2D Fabric and 2.5D Interlock Composites. *Textiles* **2022**, *2*, 142–161. [[CrossRef](#)]
21. Power, J. Fabric objective measurements for commercial 3D virtual garment simulation. *Int. J. Cloth. Sci. Technol.* **2013**, *25*, 423–439. [[CrossRef](#)]
22. Lee, H.W. Development of Sustainable Creative Three-Dimensional Virtual Woven Textiles Using Clothing Waste. *Sustainability* **2023**, *15*, 2263. [[CrossRef](#)]
23. Lim, H.; Istook, C. Drape simulation of three-dimensional virtual garment enabling fabric properties. *Fibers Polym.* **2011**, *12*, 1077–1082. [[CrossRef](#)]

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.