

Abstract

Piezoelectric Ultrasonic Micromotor [†]

Giorgio Casiraghi ¹, Daniele Caltabiano ², Andrea Picco ³ and Stefano Mariani ^{1,*}

¹ Politecnico di Milano, Department of Civil and Environmental Engineering, 20133 Milano, Italy; giorgio2.casiraghi@mail.polimi.it

² STMicroelectronics, SRA Advanced Sensors and Smart Controls Group, 20864 Agrate Brianza, Italy; daniele.caltabiano@st.com

³ STMicroelectronics, MEMS Technology Development Group, 20864 Agrate Brianza, Italy; Andrea.PICCO@st.com

* Correspondence: stefano.mariani@polimi.it

[†] Presented at the 1st International Conference on Micromachines and Applications, 15–30 April 2021; Available online: <https://micromachines2021.sciforum.net/>.

Abstract: Ultrasonic motors are characterized by low speed and high-torque operation, without the need for gear trains. They can be compact and lightweight, and they can also work in the absence of applied loads, due to the frictional coupling between the rotor and the stator induced by the traveling wave. In this work, we discuss a concept design based on thin piezoelectric films, sol-gel directly deposited onto a silicon substrate to provide high-torque motors compatible with wafer integration technologies. Due to the large dielectric constants and the enhanced breakdown strengths of thin piezoelectric films, such ultrasonic micromotors can lead to meaningful improvements over electrostatic ones in terms of energy density. As far as the fabrication of the micromotor at the mm-scale is concerned, an integrated approach is proposed with significant improvements regarding: the comb-tooth structure, to maximize/optimize the motor torque; a back and front etch lithographic process; and the design of the electrodes, which provide the electric signal at the central anchor of the stator, taking advantage of low-temperature soldering. The proposed design has been assessed through multiphysics simulations, carried out to evaluate the resonant behavior of the stator and the motor performance in terms of angular velocity, torque, and output power, and it is shown to lead to promising results.

Keywords: micro electro-mechanical systems; ultrasonic micromotor; piezoelectric micromotor; multiphysics; finite element simulations

Citation: Casiraghi, G.; Caltabiano, D.; Picco, A.; Mariani, S. Piezoelectric Ultrasonic Micromotor. *Eng. Proc.* **2021**, *4*, 24. <https://doi.org/10.3390/Micromachines2021-09560>

Academic Editor: Ion Stiharu

Published: 14 April 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).

Supplementary Materials: The supplementary file is available at <https://www.mdpi.com/article/10.3390/Micromachines2021-09560/s1>.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: Data sharing not applicable.