encyclopedia

Entry

Human Factors in Aviation Safety

Efstratios Psomas

Department of Social Sciences & Psychology, Varna Free University "Chernorizets Hrabar", 9007 Varna, Bulgaria; efstratios.psomas@vfu.bg

Definition

Human factors in aviation comprise the cognitive, physiological, interpersonal, organizational, and cultural conditions that shape how people interact with aircraft, technology, procedures, other personnel, and the operational environment. In safety-critical flight operations, these factors influence whether information is detected and understood, whether decisions are timely and appropriate, whether workload and fatigue remain manageable, and whether crews communicate and coordinate effectively. Situation awareness, decision-making, fatigue, occupational stress, Crew Resource Management (CRM), leadership, safety voice, and safety culture are therefore interdependent rather than isolated topics. Contemporary human-factors practice treats aviation safety as a socio-technical outcome: safe performance emerges from the interaction between individual cognition, team processes, organizational systems, and operational constraints. Human-factors interventions consequently aim not to eliminate human variability, but to design systems, training, procedures, and cultures that anticipate error, support adaptive performance, and prevent threats from developing into accidents.

Keywords: aviation human factors; aviation psychology; decision-making; situation awareness; fatigue; Crew Resource Management; safety culture; safety voice; aviation safety

1. Introduction

Aviation is a high-reliability domain in which technical systems, standardized procedures, professional competence, and organizational controls are designed to make serious failure uncommon. Nevertheless, operational safety still depends on human performance in environments characterized by time pressure, uncertainty, automation, changing weather, complex traffic, interruptions, and the need to coordinate across multiple professional groups. Human factors provide the conceptual and applied framework for understanding this interaction. Its central question is not simply why an individual makes an error, but how cognition, physiology, teamwork, technology, procedures, leadership, and organizational context combine to shape performance.

Three domains provide a useful organizing structure for the aviation literature: cognitive performance and decision-making; fatigue and stress; and Crew Resource Management (CRM) together /with safety culture. These domains are tightly connected. Situation awareness supplies the cognitive representation on which decisions depend; fatigue and workload can degrade the attention and memory needed to maintain that representation; and CRM determines whether distributed information held by different crew members is communicated, challenged, integrated, and acted upon. Organizational culture influences

Academic Editor: José Aparecido Da Silva

Received: 15 September 2026
Revised: 23 November 2026
Accepted: 27 November 2026
Published: 28 November 2026

Copyright: © 2026 by the author. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license.

all three by shaping staffing, scheduling, training, reporting, authority gradients, and the practical meaning attached to safety.

This entry synthesizes these linked domains with particular attention to flight-deck and flight-operations evidence. Although human factors also encompass air traffic control, maintenance, cabin services, airport ground handling, and design/certification, these domains are not reviewed comprehensively here. The title denotes the broader safety context, whereas the analytical examples and application focus on flight operations. The Korean Air Flight 801 investigation is used as a bounded application of a proposed analytical framework rather than as empirical validation of that framework.

The contemporary perspective is therefore systemic. Human error is treated as a phenomenon to be anticipated and managed within a socio-technical system rather than as an adequate endpoint for accident explanation. This perspective supports interventions that combine interface design, evidence-informed training, fatigue risk management, nontechnical skills, leadership, reporting systems, and organizational learning. It also extends earlier integrative work linking industrial-organizational psychology with aviation human factors and human performance [1].

Review Approach and Contribution

This entry uses a narrative, thematically organized synthesis of foundational human-factors theory, selected aviation empirical studies and reviews, accident-investigation evidence, and regulatory or professional guidance. Sources were selected for their direct relevance to the interacting domains of cognition, fatigue, teamwork, automation, and organizational safety, rather than through a prospectively registered or reproducible systematic-search protocol. The manuscript therefore does not claim exhaustive retrieval, formal risk-of-bias scoring, or meta-analytic comparability. Foundational conceptual works are used to explain mechanisms; empirical studies to illustrate observed associations; official investigation reports to establish event-specific findings; and regulatory materials to describe recommended or required practices. The selection is vulnerable to publication and author-selection bias, and findings from distinct tasks, populations, and methods are not treated as interchangeable. The contribution is a transparent, proposed cross-level analytical framework and an evidence-bounded case mapping, not a newly validated causal or predictive model.

Evidence appraisal within this narrative synthesis is therefore claim-specific rather than a formal grading exercise. Official accident reports provide comparatively strong documentation of investigated event sequences and identified contributing factors, but they do not establish the general frequency of a mechanism across aviation. Controlled simulation studies offer stronger control of task conditions and can test performance mechanisms, although transfer to routine line operations remains uncertain. Observational and survey studies may capture operational context and perceived culture, but associations can reflect self-report bias, selection effects, and confounding. Conceptual models and regulatory guidance help organize explanation or prescribe practice; neither alone constitutes empirical proof that an intervention prevents accidents. Accordingly, the entry treats convergent findings across independent methods more confidently than isolated, context-dependent associations, without assigning numerical evidence grades unsupported by a systematic appraisal.

Several apparent tensions in the literature concern different outcomes rather than direct contradictions. For example, CRM studies can report improvements in knowledge, attitudes, or observed training behaviors without demonstrating corresponding reductions in rare safety events; those endpoints should not be equated [2]. Automation can reduce demands for routine manual control while increasing supervisory monitoring and mode-awareness requirements under abnormal conditions [3–5]. Similarly, individual

fatigue or workload measures cannot by themselves establish a causal explanation for an accident, even where an official investigation identifies fatigue as a contributing factor [6,7]. These differences in research design, context, and outcome measurement qualify broad claims about the effectiveness of human-factors interventions.

Table 1 summarizes the principal domains reviewed in this entry and makes explicit how each mechanism connects to operational risk and representative safety countermeasures.

Table 1. Integrated human-factors domains, mechanisms, operational risks, and safety countermeasures.

Domain	Principal Mechanism	Operational Risk	Safety Countermeasure	Key Sources
Situation awareness	Perception, comprehension, and projection of system state	Missed cues; incorrect mental model; delayed response	Goal-relevant displays; cross-checking; shared situation awareness; explicit updates	[8–10]
Decision-making	Integration of evidence, experience, uncertainty, and time pressure	Premature closure; plan continuation; delayed or inappropriate action	Decision gates; verbalized assumptions; challenge; predefined change-of-plan criteria	[11–13]
Fatigue and stress	Reduced alertness, vigilance, working memory, and cognitive flexibility	Slower reactions; attention lapses; impaired monitoring and judgment	Scientific scheduling; fatigue reporting; FRMS; recovery opportunities	[14–16]
CRM/TEM	Use of team, information, procedures, and error countermeasures	Unmanaged threats; trapped information; coordination breakdown	Briefing; monitoring; workload distribution; error trapping and mitigation	[2,17–20]
Safety voice and listening	Transmission and reception of safety-critical concerns across authority gradients	Warnings ignored, softened, or not converted into action	Assertive challenge; active safety listening; closed-loop response	[21,22]
Safety culture/SMS	Organizational priorities, reporting norms, learning, and resource decisions	Normalization of risk; underreporting; production pressure overriding safety	Just and learning-oriented reporting; safety data integration; leadership reinforcement	[23–25]
Human-automation interaction	Allocation of monitoring, analysis, decision, and control functions	Mode confusion; automation surprise; out-of-the-loop performance	Mode transparency; appropriate automation allocation; recurrent manual/abnormal practice	[3–5]

Note: CRM = Crew Resource Management; TEM = Threat and Error Management; FRMS = Fatigue Risk Management System; SMS = Safety Management System.

2. Cognitive Performance and Decision-Making

Naturalistic decision-making research describes how experienced operators recognize familiar patterns and mentally simulate plausible actions under time pressure; Klein's recognition-primed decision model complements, rather than replaces, analytical decision procedures [26]. This distinction matters because recognition can accelerate a response but can also be misleading when an event departs from familiar patterns.

Decision-making in aviation is rarely a detached choice between clearly defined alternatives. Pilots and other operational personnel often decide whether information is incomplete, dynamic, and distributed across displays, radio communications, procedures, other crew members, and memory. The quality of a decision therefore depends on what information enters attention, how it is interpreted, what future states are anticipated, and how rapidly the individual or team can update an initial plan when conditions change.

Situation awareness is one of the most influential constructs for explaining this process. Endsley conceptualized situation awareness as the perception of relevant elements in the environment, comprehension of their meaning, and projection of their likely future status [8,9]. This formulation is important because it distinguishes awareness from simple data acquisition. A pilot may visually register altitude, weather, traffic, and system

indications yet still fail to integrate them into an accurate understanding of the operational situation. The safety problem is therefore not merely whether information is available, but whether the system supports correct comprehension and anticipation.

Aviation decision-making also reflects the interaction between expertise and cognitive style. Recent simulation research with commercial pilots found that cognitive reflection, flight time, and task-related performance measures predicted decision-making performance, with the overall model explaining a substantial proportion of variance [11]. Such findings caution against treating experience as a complete proxy for decision quality. Experience can support pattern recognition and efficient problem solving, but its benefits depend on how information is processed and on whether the operator can reconsider an initially compelling response.

Individual differences may also influence decision latency under emergency conditions. Flight-simulation and neurocognitive evidence published in 2026 reported that sensory processing sensitivity predicted longer pilot decision time through indecisiveness [12]. As an individual study, this finding should be interpreted as preliminary rather than as evidence of a generalizable trait-based risk. The operational implication is not that a particular personality characteristic is inherently unsafe. Rather, training and system design should recognize that pilots can differ in how quickly they integrate competing cues under stress. Scenario-based training can help personnel identify personal decision tendencies while rehearsing structured strategies for time-critical situations.

2.1. Situation Awareness as a Cognitive Substrate

Situation awareness is continuously constructed and revised. It can be disrupted by attentional tunneling, interruption, high workload, expectation bias, ambiguous automation states, weak cross-checking, or a mismatch between information presentation and operational goals. Human–machine interface design is consequently part of the decision-making system. Displays that require excessive mental integration can increase cognitive burden, whereas goal-relevant presentation can support comprehension and projection [8,10].

The concept is also inherently distributed. In multi-crew operations, no single individual necessarily holds all relevant information. One pilot may be focused on aircraft control while another manages communications, navigation, checklists, or system diagnosis. Cabin crew, dispatchers, air traffic controllers, engineers, and ground personnel may each possess information relevant to the evolving risk picture. Shared situation awareness therefore depends on communication and coordination. This is one reason why cognitive performance cannot be separated cleanly from CRM [8,9,18].

Loss of situation awareness should not be interpreted as a purely internal mental failure. It can arise from poorly designed interfaces, confusing procedures, interruptions, inadequate briefings, automation surprises, or organizational practices that normalize excessive workload. A systems approach asks what information the operator reasonably needed, how that information was presented, what competing demands existed, and what barriers prevented detection or comprehension [3,8,27].

2.2. Workload, Stress, and Decision Quality

Wickens◎multiple-resource theory predicts that interference depends not only on total task demand but also on whether concurrent tasks draw on overlapping perceptual, cognitive, and response resources [28]. Underload and abrupt transitions from automated monitoring to active control also require consideration of vigilance and out-of-the-loop effects [3,4].

Workload describes the relationship between task demands and the resources available to meet them. Both overload and underload can create risk. Excessive workload may

narrow attention, reduce cross-checking, delay communication, and encourage premature closure; prolonged underload can reduce vigilance and readiness to respond. Automation changes rather than eliminates this problem. It can reduce routine manual demands while creating monitoring requirements and abrupt workload transitions when the system reaches a limit or behaves unexpectedly [3,4,28].

Stress is similarly non-linear. Acute arousal can support focused performance, but excessive or prolonged stress can impair working memory, flexible reasoning, and attentional control. Importantly, empirical relationships are context dependent. In the commercial-pilot simulation study by Mohan and colleagues, perceived stress itself was not a significant predictor of decision performance after other variables were considered [11]. Accordingly, stress should not be treated as a uniform predictor of poor decision-making. Its operational effect varies with intensity, duration, appraisal, task characteristics, experience, available support, and concurrent workload.

Operational countermeasures include structured briefings, explicit decision points, standard operating procedures, cross-monitoring, automation mode awareness, and the deliberate use of the second crew member as a cognitive resource. These mechanisms reduce reliance on unaided memory and individual judgment. They are most effective when procedures remain usable under actual workload rather than existing only as formal compliance requirements [18,19,28].

A further implication concerns metacognitive calibration: crews must judge not only the external situation but also the reliability of their own interpretation. Confirmation bias, plan-continuation tendencies, and overconfidence can make an initially plausible mental model resistant to disconfirming evidence. Analyses of aviation decision errors have shown that plan-continuation errors can persist despite cues indicating that the original course of action should be changed [13]. Cross-checking and explicit verbalization of assumptions are therefore cognitive safeguards as well as communication techniques. In high-tempo phases of flight, a useful team process is to make uncertainty visible, for example, by stating what is known, what remains uncertain, and what condition would trigger a change in plan. This converts private doubt into shared operational information and reduces the risk that several crew members silently maintain incompatible mental models.

Decision support should also be designed around the temporal characteristics of aviation. Information that is accurate but arrives too late may have little safety value. Conversely, excessive alerts can compete for attention and encourage habituation. Human-factors engineering therefore requires prioritization, salience, and timing to be considered together. The objective is not maximal information display, but the right information in a form that supports perception, comprehension, projection, and action at the point of need [8].

3. Fatigue and Occupational Stress

Fatigue is among the clearest physiological and psychological hazards in aviation because it affects multiple functions required for safe performance. A systematic review by Bendak and Rashid identified adverse effects on judgment, memory, reaction time, decision-making, and situation awareness and found substantially elevated fatigue risk when duty periods exceeded approximately 16 h, pre-duty sleep was below approximately six hours, or work occurred during the individual's usual sleep period [14]. Aviation medicine research likewise identifies irregular work hours, long duty periods, circadian disruption, and insufficient sleep as recurrent contributors to pilot fatigue [15]. These findings are especially relevant to aviation because irregular schedules, early starts, night operations, time-zone transitions, and extended duty can combine with operational workload.

Fatigue should be distinguished from ordinary subjective tiredness. Personnel may underestimate their impairment, and motivation does not fully restore neurobehavioral performance. This makes fatigue a system-management problem as well as individual responsibility. Scheduling practices, reserve arrangements, reporting culture, commuting patterns, opportunities for restorative sleep, and the design of Fatigue Risk Management Systems (FRMS) all influence exposure [14–16].

The psychological effects of fatigue are operationally significant because they overlap with the mechanisms discussed in the previous section. Reduced vigilance can delay detection of weak signals; impaired working memory can undermine checklist and communication performance; slower reaction time can reduce the margin available for recovery; and diminished cognitive flexibility can make crews more likely to persist with an initial plan. Fatigue therefore acts as a multiplier of other human-factors vulnerabilities rather than as a separate risk category.

Mental Fatigue, Work Pressure, and Safety Behavior

One study reports that mental fatigue may be more strongly related to unsafe behavior than physical fatigue and that work pressure can be a major contributor to pilot fatigue [29]. Cabin-crew research similarly links fatigue-related attention deficits and distraction with reduced planning and safety behavior [30]. Although the operational tasks of pilots and cabin crew differ, these preliminary findings suggest the importance of attentional control and prospective planning in safety-critical work.

Occupational stress interacts with fatigue through both acute and chronic pathways. High work pressure can extend effort, reduce recovery, and increase the likelihood that personnel continue operating despite reduced capacity. Conversely, chronic sleep disruption can lower tolerance for stress and increase emotional reactivity. From an organizational perspective, the relevant intervention is therefore not limited to individual resilience training. Work design, staffing, rostering, predictable recovery opportunities, nonpunitive fatigue reporting, and managerial decisions about operational tempo are equally important [14–16].

Fatigue management is strongest when it combines regulatory limits with risk-based controls. Prescriptive duty-time rules establish boundaries but cannot capture every combination of circadian timing, sleep history, workload, and individual variation. International Civil Aviation Organization (ICAO) guidance consequently frames fatigue management as a scientifically informed and data-driven safety process rather than a matter of duty-time compliance alone [16]. In practice, this requires combining operational data, fatigue reports, schedule analysis, and established fatigue science to identify recurrent exposure patterns and select proportionate mitigations.

The evidence base also argues for caution when converting group-level fatigue findings into deterministic individual thresholds. Bendak and Rashid found substantial increases in risk under long workdays, short pre-duty sleep, and work during usual sleep hours, while also emphasizing that fatigue risk is heterogeneous and not fully captured by existing prediction models [14]. Operationally, this means that a duty period can be legally compliant yet still present elevated fatigue risk because of circadian timing, accumulated sleep debt, workload, or disrupted recovery. FRMS should therefore complement, rather than simply reproduce, prescriptive flight- and duty-time limitations.

An effective fatigue reporting system also requires a just and learning-oriented response. If fatigue declarations are routinely interpreted as lack of commitment, personnel have an incentive to conceal a safety-relevant state. If every fatigue report is accepted without analysis, the organization loses an opportunity to identify recurrent scheduling or staffing problems. The appropriate human-factors response is to separate immediate fitness-for-duty decisions from subsequent system learning: protect the operation first,

then examine whether the event reflects an individual circumstance, a roster pattern, a workload issue, or a broader organizational exposure.

4. Crew Resource Management

Crew Resource Management is the principal aviation training framework for the non-technical skills that allow crews to use people, information, procedures, and equipment effectively. Its purpose is safety and error management rather than interpersonal harmony alone. Contemporary CRM includes communication, leadership and followership, teamwork, decision-making, workload management, situation awareness, threat-and-error management, and the recognition of human performance limitations [18,19].

CRM emerged from recognition that technically competent crews could still experience catastrophic outcomes when coordination, leadership, communication, or decision-making failed. Over time, its scope expanded from cockpit attitudes and authority gradients to team coordination, organizational context, error management, and Threat and Error Management [18]. Evaluations of CRM have generally found positive trainee reactions and evidence of learning and behavioral change, while also demonstrating the difficulty of attributing organization-level safety outcomes to training alone [2]. A recent narrative review describes CRM as a cornerstone of aviation safety while arguing that training must continue to evolve in response to artificial intelligence, mental health and resilience, workforce diversity, competency-based training, and the need for stronger transfer of human-factors research into operational practice [17].

This evolution is important because CRM should not become a static syllabus of generic communication principles. Non-technical skills must be practiced under realistic operational constraints. Scenario-based training allows communication, monitoring, leadership, and decision-making to emerge in context, particularly when crews face uncertainty, competing priorities, or an unexpected deterioration. The goal is not to teach a single conversational style but to create robust coordination behaviors that remain functional under pressure.

The current CRM literature also highlights an implementation problem: scientific knowledge and regulatory development do not automatically translate into training practice. Pollitt and colleagues argue that progress across operators remains uneven and that institutional mechanisms for translating emerging evidence into CRM design are often weak [17]. This observation supports a recurrent evidence cycle in which operators identify operational risk, define observable non-technical competencies, design scenarios that elicit those competencies, assess behavior using trained evaluators, and feed the resulting evidence back into training governance. Such a cycle connects CRM to the Safety Management System rather than treating it as a stand-alone recurrent training requirement.

CRM assessment should distinguish knowledge from behavior. A crew member may correctly describe assertiveness, workload management, or Threat and Error Management (TEM) in a classroom while failing to demonstrate these competencies under surprise, ambiguity, or social pressure. Behavioral markers are useful because they make non-technical performance observable: examples include whether threats are verbalized during briefing, whether monitoring continues during high workload, whether deviations are challenged, whether leadership adapts to the situation, and whether the crew explicitly confirms recovery from an error. The quality of assessment, however, depends on rater training and on avoiding the reduction in complex team behavior to mechanical checklist compliance.

4.1. Competency-Based Training, Evidence-Based Training, and Assessment

Competency-based training and assessment (CBTA) specifies observable competencies and standards rather than relying solely on training hours. ICAO's Evidence-Based

Training (EBT) guidance (Doc 9995) uses operational evidence and defined competencies to design and assess recurrent training [31]. Within the European framework, Commission Regulation (EU) No 965/2012, Annex III (Part-ORO), addresses CRM training under ORO.FC.115 and evidence-based training under ORO.FC.231, with associated European Union Aviation Safety Agency (EASA) acceptable means of compliance and guidance material. Operators must consult the current consolidated rules and applicable approvals when implementing these provisions [32]. Assessment should use scenario-relevant behavioral markers, trained evaluators, and structured debriefing; reliability and transfer to line operations should be examined rather than assumed [2,6].

4.2. Threat and Error Management

Threat and Error Management (TEM) provides a practical bridge between systemic human-factors thinking and crew behavior. Threats include conditions that increase operational complexity or risk but are not necessarily created by the crew, such as weather, technical abnormalities, time pressure, unfamiliar airports, or traffic constraints. Errors are actions or inactions that deviate from intentions or expectations. In the Line Operations Safety Audit (LOSA)/TEM framework, crew countermeasures are evaluated in relation to how threats and errors are anticipated, trapped, and mitigated during normal operations [18,20]. CRM supplies the behavioral resources that support this process.

The TEM perspective reduces the usefulness of a blame-based distinction between ◎good◎ and ◎bad◎ operators. Error is treated as an expected feature of complex human performance. The safety objective is to make the system resilient: threats should be identified early, errors should be detectable, and recovery pathways should remain available. Briefings, cross-checks, challenge-and-response procedures, monitoring, standardized callouts, and open communication are examples of defenses that create this resilience.

4.3. CRM and Safety Culture

CRM effectiveness depends on the organizational environment in which trained behaviors are expected to occur. A study of 451 airline pilots found a significant positive relationship between CRM and flight safety culture [23]. This relationship is conceptually important: training can reinforce safety culture, while culture determines whether CRM behaviors are supported in line operations. An organization cannot credibly teach assertiveness, reporting, and challenge in the classroom while rewarding silence, schedule completion at any cost, or unquestioned authority in daily operations.

Safety culture includes shared assumptions about priorities, reporting, learning, accountability, and acceptable risk. Reviews of safety-culture research emphasize both the multidimensional nature of the construct and the need to distinguish deeper organizational culture from measurable safety-climate perceptions [24]. It is expressed through decisions about staffing and resources as much as through formal safety statements. ICAO safety-management guidance similarly treats safety culture, reporting, safety data, and organizational learning as interdependent components of safety management [25]. When safety culture is strong, personnel receive consistent signals that operational concerns should be raised and investigated. When it is weak, local production pressures can override formal policy, and CRM behaviors may become performative rather than operationally meaningful.

5. Safety Voice, Safety Listening, and Power Distance

A central CRM problem is how safety-critical information moves across status boundaries. Safety voice refers to speaking up about perceived hazards; safety listening concerns how recipients, particularly those with greater authority, respond to such concerns. Analysis of 172 cockpit voice recorder (CVR) transcripts from historic aviation

accidents showed that flight crews spoke up in all but two accidents, challenging the assumption that accidents primarily occur because junior crew remain silent [21,22]. The more discriminating issue was whether concerns were effectively heard, interpreted, and acted upon.

The same research found that power distance and poor safety listening explained variation in safety voice and that historical CRM improvements were more evident in lower-power-distance environments [21]. This shifts attention from the speaker alone to the interaction. Training a first officer to be assertive is insufficient if a captain dismisses, minimizes, or fails to process the warning. Effective CRM therefore requires both competent voice and competent listening.

Power distance is useful here as a description of the extent to which unequal authority is accepted and enacted. Aviation necessarily contains formal authority and role differentiation; safe operations do not require the elimination of command. The human-factors objective is instead a functional authority gradient: roles remain clear, but safety-relevant information can cross the gradient rapidly and without distortion. Too steep a gradient can suppress challenge or encourage indirect communication; too flat or ambiguous a gradient can impair decisive command when rapid coordination is required.

This distinction also prevents an overly culturalized interpretation of accidents. National culture may influence communication expectations, but organizational culture, training standards, leadership behavior, professional norms, language proficiency, and immediate operational pressure all shape cockpit interaction. Power distance should therefore be treated as one contextual variable within a socio-technical system, not as a deterministic explanation of individual behavior.

The safety-listening evidence is particularly important because it changes the target of intervention. Noort, Reader, and Gillespie analyzed communication in historic accident CVR transcripts and found that speaking up was common, while poor listening and high-power distance helped explain why safety concerns did not reliably alter the course of events [21,22]. Training should therefore include the response to challenge as an explicit leadership competence. Observable behaviors include acknowledging the concern, requesting clarification when needed, checking the relevant parameter or source, verbalizing the resulting decision, and ensuring that the challenger knows the concern has been processed. These closed-loop behaviors reduce ambiguity about whether a warning was merely heard acoustically or incorporated cognitively.

6. Korean Air as an Applied Human-Factors Case

The Korean Air accidents of the 1990s became a prominent case in discussions of CRM, hierarchy, and organizational safety reform. Korean Air Flight 801 and the airline's subsequent organizational transformation provide a useful illustration of how communication, authority gradients, training, and organizational context can interact with technical and operational factors. The case is valuable when used carefully: it should illuminate system reform rather than reduce a complex accident history to a stereotype about national culture [7,33].

Human-factors interpretations of the Korean Air case have often emphasized communication failures and highly deferential cockpit interaction as part of a broader problem in which junior crew could possess relevant information without converting that information into sufficiently forceful intervention [33]. Later research on safety voice adds an important qualification. Across historical accidents, junior personnel often did speak; failure could occur because warnings were indirect, poorly listened to, or insufficiently integrated into the senior decision-maker's mental model [21]. Thus, the practical lesson is not merely "speak up," but to establish communication structures in which risk information is recognizable as a challenge and requires an explicit response.

The reform narrative associated with Korean Air emphasizes systematic CRM training, recognition of cultural legacy, standardization, and organizational change. The significance of this example is that CRM was not treated as a one-off communication course. Sustainable change required alignment between training, leadership expectations, operational standards, and organizational safety priorities. This is consistent with evidence that CRM competence and safety culture are related [23].

The case also illustrates why CRM must be culturally sensitive without becoming culturally deterministic. Standardized aviation phraseology and procedures can reduce ambiguity, while training can explicitly address how authority, face-saving, indirectness, and leadership expectations affect challenge behavior. At the same time, captains must be trained in safety listening: inviting input, recognizing weak signals, acknowledging challenges, and demonstrating that raising a concern is an expected professional act.

The official investigation of Flight 801 provides a more precise foundation for this interpretation. The National Transportation Safety Board (NTSB) identified the captain's failure to adequately brief and execute the nonprecision approach and the first officer's and flight engineer's failure to effectively monitor and cross-check the captain as the probable cause; the captain's fatigue and Korean Air's inadequate flight crew training were contributing factors [7]. The report also identified an external system defense that was unavailable: the Federal Aviation Administration (FAA) had intentionally inhibited the minimum safe altitude warning system in Guam and had not adequately managed it [32]. These findings demonstrate why accidents should not be reduced to cockpit hierarchy alone. Crew coordination, fatigue, training, approach execution, monitoring, and air-traffic-system defenses formed an interacting risk configuration.

This multi-layered reading is more useful for CRM than a simplified cultural narrative. It directs attention to concrete competencies: approach briefing quality, monitoring discipline, cross-checking, recognition of an unsafe trajectory, escalation of challenge, and the captain's response to monitoring input. It also connects CRM with technical and organizational defenses. When one defense is degraded, the importance of other defenses increases; conversely, robust monitoring and challenge can sometimes compensate for imperfect technical or environmental conditions. The lesson is therefore about defense-in-depth and organizational learning, not the attribution of risk to nationality.

6.1. Structured Mapping of Flight 801: Findings, Mechanisms, and Barriers

The mapping in Table 2 distinguishes the NTSB's documented findings from a secondary, conceptual human-factors interpretation. It is not a reconstruction of unrecorded crew cognition and cannot validate causal paths independently of the investigation [7].

The cross-level relationships can be traced as an evidence-bounded sequence rather than inferred from category membership alone. In Flight 801, the documented approach-briefing and execution deficiencies define an operational decision point; inadequate monitoring and cross-checking represent a team-level opportunity for detection or correction; fatigue and inadequate training are investigation-identified contributing conditions; and the inhibited minimum safe altitude warning system represents an unavailable external defense [7]. The analytical question is how these conditions could jointly reduce opportunities to recognize and interrupt an unsafe trajectory, not whether the table proves that one factor caused another. Any proposed link between internal cognition and a particular communication response must remain a hypothesis unless supported by recorded or corroborated evidence.

To apply the mapping to another occurrence, an analyst should first establish a chronological event timeline from authoritative records and mark what is observed, reported, or unknown. Second, identify decision points and map the operational cue, relevant performance conditions, team communication, and available defenses to the five

framework levels; multiple levels may be coded for one event. Third, record the evidence source and confidence or uncertainty for each link, explicitly separating documented findings from interpretive hypotheses. Fourth, examine alternative explanations and both failed and successful barriers, including whether a different layer could plausibly have interrupted the sequence. Finally, translate the resulting interaction map into testable safety questions or candidate mitigations, and seek independent review of coding consistency. This is a proposed analytical workflow, not a validated accident-classification instrument; it should be tested on additional cases before claims of reproducibility or superiority are made.

Table 2. Korean Air Flight 801: documented findings, interpretive mechanisms, and prospective safety barriers.

National Transportation Safety Board (NTSB) Finding	Analytical Mechanism (Interpretation)	Relevant Barrier/Evaluation
Inadequate approach briefing and execution	Incomplete shared plan and inadequate monitoring of approach constraints	Briefing content, approach gates, procedural compliance
Ineffective first-officer and flight-engineer monitoring/cross-checking	Distributed situation awareness and challenge-response breakdown	Monitoring markers, cross-check callouts, escalation
Captain fatigue (contributing factor)	Potential impairment of vigilance and cognitive flexibility	Roster/sleep review and fatigue-risk controls
Inadequate flight-crew training (contributing factor)	Insufficient rehearsal of recognition, coordination, and recovery	Scenario-based CRM/Evidence-Based Training (EBT) and evaluator calibration
Guam minimum safe altitude warning function inhibited	Loss of an external independent alerting barrier	System availability, alert governance, safety assurance

6.2. From Communication Training to Organizational Transformation

The broader historical contribution of cases such as Korean Air is the movement from an individual-error model toward an organizational model of human performance. Early CRM interventions often focused on personal attitudes and interpersonal style. Later generations incorporated team coordination, automation, organizational culture, error management, and TEM. Contemporary approaches increasingly integrate CRM with competency-based training, evidence-based training, resilience, and safety management [2,18,31].

This evolution matters because recurrent training can lose effectiveness when it becomes predictable, generic, or detached from operational data. Modern CRM should be informed by the operator's actual risk profile, reports, unstable approaches, automation events, communication breakdowns, fatigue concerns, and other recurrent patterns. Scenario design can then target the cognitive and interpersonal mechanisms most relevant to those risks [2,17,31].

The 2026 review of CRM training argues that many operators still lack strong mechanisms for translating emerging scientific evidence into training design [17]. This gap is a current human-factors challenge. Aviation has accumulated a sophisticated vocabulary for non-technical skills, but terminology alone does not guarantee transfer to line operations. Training quality depends on instructional design, facilitator competence, realistic practice, behavioral assessment, feedback, and organizational reinforcement.

6.3. Limits of Case-Based Inference

The Flight 801 mapping is an analytical demonstration, not a statistical test or independent validation. Multiple mechanisms may coexist, and observed failures do not establish that any one proposed intervention would have prevented the accident. Official

investigation findings remain the evidentiary anchor; suggested behavioral markers and safety barriers are prospective applications requiring local validation [7,34].

7. Integrating Human Factors as a Socio-Technical Safety System

The domains discussed above converge in actual operations. Consider a time-critical abnormal event. A technical malfunction creates a threat. Automation behavior and cockpit displays determine what cues are available. Fatigue and workload influence attention and working memory. Situation awareness determines whether the crew correctly comprehends the developing state. Decision processes shape the selected response. CRM determines how tasks are allocated and whether divergent interpretations are voiced. Leadership and power distance affect whether a challenge is accepted. Organizational culture influences whether the crew feels permitted to discontinue an approach, delay a departure, divert, or otherwise prioritize safety over production.

No single layer is sufficient. A technically reliable aircraft cannot compensate for every failure of coordination; excellent CRM cannot remove the neurobehavioral consequences of severe fatigue; and an individual pilot cannot indefinitely overcome poor interface design or organizational pressure. Safety is produced by overlapping defenses that reduce the probability that weaknesses align.

This perspective has direct implications for investigation. Describing an event as ◎pilot error◎ provides little explanatory depth unless the analysis identifies the cognitive mechanism, local conditions, system design, training history, team interaction, and organizational influences that made the error possible or difficult to recover from. Similarly, describing an organization as having a ◎poor safety culture◎ is insufficient unless the analysis identifies observable practices, incentives, communication patterns, and decisions through which culture affected performance.

A mature human-factors program therefore integrates data from multiple sources: occurrence reports, flight data monitoring, training observations, fatigue reports, safety surveys, confidential reporting, operational audits, and investigation findings. The objective is to detect recurring conditions before they combine into a serious event. This is consistent with the broader transition from reactive accident analysis toward proactive and predictive safety management embedded in contemporary Safety Management System (SMS) practice [25].

Integration also requires attention to the level of analysis. Some indicators describe individuals, other teams, and others organizational systems. Combining them without distinction can create misleading conclusions, for example, inferring individual safety attitudes from aggregate occurrence rates or attributing a system-level scheduling problem to personal resilience. Human-factors analysis is strongest when the proposed mechanism and the evidence are aligned at the same level. Individual cognitive data can inform training and interface design; team observations can inform CRM; roster and reporting patterns can inform FRMS and organizational controls; and cross-source trends can inform safety governance.

For practitioners, a human-performance event can be examined sequentially: first identify the operational goal and threat; then reconstruct the information available at each decision point; examine workload, fatigue, and attention; map team communication and authority interactions; identify technical and procedural defenses; and finally assess the organizational conditions that shaped those layers. The purpose is not to remove individual accountability where it is warranted, but to avoid stopping the analysis at the most visible human action. A useful investigation explains both why the action made sense locally and why the system did not prevent or recover from it.

Cross-Level Framework and Operational Use

Figure 1 presents a proposed five-stage framework that links (1) operational demands and technical conditions, (2) physiological and cognitive capacity, (3) perception, situation awareness, and decision processes, (4) team coordination and safety voice/listening, and (5) procedural, technological, and organizational defenses. The stages are interacting levels rather than a fixed linear causal chain. Organizational decisions shape exposure and available defenses, while outcomes and reports feed back into training and safety governance. Reason's organizational accident model highlights latent conditions and defenses [35]; Dekker's systems-oriented account cautions against stopping at individual blame [27]; and Hollnagel's Safety-II perspective emphasizes the adaptations through which everyday work succeeds [36]. The Human Factors Analysis and Classification System (HFACS) organizes unsafe acts, preconditions, supervision, and organizational influences [34], while the Software, Hardware, Environment, Liveware, and Liveware (SHELL) model draws attention to mismatches among people, software, hardware, environment, and other people [37]. These frameworks are complementary lenses, not equivalent validated scoring instruments. The proposed synthesis should be tested prospectively for usefulness, inter-rater agreement, and predictive value.




Figure 1. Proposed cross-level framework integrating operational demands, human performance, team coordination, safety barriers, and learning. CRM = Crew Resource Management; SOPs = standard operating procedures. Arrows represent conceptual relationships and feedback, not validated causal effects. Conceptual synthesis; not an empirically validated causal model.

The specific added value of the five-level synthesis is procedural and relational rather than taxonomic novelty. HFACS provides a structured classification of unsafe acts, preconditions, supervision, and organizational influences [34]; SHELL foregrounds interfaces between the operator and the surrounding socio-technical components [37]; and Reason's model emphasizes how latent conditions and imperfect defenses can align [35]. The present framework does not replace these approaches or claim higher predictive accuracy. It instead asks analysts to document, for each consequential decision point, a traceable progression from operational cue and capacity constraints through interpretation and

interpersonal response to barrier availability, while explicitly recording feedback and evidentiary uncertainty. This can expose an unexamined transition—for example, a cue that was available but not effectively interpreted, or a challenge that was voiced but not acted upon—without treating those transitions as established causal facts. Its distinctiveness lies in the common cross-level questioning sequence and evidence log, which can be applied alongside HFACS or SHELL categories.

A practical comparison would require independent analysts to code the same incidents using the proposed sequence and established approaches, then assess inter-rater agreement, completeness of identified interactions, time required, and usefulness of resulting intervention hypotheses. These are prospective evaluation criteria, not results demonstrated by the present entry. Until such testing is conducted, the framework should be described as a transparent organizing heuristic with potential analytical utility, not as a methodologically superior or empirically validated safety model.

For practical use, investigators can record the observed cue, operator interpretation, available cognitive resources, communication response, failed or successful barrier, and evidentiary source at each decision point. A safety team can then triangulate simulator observations, line-operations data, fatigue reports, and organizational measures. Cross-level associations should not be interpreted causally without an appropriate research design [25,34].

8. Current Challenges and Future Directions

Human factors in aviation are evolving as operational systems become more automated, data-rich, and organizationally interconnected. Several future directions follow directly from the evidence reviewed here. First, CRM training must remain evidence-informed. The 2026 CRM review identifies artificial intelligence, mental health and resilience, diversity, and stronger knowledge exchange between researchers and practitioners as emerging priorities [17]. These issues should be integrated only where they improve operational competence rather than simply expanding the syllabus.

Second, human-automation interaction will become increasingly central. Advanced automation can reduce workload and standardize performance, but it can also create out-of-the-loop performance problems, loss of situation awareness, mode confusion, automation surprises, monitoring demands, and new forms of dependency [3,4]. More generally, automation changes the allocation of information acquisition, analysis, decision selection, and action implementation between people and systems rather than simply removing human work [5]. Human-factors design must preserve meaningful operator understanding and ensure that transitions from automated to manual or supervisory control are manageable under realistic conditions.

Third, fatigue management requires continued movement from compliance alone toward operational risk management. Duty limits remain essential, but organizations also need data capable of identifying recurrent fatigue exposures and evaluating mitigations. A reporting environment in which personnel can disclose fatigue without inappropriate stigma is necessary for this approach.

Fourth, CRM should increasingly address the receiving side of communication. The evidence on safety listening indicates that encouraging voice is not enough [21]. Leadership training should include observable behaviors for receiving challenges, clarifying ambiguous warnings, and closing the communication loop. This is especially important in multinational and multilingual operations, where linguistic proficiency and cultural expectations can influence how urgency is expressed.

Fifth, human-factors evaluation should move beyond trainee satisfaction and knowledge tests. The more consequential questions concern behavioral transfer, operational performance, recurrence of targeted events, and whether training changes the

system's capacity to detect and recover from threats. CRM evaluation reviews show why this multilevel approach is necessary: positive reactions and learning do not automatically demonstrate organization-level safety impact [2]. Where feasible, organizations should connect training objectives to safety data while avoiding simplistic attribution of accident rates to a single intervention.

A balanced account of the human role is also necessary. Human performance introduces variability and the possibility of error, but it also provides adaptation when unexpected combinations of events exceed procedural assumptions. Effective human-factors engineering therefore does not seek to design people out of aviation. It seeks to make human contribution more reliable by designing technology, procedures, teams, and organizations around realistic capabilities and limitations.

Research also needs a stronger linkage between psychological constructs and operational outcomes. Situation awareness, workload, resilience, safety culture, and trust in automation are useful constructs only when they are defined and measured with sufficient precision to guide intervention. Future studies should combine validated psychological measures with behavioral, simulator, operational, and longitudinal data where feasible. This would help distinguish associations from mechanisms and improve the ability of airlines, regulators, and training organizations to select interventions that address the actual source of risk.

Measurement Models in Simulation-Based Human-Factors Research

Simulation allows controlled variation in workload, automation modes, failures, time pressure, and communication demands while preserving task realism. Measurement models translate latent constructs into observable indicators: situation awareness may be assessed through scenario-specific probes such as the Situation Awareness Global Assessment Technique (SAGAT), workload through the National Aeronautics and Space Administration Task Load Index (NASA-TLX), and team performance through behaviorally anchored CRM markers [6,38,39]. Eye tracking, response times, flight-path deviations, error detection, and physiological indicators can provide complementary information, but none is an unambiguous stand-alone measure of awareness or safety. Construct validity, scenario representativeness, inter-rater reliability, sensitivity to workload manipulation, and transfer to operational outcomes must be established. Multimethod triangulation and repeated scenarios can help separate task effects from individual differences; simulation evidence should not be mistaken for direct proof of accident prevention [2,6,38,39].

9. Conclusions and Prospects

Human factors in aviation safety is best understood as an integrated system of cognitive, physiological, interpersonal, and organizational influences. Situation awareness and decision-making explain how crews perceive, interpret, and respond to dynamic conditions. Fatigue and occupational stress alter the resources available for those cognitive processes. CRM provides behavioral mechanisms for distributing workload, sharing information, managing threats and errors, and coordinating action. Safety culture and leadership determine whether those mechanisms are supported in everyday operations.

The evidence reviewed here also refines traditional assumptions about communication failure. Historical accident analysis indicates that safety voice is often present; the critical weakness may be safety listening, the force and clarity of the challenge, or the authority gradient through which information must travel. This makes leadership behavior and organizational context central components of CRM rather than peripheral cultural issues.

The Korean Air case illustrates the value of moving from isolated communication fixes toward organization-wide reform. Its broader lesson is not that one culture or one

communication style explains aviation accidents. It is that CRM becomes credible when training, leadership, standardization, operational practice, and safety culture reinforce one another.

Future aviation systems will introduce new forms of automation, artificial intelligence, workforce diversity, and operational complexity. The core human-factors requirement will nevertheless remain stable: safety depends on whether the socio-technical system enables people to perceive weak signals, understand evolving risk, communicate across boundaries, make timely decisions, and recover when plans or technologies fail. Human factors is therefore not an adjunct to aviation safety; it is one of the disciplines through which aviation safety is designed, trained, managed, and continuously improved.

The specific contribution of this entry is a proposed cross-level framework that connects operational demands, human performance, team interaction, and layered defenses, together with a bounded case-mapping procedure. For practitioners, the immediate implication is to assess the chain from cue availability through interpretation, challenge, action, and barrier performance rather than assigning a single-factor label. For researchers, priorities include testing the framework's reliability across analysts, evaluating simulation-based measures against operational indicators, and comparing interventions using longitudinal or controlled designs. The narrative source selection, heterogeneous evidence, and single accident illustration limit generalizability and do not support claims of causal validation.

In particular, the framework should be evaluated against established analytical methods on multiple events, while evidence claims should be differentiated by study design and outcome: simulator performance, observed team behavior, self-reported safety climate, and actual operational safety events are not interchangeable endpoints. Such comparisons would determine whether the proposed cross-level sequence adds practical insight beyond familiar classifications without overstating what the current narrative review and single-case illustration can establish.

Funding: This research received no external funding.

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.

Data Availability Statement: No new data were created or analyzed in this study.

Acknowledgments: During the preparation of this manuscript, the author used OpenAI ChatGPT (GPT-5.6) for drafting support, language refinement, structural organization, assistance with reference formatting, conceptual synthesis, and development and refinement of the explanatory tables and conceptual framework. The author reviewed and edited the output and takes full responsibility for the content of this publication.

Conflicts of Interest: The author declares no conflicts of interest.

Abbreviations

CRM	Crew Resource Management
CVR	Cockpit Voice Recorder
FRMS	Fatigue Risk Management System
TEM	Threat and Error Management

References

1. Psomas, E. Integrating Industrial–Organizational Psychology and Human Factors to Enhance Human Performance in Aviation. *E-J. VFU* **2025**, *24*, 470–482. https://doi.org/10.53606/evfu.24.470-482.
2. Salas, E.; Wilson, K.A.; Burke, C.S.; Wightman, D.C. Does Crew Resource Management training work? An update, an extension, and some critical needs. *Hum. Factors* **2006**, *48*, 392–412. https://doi.org/10.1518/001872006777724444.
3. Endsley, M.R.; Kiris, E.O. The out-of-the-loop performance problem and level of control in automation. *Hum. Factors* **1995**, *37*, 381–394. https://doi.org/10.1518/001872095779064555.
4. Sarter, N.B.; Woods, D.D. Team play with a powerful and independent agent: Operational experiences and automation surprises on the Airbus A-320. *Hum. Factors* **1997**, *39*, 553–569. https://doi.org/10.1518/001872097778667997.
5. Parasuraman, R.; Sheridan, T.B.; Wickens, C.D. A model for types and levels of human interaction with automation. *IEEE Trans. Syst. Man Cybern. A* **2000**, *30*, 286–297. https://doi.org/10.1109/3468.844354.
6. Flin, R.; O'Connor, P.; Crichton, M. *Safety at the Sharp End: A Guide to Non-Technical Skills*; Ashgate: Aldershot, UK, 2008.
7. National Transportation Safety Board. *Controlled Flight Into Terrain, Korean Air Flight 801, Boeing 747-300, HL7468, Nimitz Hill, Guam, August 6, 1997*; Aircraft Accident Report NTSB/AAR-00/01; NTSB: Washington, DC, USA, 2000.
8. Endsley, M.R. Toward a Theory of Situation Awareness in Dynamic Systems. *Hum. Factors* **1995**, *37*, 32–64. https://doi.org/10.1518/001872095779049543.
9. Endsley, M.R. Situation Awareness in Aviation Systems. In *Handbook of Aviation Human Factors*; Garland, D.J., Wise, J.A., Hopkin, V.D., Eds.; Lawrence Erlbaum Associates: Mahwah, NJ, USA, 1999; pp. 257–276.
10. Endsley, M.R. Design and Evaluation for Situation Awareness Enhancement. *Proc. Hum. Factors Soc. Annu. Meet.* **1988**, *32*, 97–101. https://doi.org/10.1177/154193128803200221.
11. Mohan, A.; Simonovic, B.; Correa Vione, K.; Stupple, E. Examining flight time, cognitive reflection, workload, stress and metacognition on decision making performance for pilots during flight simulation. *Ergonomics* **2025**, *68*, 1335–1347. https://doi.org/10.1080/00140139.2024.2404642.
12. Zhou, K.; Zhang, Y.; Lei, Y.; Li, J.; Tang, H. Sensory processing sensitivity predicts pilot decision time via indecisiveness: Evidence from flight simulation and fNIRS. *BMC Psychol.* **2026**, *14*, 665. https://doi.org/10.1186/s40359-026-04402-y.
13. Orasanu, J.; Martin, L.; Davison, J.; Null, C.H. Errors in Aviation Decision Making: Bad Decisions or Bad Luck? In *Proceedings of the Fourth Conference on Naturalistic Decision Making, Warrenton, VA, USA, 29–31 May 1998*; NASA Ames Research Center: Moffett Field, CA, USA, 1998.
14. Bendak, S.; Rashid, H.S.J. Fatigue in aviation: A systematic review of the literature. *Int. J. Ind. Ergon.* **2020**, *76*, 102928. https://doi.org/10.1016/j.ergon.2020.102928.
15. Caldwell, J.A.; Mallis, M.M.; Caldwell, J.L.; Paul, M.A.; Miller, J.C.; Neri, D.F. Fatigue countermeasures in aviation. *Aviat. Space Environ. Med.* **2009**, *80*, 29–59. https://doi.org/10.3357/ASEM.2435.2009.
16. International Civil Aviation Organization. *Manual for the Oversight of Fatigue Management Approaches (Doc 9966)*, 2nd ed.; ICAO: Montréal, QC, Canada, 2020.
17. Pollitt, A.; Vlaskamp, D.M.L.; Blundell, J.; Landman, A. Whither CRM?—30 Years on: A Narrative Review and Position Paper on the Future of Aviation CRM Training. *Aerospace* **2026**, *13*, 500. https://doi.org/10.3390/aerospace13060500.
18. Helmreich, R.L.; Merritt, A.C.; Wilhelm, J.A. The evolution of Crew Resource Management training in commercial aviation. *Int. J. Aviat. Psychol.* **1999**, *9*, 19–32. https://doi.org/10.1207/s15327108ijap0901_2.
19. Federal Aviation Administration. *Crew Resource Management Training*; Advisory Circular AC 120-51E; FAA: Washington, DC, USA, 2004.
20. Helmreich, R.L.; Klinect, J.R.; Wilhelm, J.A. System safety and threat and error management: The Line Operations Safety Audit (LOSA). In *Proceedings of the Eleventh International Symposium on Aviation Psychology*; Ohio State University Press: Columbus, OH, USA, 2001.
21. Noort, M.C.; Reader, T.W.; Gillespie, A. Safety voice and safety listening during aviation accidents: Cockpit voice recordings reveal that speaking up to power is not enough. *Saf. Sci.* **2021**, *139*, 105260. https://doi.org/10.1016/j.ssci.2021.105260.
22. Noort, M.C.; Reader, T.W.; Gillespie, A. Cockpit voice recorder transcript data: Capturing safety voice and safety listening during historic aviation accidents. *Data Brief* **2021**, *39*, 107602. https://doi.org/10.1016/j.dib.2021.107602.
23. Terzioğlu, M. The effects of crew resource management on flight safety culture: Corporate crew resource management (CRM 7.0). *Aeronaut. J.* **2024**, *128*, 1743–1766. https://doi.org/10.1017/aer.2023.113.
24. Wiegmann, D.A.; Zhang, H.; von Thaden, T.L.; Sharma, G.; Gibbons, A.M. Safety Culture: An Integrative Review. *Int. J. Aviat. Psychol.* **2004**, *14*, 117–134. https://doi.org/10.1207/s15327108ijap1402_1.

25. International Civil Aviation Organization. *Safety Management Manual (Doc 9859)*, 4th ed.; ICAO: Montréal, QC, Canada, 2018.
26. Klein, G. *Sources of Power: How People Make Decisions*; MIT Press: Cambridge, MA, USA, 1998.
27. Dekker, S. *The Field Guide to Understanding "Human Error"*, 3rd ed.; CRC Press: Boca Raton, FL, USA, 2014.
28. Wickens, C.D. Multiple resources and performance prediction. *Theor. Issues Ergon. Sci.* **2002**, *3*, 159–177. https://doi.org/10.1080/14639220210123806.
29. Zhu, S.; Chen, J. Influence of Fatigue on Flight Safety: A Structural Equation Modeling Analysis. *Appl. Math. Nonlinear Sci.* **2023**, *8*, 3371–3382. https://doi.org/10.2478/amns.2023.2.01135.
30. Park, I.-S.; Kim, K.-W.; Park, S.-S. A Research on the Effect of a Cabin Crews◉Low Level of Work Situational Awareness to Their Safety Behavior: Including the Mediation Effect Analysis on Cabin Crews◉ Forward Planning. *J. Korean Soc. Aviat. Aeronaut.* **2022**, *30*, 76–85. https://doi.org/10.12985/ksaa.2022.30.3.076.
31. International Civil Aviation Organization. *Manual of Evidence-Based Training (Doc 9995)*, 1st ed.; ICAO: Montréal, QC, Canada, 2013.
32. European Commission. Commission Regulation (EU) No 965/2012 of 5 October 2012 laying down technical requirements and administrative procedures related to air operations, as amended; Annex III (Part-ORO), ORO.FC.115 (Crew resource management (CRM) training) and ORO.FC.231 (Evidence-based training (EBT)). *Off. J. Eur. Union* **2012**, *L 296*, 1–148.
33. Cheng, Y. From a Safety Outlier to One of the Best Airlines in the World—How CRM Changed Korean Air. In *Crew Resource Management: Trends and Directions Graduate Research Conference*; Embry-Riddle Aeronautical University: Daytona Beach, FL, USA, 2015.
34. Shappell, S.A.; Wiegmann, D.A. *The Human Factors Analysis and Classification System—HFACS*; DOT/FAA/AM-00/7; Federal Aviation Administration: Washington, DC, USA, 2000.
35. Reason, J. *Human Error*; Cambridge University Press: Cambridge, UK, 1990.
36. Hollnagel, E. *Safety-I and Safety-II: The Past and Future of Safety Management*; Ashgate: Farnham, UK, 2014.
37. Hawkins, F.H. *Human Factors in Flight*; Gower: Aldershot, UK, 1987.
38. Endsley, M.R. Measurement of situation awareness in dynamic systems. *Hum. Factors* **1995**, *37*, 65–84. https://doi.org/10.1518/001872095779049499.
39. Hart, S.G.; Staveland, L.E. Development of NASA-TLX (Task Load Index): Results of empirical and theoretical research. In *Human Mental Workload*; Hancock, P.A., Meshkati, N., Eds.; North-Holland: Amsterdam, The Netherlands, 1988; pp. 139–183.

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.