crystals

MDPI

Article

Fabrication of Polarization Grating on *N*-benzylideneaniline Polymer Liquid Crystal and Control of Diffraction Beam

Mizuho Kondo [1,2,*], Kyohei Fujita [1], Tomoyuki Sasaki [2,3], Moritsugu Sakamoto [2,3], Hiroshi Ono [2,3] and Nobuhiro Kawatsuki [1,2,*]

[1] Department of Applied Chemistry, Graduate School of Engineering, University of Hyogo, 2167 Shosha, Himeji 671-2280, Japan; m1fujitak@gmail.com
[2] Japan Science and Technology Agency (JST), Core Research for Evolutional Science and Technology (CREST), Chiyoda-ku, Tokyo 102-0076, Japan; sasaki_tomoy@vos.nagaoka.ac.jp (T.S.); sakamoto@vos.nagaokaut.ac.jp (M.S.); onoh@vos.nagaokaut.ac.jp (H.O.)
[3] Department of Electrical Engineering, Nagaoka University of Technology, 1603-1 Kamitomioka, Nagaoka 940-2188, Japan
* Correspondence: mizuho-k@eng.u-hyogo.ac.jp (M.K.); kawatuki@eng.u-hyogo.ac.jp (N.K.); Tel.: +81-79-267-4014 (M.K.)



Figure S1. Diffraction photographs of an optical switch in (**a**) voltage-off state and (**b**) voltage-on state using an AC input (4 V, 60 Hz).