

Strain Rate and Stress Amplitude Effects on The Mechanical Behavior of Carbon Paste Used in The Hall–Hérout Process and Subjected to Cyclic Loadings

Zahraa Kansoun ^{1,*}, Hicham Chaouki ², Donald Picard ³, Julien Lauzon-Gauthier ⁴,
Houshang Alamdari ⁵ and Mario Fafard ¹

¹ Department of Civil and Water Engineering, NSERC/Alcoa Industrial Research Chair MACE3, Aluminium Research Centre—REGAL, Université Laval, Quebec, QC G1V 0A6, Canada; mario.fafard.2@ulaval.ca

² SAFI Quality Software Inc., Quebec, QC G1X 1S7, Canada; hicham.chaouki.1@ulaval.ca

³ Eddify Technologies Company, Quebec, QC G1P 0B3, Canada; dpicard@eddyfi.com

⁴ Continuous Improvement Smelting Technology, Alcoa, Deschambault-Grondines, QC G0A 1S0, Canada; julien.lauzon-gauthier@alcoa.com

⁵ Department of Mining, Metallurgical and Materials Engineering, NSERC/Alcoa Industrial Research Chair MACE3, Aluminium Research Centre—REGAL, Université Laval, Quebec, QC G1V 0A6, Canada; houshang.Alamdari@gmn.ulaval.ca

* Correspondence: zahraa.kansoun.1@ulaval.ca; Tel.: +15816812007




Figure S1. Experimental set-up.