

**Fenton-Oxidation Adsorption-Enhanced Ceramic Membrane Filtration for Advanced
Treatment of Refinery Wastewater: Treatment Efficiency and Membrane-Fouling Control**

Haotian Mu¹, Qi Qiu³, Renzhen Cheng¹, Liping Qiu^{1,2,*}, Kang Xie^{1,2}, Mingchang Gao¹ and Guicai

Liu^{1,2,*}

- 1 School of Civil Engineering and Architecture, University of Jinan, Jinan 250022,
China; muhaotian1997@163.com (H.M.); 18366105822@163.com (R.C.);
cea_xiek@ujn.edu.cn (K.X.); gaomc555@163.com (M.G.)
- 2 Research Center for Functional Material & Water Purification Engineering of
Shandong Province, Jinan 250022, China
- 3 School of Water Conservancy and Environment, University of Jinan, Jinan 250022,
China; qiuqi_1994@163.com

*Correspondence: lipingqiu@163.com (L.Q.); cea_liugc@ujn.edu.cn (G.L.)

Submitted to

Membranes

August 25, 2021

*To whom correspondence should be address.

[Tel: 13793189608](tel:13793189608) e-mail: lipingqiu@163.com; Tel: 18769707072 e-mail: cea_liugc@ujn.edu.cn

List of Supplementary materials

Figure S1: The structure of the membrane module.

Figure S2: Membrane resistance of CM in the operation of direct filtration and combined process: The membrane fouling resistance was calculated by equation (1-4).




Figure S1: The structure of the membrane module.




Figure S2: Membrane resistance of CM in the operation of direct filtration and combined process: The membrane fouling resistance was calculated by equation (1-4).