
Supplementary Information

Thin film composite membranes based on the polymer of intrinsic microporosity PIM-EA(Me₂)-TB blended with Matrimid®5218.

Mariagiulia Longo¹, Marcello Monteleone¹, Elisa Esposito^{1*}, Alessio Fuoco¹, Elena Tocci¹, Maria-Chiara Ferrari², Bibiana Comesaña-Gándara³, Richard Malpass-Evans³, Neil B. McKeown³, Johannes C. Jansen^{1*}

¹Institute on Membrane Technology (CNR-ITM), Via P. Bucci, 17/C, 87036 Rende (CS), Italy


² School of Engineering, University of Edinburgh, Robert Stevenson Road, Edinburgh EH9 3FB, UK

³ EaStCHEM, School of Chemistry, University of Edinburgh, David Brewster Road, Edinburgh EH9 3FJ, UK

* Correspondence: e.esposito@itm.cnr.it (E.E.); johannescarolus.jansen@cnr.it (J.C.J.)

Support	Matrimid/PIM ratios (wt%)				
	0/100	25/75	50/50	75/25	100/0
Vladipor					
Fluoroplast 50 nm					
Sulzer PAN UF					
Synder PAN 30kDa					
Nanostone PVDF PV350					

SI Figure S1. Images of the TFC membranes with the four different supports after the permeability tests.



SI Figure S2. Cross-sectional SEM images of the of Matrimid®5218 / PIM-EA(Me₂)-TB blend membranes with different blend compositions

