



Supporting Information

Enhancing the Capacity and Stability by CoFe_2O_4 Modified g- C_3N_4 Composite for Lithium-Oxygen Batteries

Xiaoya Li ¹, Yajun Zhao ¹, Lei Ding ¹, Deqiang Wang ¹, Qi Guo ¹, Zhiwei Li ¹, Hao Luo ^{1,*}, Dawei Zhang ¹ and Yan Yu ^{2,*}

¹ School of Chemistry and Chemical Engineering, Hefei University of Technology, Hefei 230009, China; Sabrina_lxy@163.com (X.L.); zyj251264@163.com (Y.Z.); dlei1107@163.com (L.D.); wondreful26@163.com (D.W.); 18297919084@163.com (Q.G.); Zhiwei.Li@hfut.edu.cn (Z.L.); zhangdw@ustc.edu.cn (D.Z.)

² Department of Materials of Science and Engineering, University of Science and Technology, Hefei 230026, China

* Correspondence: luohao@hfut.edu.cn (H.L.); yanyumse@ustc.edu.cn (Y.Y.)




Figure S1. SEM image of bulk g-C₃N₄.




Figure S2. SEM image of flake g-C₃N₄.




Figure S3. SEM image of CoFe₂O₄ cathode.




Figure S4. (a) N_2 adsorption-desorption isotherms and (b) specific surface area and pore volume of $g-C_3N_4$ and $CoFe_2O_4/g-C_3N_4$.