

Supporting Information

Model-based dielectric constant estimation of polymeric nanocomposite

Jiang Shao¹, Le Zhou², Yuqi Chen³, Xue Liu^{4,*} and Mingbo Ji^{5,*}

¹Jiangsu University of Science and Technology, Zhenjiang, 212100, P. R. China; Jiang-Shao@hotmail.com

²Changzhou Betterial Film Technologies Co., Ltd., Changzhou, 213000, P. R. China; zhoule@ betterial.cn

³University of Pennsylvania, Philadelphia, 19104, US; sevenchen9819@gmail.com

⁴Henan Key Laboratory of Polyoxometalate Chemistry, College of Chemistry and Chemical Engineering, Henan University, Kaifeng, Henan 475004, P. R. China; xliu@ipe.ac.cn

⁵ Harbin Engineering University, 264000 Yantai, China; minjikt@outlook.com

* Correspondence: xliu@ipe.ac.cn; Tel.: +86 15101544706; minjikt@outlook.com; Tel.: +86 13041090299




Figure S1 The dielectric constant of the experimental data and modeling results based on the developed Knott model of three nanocomposites: (a) PI-BTiO₃ composite; ¹ (b) ER-Al₂O₃ composite; ² (c) PI-BTiO₃ composite ³

Reference

1. Fan B H, Zha J W, Wang D R, et al. Experimental study and theoretical prediction of dielectric permittivity in BaTiO₃/polyimide nanocomposite films[J]. Applied Physics Letters, 2012, 100(9): 092903.
2. Kochetov R, Andritsch T, Morshuis P H F, et al. Thermal and electrical behaviour of epoxy-based microcomposites filled with Al₂O₃ and SiO₂ particles[C]//2010 IEEE International Symposium on Electrical Insulation. IEEE, 2010: 1-5.
3. Dang Z M, Lin Y Q, Xu H P, et al. Fabrication and dielectric characterization of advanced BaTiO₃/polyimide nanocomposite films with high thermal stability[J]. Advanced Functional Materials, 2008, 18(10): 1509-1517.