

Table S1. Water chemical analyses of groundwater samples in the study area.

Well ID	Well NO	EC	Anions (ppm or mg/l)		Cations (ppm) = (mg/l)		
		($\mu\text{s/cm}$)	HCO_3^-	Cl^-	Ca^{+2}	Mg^{+2}	Na^+
1	1	7000	109	1875	299	188	980
2	2	19000	189	5911	456	240	3249
3	3	12000	336	3071	637	388	2275
4	4	17000	109	4218	536	385	2349
5	5	11000	104	3227	373	274	1739
6	6	15000	98	4392	367	393	2199
7	7	5000	79	1627	301	101	648
8	8	6000	115	1238	186	174	787
9	9	5000	92	1298	271	132	690
10	10	6000	87	1418	294	128	787
11	11	6000	69	1652	305	131	940
12	12	7000	115	1484	282	170	900
13	13	7000	98	1562	344	132	920
14	14	8000	109	1562	294	191	880
15	15	5000	104	1232	390	127	490
16	16	5000	98	1214	288	124	580
17	17	5000	297	1056	234	110	908
18	18	6000	104	1592	277	164	780
19	19	10000	369	2517	501	298	2138
20	20	9000	299	2443	261	48	1600
21	21	12000	140	3449	585	278	1356
22	22	5000	89	1166	274	121	610
23	23	5000	81	1370	113	219	600
24	24	5000	83	1310	175	191	621
25	25	7000	92	1352	209	107	1040
26	26	9000	280	2433	234	49	1625
27	27	9000	69	2229	378	206	1274
28	28	10000	92	2031	451	200	1179
29	29	6000	69	1172	271	132	800
30	30	7000	101	1382	339	136	1279
31	31	6000	78	1238	263	122	755
32	32	7000	128	2210	273	115	1160
33	33	10000	151	2286	393	114	1500
34	34	7000	98	1562	260	183	900
35	35	11000	92	2704	548	287	1425
36	36	10000	98	2500	438	256	1219
37	37	7000	69	1550	254	181	828
38	38	9000	116	2751	293	122	1550
39	39	9000	116	2751	293	122	1550
40	40	10000	122	2624	334	106	1699
41	41	9000	153	2274	322	123	1499
42	42	7000	109	1742	316	168	980
43	43	8000	104	2223	440	222	1100

44	44	9000	58	2399	320	100	1449
45	45	7000	128	1700	190	108	1159
46	46	11000	140	3598	340	158	1849
MO23	47	3620	189	1119	152	70	600
R85	48	9890	156	3100	240	268	1700
A1	49	8940	839	1411	305	287	864
A2	50	9140	840	1442	292	240	795
A3	51	8670	841	1444	291	242	792
A6	52	8882	884	1447	309	352	887
AC2	53	4240	167	1417	124	135	606
AC3	54	3750	147	1254	109	119	536
AC7	55	6967	274	2329	203	221	936
AC8	56	6240	245	2086	182	198	892
GV874	57	5584	100	1382	340	135	1279
Mo1	58	5770	189	2022	215	120	1032
Mo2	59	8270	226	3012	303	151	1642
Mo13	60	5820	244	1797	212	134	1044
Mo14	61	6120	164	2518	299	159	1310
Mo20	62	7840	171	2868	327	173	1432
Mo21	63	4360	79	1488	186	87	209
Mo24	64	7760	201	3135	345	195	1511
Mo26	65	3420	244	1018	139	61	574
Mo27	66	6160	305	2057	275	158	1099
Mo29	67	4820	128	1823	205	103	896
Mo30	68	5620	207	1665	176	93	963
Mo33	69	9031	116	1165	183	67	701
Mo8	70	4940	134	1589	232	105	774
R113	71	10290	160	2900	180	292	1700
R134	72	11770	180	3300	280	328	1600
R140	73	11800	180	3600	200	377	2000
R58	74	6000	144	1950	160	146	1125
R90	75	10540	152	3200	200	292	1800
X115	76	8780	180	2800	200	207	1700
X57	77	9470	156	2700	180	243	1550
X60	78	9140	152	2700	180	243	1550
X85	79	8390	144	2700	180	207	1400
Minimum value		3420	58	1018	109	48	209
Maximum value		19000	884	5911	637	393	3249
Mean value		7866.5	190.1	2128.8	286.0	180.3	1184.5

Table S2. Comparison between productivity values and reject salts for practical experiments and modeling using ROSA software.

Exp no	Feed salinity, ppm	Feed pressure, bar	Exp		ROSA		Error	
			Flux, l/hr.m ²	Rejection, %	Flux, l/hr.m ²	Rejection, %	Flux, l/hr.m ²	Rejection, %
1	250	2	6.20	96.40	5.32	98.38	-14.19	2.05
2	500	2	5.20	96.00	4.53	97.56	-12.88	1.62
3	750	2	4.25	95.60	3.78	96.57	-11.06	1.02
4	1000	2	3.45	94.45	3.08	95.32	-10.72	0.92
5	1250	2	2.71	92.90	2.43	93.65	-10.33	0.81
6	1500	2	2.05	90.67	1.85	91.32	-9.76	0.72
7	250	4	13.50	98.00	12.54	99.23	-7.11	1.26
8	500	4	12.60	97.70	11.67	98.93	-7.38	1.26
9	750	4	11.60	97.60	10.83	98.65	-6.64	1.07
10	1000	4	10.70	97.30	10.03	98.36	-6.26	1.09
11	1250	4	9.81	97.10	9.24	98.08	-5.81	1.01
12	1500	4	9.00	96.90	8.49	97.78	-5.67	0.91
13	1500	1	0.19	47.90	0.16	48.20	-15.79	0.63
14	1500	2	2.05	90.67	1.85	91.32	-9.76	0.72
15	1500	3	5.50	95.60	5.12	96.53	-6.91	0.97
16	1500	4	9.00	96.90	8.49	97.78	-5.67	0.91
17	1500	5	12.40	97.00	11.80	98.32	-4.84	1.36
18	1500	6	15.70	97.20	15.05	98.61	-4.14	1.45
Standard deviation			4.49	11.18		11.39		
					4.30			

Table S3. Salt rejection values for EC, Na, Ca, Mg, HCO₃, and Cl.

Well	Rejection, %											
	EC		Na		Ca		Mg		HCO ₃		Cl	
	ROS A	Exp	ROS A	Exp	ROS A	Exp	ROS A	Exp	ROS A	Exp	ROS A	Exp
W47	98.19	95.13	97.83	94.20	98.96	95.92	98.94	95.90	97.69	94.35	98.10	95.20
W54	98.18	95.09	97.89	94.25	98.81	95.73	98.79	95.70	97.71	94.33	98.24	95.30
W65	98.24	95.26	97.91	94.28	98.99	96.10	98.98	96.05	97.79	94.41	98.17	95.26
Error, %	3.22		3.86		3.17		3.17		3.54		3.04	

Table S4. source water assessment based on IWQI.

Well	EC	SAR	Na	Cl	HCO ₃	IWQI	Water class
	µs/cm	mmol/lit) ^{0.50}	mmol/l				
W1	7000	10.8	42.1	54.4	1.7	40.1	HR
W2	19000	30.2	139.7	171.4	3.0	14.6	SR
W3	12000	17.3	97.8	89.1	5.4	24.7	SR
W4	17000	18.6	101.0	122.3	1.7	26.1	SR
W5	11000	16.4	74.8	93.6	1.7	32.4	SR
W6	15000	18.7	94.6	127.4	1.6	27.4	SR
W7	5000	8.1	27.9	47.2	1.3	46.1	HR
W8	6000	9.8	33.8	35.9	1.8	42.4	HR
W9	5000	8.5	29.7	37.6	1.5	44.8	HR
W10	6000	9.5	33.8	41.1	1.4	43.7	HR
W11	6000	11.2	40.4	47.9	1.1	43.4	HR
W12	7000	10.3	38.7	43.0	1.8	41.0	HR
W13	7000	10.5	39.6	45.3	1.6	41.1	HR
W14	8000	9.7	37.8	45.3	1.7	41.1	HR
W15	5000	5.4	21.1	35.7	1.7	47.8	HR
W16	5000	7.1	24.9	35.2	1.6	46.0	HR
W17	5000	12.1	39.0	30.6	4.8	36.3	SR
W18	6000	9.1	33.5	46.2	1.7	42.9	HR
W19	10000	18.4	91.9	73.0	5.9	25.5	SR
W20	9000	23.6	68.8	70.8	4.8	26.9	SR
W21	12000	11.4	58.3	100.0	2.2	33.7	SR
W22	5000	7.6	26.2	33.8	1.4	46.1	HR
W23	5000	7.5	25.8	39.7	1.3	46.8	HR
W24	5000	7.6	26.7	38.0	1.3	46.5	HR
W25	7000	14.4	44.7	39.2	1.5	39.4	SR
W26	9000	24.9	69.9	70.6	4.5	26.8	SR
W27	9000	12.9	54.8	64.6	1.1	39.6	SR
W28	10000	11.5	50.7	58.9	1.5	38.1	SR
W29	6000	9.8	34.4	34.0	1.1	45.4	HR
W30	7000	14.6	55.0	40.1	1.6	38.3	SR
W31	6000	9.5	32.5	35.9	1.2	44.8	HR
W32	7000	14.6	49.9	64.1	2.0	36.9	SR
W33	10000	16.9	64.5	66.3	2.4	33.1	SR
W34	7000	10.3	38.7	45.3	1.6	41.4	HR
W35	11000	12.1	61.3	78.4	1.5	35.8	SR
W36	10000	11.3	52.4	72.5	1.6	37.3	SR
W37	7000	9.6	35.6	45.0	1.1	44.6	HR
W38	9000	18.9	66.7	79.8	1.9	33.1	SR
W39	9000	18.9	66.7	79.8	1.9	33.1	SR
W40	10000	20.5	73.1	76.1	2.0	31.8	SR

W41	9000	17.8	64.5	65.9	2.4	33.3	SR
W42	7000	10.9	42.1	50.5	1.7	40.2	HR
W43	8000	10.5	47.3	64.5	1.7	39.3	SR
W44	9000	17.9	62.3	69.6	0.9	24.2	SR
W45	7000	16.4	49.8	49.3	2.0	36.8	SR
W46	11000	20.5	79.5	104.3	2.2	29.3	SR
W47	3620	10.0	25.8	32.5	3.0	42.0	HR
W48	9890	17.7	73.1	89.9	2.5	31.3	SR
W49	8940	8.4	37.2	40.9	13.4	26.1	SR
W50	9140	8.2	34.2	41.8	13.4	26.2	SR
W51	8670	8.2	34.1	41.9	13.5	26.5	SR
W52	8882	8.1	38.1	42.0	14.1	25.4	SR
W53	4240	8.8	26.1	41.1	2.7	42.8	HR
W54	3750	8.3	23.0	36.4	2.4	44.3	HR
W55	6967	10.7	40.2	67.5	4.4	35.3	SR
W56	6240	10.7	38.4	60.5	3.9	36.8	SR
W57	5584	14.6	55.0	40.1	1.6	39.0	SR
W58	5770	13.8	44.4	58.6	3.0	36.6	SR
W59	8270	19.0	70.6	87.3	3.6	30.0	SR
W60	5820	13.6	44.9	52.1	3.9	35.4	SR
W61	6120	15.0	56.3	73.0	2.6	35.4	SR
W62	7840	15.7	61.6	83.2	2.7	33.5	SR
W63	4360	3.1	9.0	43.2	1.3	53.8	HR
W64	7760	15.9	65.0	90.9	3.2	32.1	SR
W65	3420	10.1	24.7	29.5	3.9	40.7	HR
W66	6160	12.9	47.3	59.7	4.9	33.6	SR
W67	4820	12.6	38.5	52.9	2.0	39.7	SR
W68	5620	14.4	41.4	48.3	3.3	36.6	SR
W69	9031	11.1	30.1	33.8	1.9	40.3	HR
W70	4940	10.4	33.3	46.1	2.1	41.5	HR
W71	10290	17.9	73.1	84.1	2.6	31.2	SR
W72	11770	15.2	68.8	95.7	2.9	30.7	SR
W73	11800	18.9	86.0	104.4	2.9	28.0	SR
W74	6000	15.3	48.4	56.6	2.3	37.1	SR
W75	10540	18.7	77.4	92.8	2.4	30.4	SR
W76	8780	19.8	73.1	81.2	2.9	30.8	SR
W77	9470	17.5	66.7	78.3	2.5	32.4	SR
W78	9140	17.5	66.7	78.3	2.4	32.7	SR
W79	8390	16.6	60.2	78.3	2.3	33.9	SR

Table S5. Classification of water after desalination by all membranes based on USSL staff classification.

Well	Raw Water	M1	M2	M3	M4	M5
W1	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W2	C4S4	C1S1	C2S1	C1S4	C4S4	C3S3
W3	C4S4	C1S1	C2S1	C1S3	C4S4	C2S1
W4	C4S4	C1S1	C2S1	C1S3	C4S4	C3S2
W5	C4S4	C1S1	C2S1	C0S3	C4S4	C2S2
W6	C4S4	C1S1	C2S1	C1S3	C4S4	C3S2
W7	C4S3	C0S1	C1S1	C0S1	C4S2	C2S1
W8	C4S3	C0S1	C1S1	C0S2	C4S3	C2S1
W9	C4S3	C0S1	C1S1	C0S1	C4S3	C2S1
W10	C4S3	C0S1	C1S1	C0S2	C4S3	C2S1
W11	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W12	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W13	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W14	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W15	C4S2	C0S1	C1S1	C0S1	C4S2	C2S1
W16	C4S3	C0S1	C1S1	C0S1	C4S2	C2S1
W17	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W18	C4S3	C0S1	C1S1	C0S1	C4S3	C2S1
W19	C4S4	C0S1	C2S1	C0S3	C4S4	C2S2
W20	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W21	C4S4	C1S1	C2S1	C1S2	C4S4	C2S1
W22	C4S3	C0S1	C1S1	C0S1	C4S2	C2S1
W23	C4S3	C0S1	C1S1	C0S1	C4S2	C2S1
W24	C4S3	C0S1	C1S1	C0S1	C4S2	C2S1
W25	C4S4	C0S1	C1S1	C0S2	C4S4	C2S2
W26	C4S4	C0S1	C1S1	C0S4	C4S4	C2S2
W27	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W28	C4S4	C0S1	C2S1	C0S2	C4S4	C2S1
W29	C4S3	C0S1	C1S1	C0S2	C4S3	C2S1
W30	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W31	C4S3	C0S1	C1S1	C0S2	C4S3	C2S1
W32	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W33	C4S4	C0S1	C2S1	C0S3	C4S4	C2S2
W34	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W35	C4S4	C1S1	C2S1	C0S2	C4S4	C2S1
W36	C4S4	C0S1	C2S1	C0S2	C4S4	C2S1
W37	C4S3	C0S1	C1S1	C0S2	C4S3	C2S1
W38	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W39	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W40	C4S4	C0S1	C2S1	C0S3	C4S4	C2S2
W41	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2

W42	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W43	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W44	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W45	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W46	C4S4	C1S1	C2S1	C0S3	C4S4	C2S2
W47	C4S3	C0S1	C0S1	C0S2	C3S3	C1S1
W48	C4S4	C0S1	C2S1	C0S3	C4S4	C2S2
W49	C4S3	C0S1	C1S1	C0S1	C4S3	C2S1
W50	C4S3	C0S1	C1S1	C0S1	C4S3	C2S1
W51	C4S3	C0S1	C1S1	C0S1	C4S3	C2S1
W52	C4S3	C0S1	C1S1	C0S1	C4S3	C2S1
W53	C4S3	C0S1	C1S1	C0S1	C3S3	C1S1
W54	C4S3	C0S1	C0S1	C0S1	C3S2	C1S1
W55	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W56	C4S4	C0S1	C1S1	C0S2	C4S3	C2S1
W57	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W58	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W59	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W60	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W61	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W62	C4S4	C0S1	C1S1	C0S2	C4S4	C2S2
W63	C4S2	C0S1	C1S1	C0S1	C3S1	C1S1
W64	C4S4	C0S1	C1S1	C0S2	C4S4	C2S2
W65	C4S3	C0S1	C0S1	C0S2	C3S3	C1S1
W66	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W67	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W68	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W69	C4S4	C0S1	C1S1	C0S2	C4S4	C2S1
W70	C4S3	C0S1	C1S1	C0S2	C4S3	C2S1
W71	C4S4	C0S1	C2S1	C0S3	C4S4	C2S2
W72	C4S4	C1S1	C2S1	C0S2	C4S4	C2S1
W73	C4S4	C1S1	C2S1	C1S3	C4S4	C2S2
W74	C4S4	C0S1	C1S1	C0S2	C4S4	C2S2
W75	C4S4	C0S1	C2S1	C0S3	C4S4	C2S2
W76	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W77	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W78	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2
W79	C4S4	C0S1	C1S1	C0S3	C4S4	C2S2

Table S6. IWQI value after desalination for all membranes.

Well Name	Irrigation Water Quality Index (IWQI)						IWQI max	water class	best membrane
	Feed Water	M1	M2	M3	M4	M5			
W1	40.1	11.9	47.6	11.3	27.8	67.6	67.6	MR	M5
W2	14.6	45.6	62.3	44.2	5.8	15.8	62.3	MR	M2
W3	24.7	32.2	73.4	33.0	30.2	55.4	73.4	LR	M2
W4	26.1	47.3	70.0	45.6	12.8	48.5	70.0	LR	M2
W5	32.4	30.7	74.4	30.3	19.8	56.6	74.4	LR	M2
W6	27.4	46.0	70.8	44.6	14.0	49.3	70.8	LR	M2
W7	46.1	9.0	32.9	8.0	33.4	59.8	59.8	MR	M5
W8	42.4	9.6	33.1	9.1	30.6	71.1	71.1	LR	M5
W9	44.8	8.6	20.2	7.9	33.5	73.2	73.2	LR	M5
W10	43.7	9.8	34.1	9.0	30.4	71.1	71.1	LR	M5
W11	43.4	11.3	46.1	10.3	28.3	68.1	68.1	MR	M5
W12	41.0	10.8	47.9	10.2	29.1	69.2	69.2	MR	M5
W13	41.1	11.1	47.7	10.4	28.5	69.0	69.0	MR	M5
W14	41.1	11.0	62.8	10.3	28.9	69.5	69.5	MR	M5
W15	47.8	6.6	16.4	6.1	37.1	62.0	62.0	MR	M5
W16	46.0	7.6	18.1	7.0	35.3	60.6	60.6	MR	M5
W17	36.3	10.5	30.5	11.2	44.1	69.5	69.5	MR	M5
W18	42.9	9.9	47.1	9.2	30.7	71.3	71.3	LR	M5
W19	25.5	29.5	74.1	31.1	31.5	57.6	74.1	LR	M2
W20	26.9	25.6	59.2	26.2	33.3	57.7	59.2	MR	M2
W21	33.7	17.1	62.5	17.6	22.2	61.2	62.5	MR	M2
W22	46.1	7.8	18.4	7.1	34.7	60.5	60.5	MR	M5
W23	46.8	8.0	18.9	7.2	34.1	60.5	60.5	MR	M5
W24	46.5	8.0	19.0	7.2	34.2	60.4	60.4	MR	M5
W25	39.4	25.0	32.9	12.1	27.0	65.6	65.6	MR	M5
W26	26.8	25.3	58.8	25.6	33.4	56.9	58.8	MR	M2
W27	39.6	14.6	61.8	13.8	24.4	63.5	63.5	MR	M5
W28	38.1	13.7	62.5	13.1	25.0	65.6	65.6	MR	M5
W29	45.4	9.5	32.6	8.7	30.4	71.0	71.0	LR	M5
W30	38.3	25.5	34.2	24.9	26.3	64.8	64.8	MR	M5
W31	44.8	9.4	33.0	8.6	30.7	71.5	71.5	LR	M5
W32	36.9	26.8	45.9	26.4	25.9	63.7	63.7	MR	M5
W33	33.1	27.9	61.0	27.2	23.0	60.6	61.0	MR	M2
W34	41.4	11.0	47.8	10.3	28.7	69.0	69.0	MR	M5
W35	35.8	15.8	62.9	15.6	22.6	62.6	62.9	MR	M2
W36	37.3	14.5	62.6	14.1	24.3	64.5	64.5	MR	M5
W37	44.6	10.5	47.9	9.5	29.4	70.1	70.1	LR	M5

W38	33.1	27.4	60.0	27.1	21.4	57.9	60.0	MR	M2
W39	33.1	27.4	60.0	27.1	21.4	57.9	60.0	MR	M2
W40	31.8	27.2	73.1	26.7	20.3	56.8	73.1	LR	M2
W41	33.3	27.0	60.7	26.5	23.4	60.2	60.7	MR	M2
W42	40.2	11.7	47.6	11.1	27.9	67.7	67.7	MR	M5
W43	39.3	12.8	63.0	12.4	26.5	67.0	67.0	MR	M5
W44	24.2	27.0	60.1	26.0	22.1	59.8	60.1	MR	M2
W45	36.8	25.0	45.5	24.7	25.9	63.7	63.7	MR	M5
W46	29.3	29.6	71.8	42.3	18.4	53.0	71.8	LR	M2
W47	42.0	8.4	29.4	8.1	37.3	45.6	45.6	HR	M5
W48	31.3	29.5	74.5	29.4	21.2	57.0	74.5	LR	M2
W49	26.1	12.5	42.1	13.5	27.8	73.7	73.7	LR	M5
W50	26.2	12.5	54.5	13.4	28.0	74.0	74.0	LR	M5
W51	26.5	12.3	54.6	13.1	28.2	74.3	74.3	LR	M5
W52	25.4	12.6	54.9	9.5	26.0	74.3	74.3	LR	M5
W53	42.8	8.7	20.1	8.1	35.8	59.4	59.4	MR	M5
W54	44.3	7.8	18.0	7.2	37.0	59.5	59.5	MR	M5
W55	35.3	12.8	47.8	13.0	41.2	67.6	67.6	MR	M5
W56	36.8	12.0	46.8	11.9	43.4	68.5	68.5	MR	M5
W57	39.0	25.0	32.8	24.4	27.5	65.3	65.3	MR	M5
W58	36.6	13.6	44.7	13.1	29.2	65.5	65.5	MR	M5
W59	30.0	27.9	60.7	28.2	37.3	57.3	60.7	MR	M2
W60	35.4	13.1	45.3	12.9	42.9	66.0	66.0	MR	M5
W61	35.4	27.3	45.5	27.1	26.2	62.5	62.5	MR	M5
W62	33.5	28.5	47.3	28.4	24.5	60.2	60.2	MR	M5
W63	53.8	5.2	26.2	4.1	50.1	46.9	50.1	HR	M3
W64	32.1	29.1	47.5	29.3	25.0	59.3	59.3	MR	M5
W65	40.7	8.2	28.7	8.3	51.1	45.5	51.1	HR	M3
W66	33.6	13.5	46.3	14.0	40.0	65.9	65.9	MR	M5
W67	39.7	12.0	43.6	11.3	30.3	67.5	67.5	MR	M5
W68	36.6	25.1	44.3	12.6	30.6	66.5	66.5	MR	M5
W69	40.3	11.1	46.7	10.4	28.5	70.0	70.0	LR	M5
W70	41.5	10.3	44.9	9.7	31.9	70.4	70.4	LR	M5
W71	31.2	29.3	74.6	29.0	21.2	57.5	74.6	LR	M2
W72	30.7	18.9	61.7	31.5	21.8	57.6	61.7	MR	M2
W73	28.0	31.5	72.9	43.9	18.9	53.8	72.9	LR	M2
W74	37.1	25.6	44.8	25.4	26.8	64.3	64.3	MR	M5
W75	30.4	29.7	73.7	29.6	20.0	55.7	73.7	LR	M2
W76	30.8	27.4	73.8	27.4	22.2	56.9	73.8	LR	M2
W77	32.4	28.4	61.1	28.1	22.4	58.9	61.1	MR	M2
W78	32.7	28.2	61.2	28.0	22.5	59.0	61.2	MR	M2

W79	33.9	27.9	60.7	27.7	23.4	60.0	60.7	MR	M2
-----	------	------	------	------	------	------	------	----	----